

VX2776-4K-MHD - 27" 4K UHD THIN-BEZEL IPS MONITOR WITH HDMI AND DISPLAYPORT

Key Features


- 27 Inch 4K UHD (3840x2160p) IPS monitor with thin bezels and 60Hz refresh rate
- HDR10 content support for deep contrast, rich color, and vibrant details
- Optimized view settings offers "Game," "Movie," "Web," "Text," and "Mono" presets
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- The VX2776-4K-MHD supports laptops, PCs, and Macs with HDMI, and DisplayPort inputs



27
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description

Whether for office use or for enjoying entertainment at home, the ViewSonic® VX2776-4K-mhd is designed to take your viewing experience to another level. With a SuperClear® IPS panel and a sleek frameless design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Stunning 4K Ultra HD resolution delivers 4-times more pixels than Full HD monitors, which boosts efficiency and image detail needed for work or play. A mega dynamic contrast ratio of 80M:1 delivers enhanced image depth for a better user experience. Moreover, HDR10 content support delivers vivid colors and brightness that exceed standard monitors. Built-in HDMI and DisplayPort inputs deliver flexible connectivity options for a wide range of devices.

Specifications

More Information

UPC	766907995817
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED

Brightness	350 cd/m2
Colors	1.07B
Color Space Support	8-bit+Hi-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	4ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2.5W (x2)
Eco Mode (Conserve)	34W
Eco Mode (optimized)	39W
Consumption (typical)	44W
Consumption (max)	48W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 160 KHz
Frequency Vertical	40 ~ 75 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2)
Regulations	MX-CoC, Mexico Energy, CE, CE EMC, CB, Energy Star compliant
Net (lbs)	12.3
Net Without Stand (lbs)	11.0
Gross (lbs)	15.4
Net (kg)	5.6

Net Without Stand (kg)	5.0
Gross (kg)	7.0
Packaging (in.)	27.4 x 18.2 x 5.2
Physical (in.)	24.3 x 17.8 x 7.2
Physical Without Stand (in.)	24.3 x 14.4 x 1.8
Packaging (mm)	697.0 x 462.0 x 132.0
Physical (mm)	616.0 x 451.0 x 184.0
Physical Without Stand (mm)	616.0 x 366.0 x 46.0
Package Contents	VX2776-4K, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907995817



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com