





VX2768-2KPC-MHD - 27" OMNI CURVED 1440P 1MS 144HZ GAMING MONITOR WITH FREESYNC PREMIUM

Key Features


- Immersive Curved Screen Design
- 144Hz Refresh Rate
- Ultra-Fast Response Time
- AMD FreeSync™ Premium
- Wide Quad HD Resolution



27
DISPLAY



MVA
PANEL



2560 x 1440
RESOLUTION



Product Description

With an immersive 1500R curved screen and stunning WQHD 2560 x 1440 resolution, the ViewSonic® VX2768-2KPC-MHD monitor provides an incredible viewing experience for work or play. With features including a high 144Hz refresh rate, 1ms (MPRT) repsonse time and AMD FreeSync Premium technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX2768-2KPC-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v2.0) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment.

Specifications

More Information	
UPC	766907007701
Screen Size	27
Viewable Area (in.)	27
Panel Type	MVA
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED

Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit+FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	3ms
Response Time (MPRT)	1ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	144Hz
Adaptive Sync	AMD FreeSync™ Premium
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	36W
Eco Mode (optimized)	41W
Consumption (typical)	45W
Consumption (max)	60W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Key 1 (favorite); Key 2 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	30 ~ 255 KHz
Frequency Vertical	48 ~ 144 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2)
Tilt (Forward/Back)	3º / 21º

Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Net (lbs)	11.0
Net Without Stand (lbs)	9.6
Gross (lbs)	14.9
Net (kg)	5.0
Net Without Stand (kg)	4.4
Gross (kg)	6.8
Packaging (in.)	26.8 x 18.4 x 6.5
Physical (in.)	24.0 x 17.8 x 8.6
Physical Without Stand (in.)	24.0 x 14.5 x 3.1
Packaging (mm)	680.0 x 467.0 x 166.0
Physical (mm)	610.0 x 452.0 x 219.0
Physical Without Stand (mm)	610.0 x 367.0 x 78.0
Package Contents	VX2768-2KPC-MHD Display, 1 x Power Cable, 1 x DisplayPort Cable, 1 x Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
UPC: 766907007701	



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781 📞

email: salesinfo@viewsonic.com ✉️