


# VIEWSONIC 27" 4K UHD ERGONOMIC IPS DOCKING MONITOR WITH 90W USB-C, RJ45 | VG2756-4K

## Key Features


- Versatile Monitor: 27 Inch 4K (3840x2160p) IPS monitor with thin bezels and 60Hz refresh rate
- Ditch The Dock: Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 90W charging over one cable
- Ergonomic Stand: Advanced ergonomics (40-degree tilt, swivel, rotate and height) for all-day comfort
- Enhanced Viewing Comfort: Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Versatile Stand: Easy-to-install quick release stand with carrying handle and client mount
- Flexible Connectivity: The VG2756-4K supports PC, Mac and more with USB-C, RJ45, HDMI, DisplayPort, USB inputs



27  
DISPLAY



IPS  
PANEL



3840 x 2160  
RESOLUTION



## Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756-4K is a 27" 4K Ultra HD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity makes setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

## Specifications

### More Information

<b>UPC</b>	766907008555
<b>Screen Size</b>	27
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	3840 x 2160
<b>Display Resolution</b>	4K (3840x2160)
<b>Static Contrast Ratio</b>	1,000:1

<b>Dynamic Contrast Ratio</b>	50,000,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	350 cd/m <sup>2</sup>
<b>Colors</b>	1.07B
<b>Color Space Support</b>	8+2 bits
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	14ms
<b>Response Time (GTG w/OD)</b>	5ms
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-glare, Hard coating (3H)
<b>PC Resolution (max)</b>	3840 x 2160
<b>Mac® Resolution (max)</b>	3840 x 2160
<b>USB Type A</b>	2
<b>USB Type B</b>	1
<b>USB Type C</b>	90W x 1
<b>Ethernet LAN (RJ45)</b>	1
<b>HDMI 2.0 In</b>	2
<b>DisplayPort</b>	1
<b>Internal Speakers</b>	2W (x2)
<b>Eco Mode (Conserve)</b>	16.8W
<b>Eco Mode (optimized)</b>	21.2W
<b>Consumption (typical)</b>	30.7W
<b>Consumption (max)</b>	70.0W
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Power Supply</b>	Internal
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1,2,3,4,5,6 (Power)
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	15 ~ 150 KHz
<b>Frequency Vertical</b>	24 ~ 75 Hz

<b>Digital Sync</b>	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
<b>Height Adjust</b>	130 mm / 5.1 in
<b>Swivel</b>	120°
<b>Pivot (Right/Left)</b>	90° / 90°
<b>Tilt (Forward/Back)</b>	40° / 5°
<b>Regulations</b>	cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy
<b>Net (lbs)</b>	16.5
<b>Net Without Stand (lbs)</b>	11.2
<b>Gross (lbs)</b>	23.6
<b>Net (kg)</b>	7.5
<b>Net Without Stand (kg)</b>	5.1
<b>Gross (kg)</b>	10.7
<b>Packaging (in.)</b>	27.2 x 8.6 x 16.9
<b>Physical (in.)</b>	24.1 x 16.0 x 8.0
<b>Physical Without Stand (in.)</b>	24.1 x 14.3 x 2.0
<b>Packaging (mm)</b>	692.0 x 218.0 x 430.0
<b>Physical (mm)</b>	613.0 x 406.0 x 202.0
<b>Physical Without Stand (mm)</b>	613.0 x 363.0 x 52.0
<b>Package Contents</b>	VG2756-4K x1, 3-pin Plug x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	Three-year limited warranty on parts, labor and backlight

UPC: 766907008555



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)