


## VIEWSONIC 6,000 LUMENS WUXGA SHORT THROW LASER PROJECTOR W PORTRAIT MODE AND DUAL HDMI | LS921WU

### Key Features

---


- Short Throw Laser Projector: WUXGA (1920x1200p) resolution with a 0.8 throw ratio and 6,000 ANSI lumens for bright, detailed images in compact spaces
- Vibrant Colors & HDR Support: SuperColor technology and HDR/HGL compatibility deliver a wide color gamut with enhanced contrast and visual depth
- Golf Mode for Realistic Simulation: Designed for immersive play, Golf Mode supports major golf simulators for lifelike play on world-class virtual courses
- Designed for Fast Paced Content: A low 16ms input latency and 120Hz refresh rate provides faster frame-by-frame action for smooth images with minimal delay
- Large Screen Projection: Projects screen sizes from 30" to 200" with a throw distance of 3.4 ft - 11.5 ft; displays a 100" image from 5.7 ft
- Easy Setup & Image Adjustment: 1.1x optical zoom, 0.8x-2.0x digital zoom, H/V keystone, 360-degree projection, portrait mode, and 4-corner adjustment
- Advanced LAN Control: Remotely schedule and manage the projector via Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic vController
- Installation Options: This projector is ceiling mountable; compatible with ViewSonic mount PJ-WMK-007



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



3840 x 2160  
**RESOLUTION**



**INSTALLATION FLEXIBILITY  
WITH WIDE H/V LENS SHIFT**

### Product Description

---

Bright and versatile for any professional installation, the ViewSonic® LS921WU WUXGA short throw laser projector delivers everything you need for big screens in big venues. Delivering 6,000 ANSI lumens of advanced high brightness, up to 20,000 hours\* of light source life, and a screen size of up to 200", this projector is ideal for auditoriums, restaurants, gyms and other large venues. This top-notch performer is also easy to deploy and manage with its short-throw lens, 1.1x optical zoom adjustment, wide lens shift, 360° projection, and portrait mode that provide extreme flexibility in even the most challenging installations. Dual HDMI 2.0b / HDCP 2.2 ports ensure access to original 4K quality content with HDR/HLG support. In addition, its compact size and built-in HDBaseT deliver the perfect mix of high-quality projection and cost-effectiveness. \*Light source life may vary based on actual usage and other factors.

# Specifications

|                                   | More Information                               |
|-----------------------------------|------------------------------------------------|
| UPC                               | 766907008739                                   |
| Light Source                      | Laser                                          |
| Display Resolution                | WUXGA (1920x1200)                              |
| Display Resolution                | 1920 x 1200                                    |
| Brightness (Lumens)               | 6,000 ANSI                                     |
| Screen Size                       | 30 - 300 in. / 0.76 - 7.62 m                   |
| Throw Distance                    | 1.04-3.83m (100"@1.74m)                        |
| Throw Ratio                       | 0.81-0.89                                      |
| Keystone                          | Vertical (+/- 40º) / Horizontal (+/- 40º)      |
| Lens                              | 1.1x optical zoom                              |
| Light Source (watt)               | Nichia 74W x 2                                 |
| Light Source Life, Normal (hours) | 20000                                          |
| Color Depth                       | 1.07 Billion Colors                            |
| Dynamic Contrast Ratio            | 3,000,000:1                                    |
| Aspect Ratio                      | 16:10                                          |
| Input Lag                         | 37ms                                           |
| Lens Shift                        | Horizontal (50%, -50%) / Vertical (+23%, -23%) |
| Frequency Horizontal              | 15K~135KHz                                     |
| Frequency Vertical                | 23-120Hz                                       |
| PC Resolution (max)               | 3840 x 2160                                    |
| PC Resolution (min)               | 640 x 480                                      |
| Mac® Resolution (max)             | 3840 x 2160                                    |
| Mac® Resolution (min)             | 640 x 480                                      |
| USB 2.0 Type A                    | 1                                              |
| Ethernet LAN (RJ45)               | 1                                              |
| 3.5mm 12V Trigger                 | 1                                              |
| 3.5mm Audio Out                   | 1                                              |
| 3.5mm Audio In                    | 1                                              |
| Control (RS232)                   | 1                                              |
| HDMI 2.0 (with HDCP 2.2)          | 2                                              |
| VGA In                            | 1                                              |
| VGA Out                           | 1                                              |
| Composite RCA Video In            | 1                                              |

|                              |                                                                                                                                                                                                         |
|------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>RCA Audio In (L/R)</b>    | 1                                                                                                                                                                                                       |
| <b>3D VESA</b>               | 1                                                                                                                                                                                                       |
| <b>HDBT</b>                  | 1                                                                                                                                                                                                       |
| <b>Internal Speakers</b>     | 10W (x2)                                                                                                                                                                                                |
| <b>Voltage</b>               | 100-120V+/- 10%, 50/60Hz                                                                                                                                                                                |
| <b>Consumption (typical)</b> | 450W                                                                                                                                                                                                    |
| <b>Stand-by</b>              | <0.5W                                                                                                                                                                                                   |
| <b>Physical Controls</b>     | Keypad, Power key                                                                                                                                                                                       |
| <b>On Screen Display</b>     | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)                                                                                      |
| <b>Temperature</b>           | 32-104° F (0 - 40° C)                                                                                                                                                                                   |
| <b>Kensington Lock Slot</b>  | 1                                                                                                                                                                                                       |
| <b>Net (lbs)</b>             | 14.3                                                                                                                                                                                                    |
| <b>Gross (lbs)</b>           | 19.8                                                                                                                                                                                                    |
| <b>Net (kg)</b>              | 6.5                                                                                                                                                                                                     |
| <b>Gross (kg)</b>            | 9.0                                                                                                                                                                                                     |
| <b>Packaging (in.)</b>       | 20.3 x 19.3 x 10.9                                                                                                                                                                                      |
| <b>Physical (in.)</b>        | 15.9 x 12.0 x 5.7                                                                                                                                                                                       |
| <b>Packaging (mm)</b>        | 515.0 x 490.0 x 276.0                                                                                                                                                                                   |
| <b>Physical (mm)</b>         | 405.0 x 305.0 x 145.0                                                                                                                                                                                   |
| <b>Regulations</b>           | cTUVus                                                                                                                                                                                                  |
| <b>Package Contents</b>      | LS921WU projector, power cable, remote control, Quick Start Guide                                                                                                                                       |
| <b>Warranty</b>              | Five-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| <b>Recycle/Disposal</b>      | Please dispose of in accordance with local, state or federal laws.                                                                                                                                      |

UPC: 766907008739



**Contact Sales**  
**[ViewSonic.com](http://ViewSonic.com)**

888.881.8781  
email:  
[salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)