

27" Fast Action 165Hz Gaming Monitor

XG2703-GS



The ViewSonic® XG2703-GS is the ideal display for hardcore gamers who always crank their graphics settings to Ultra, rendering every frame your GPU can output in breathtaking detail. Featuring an incredible 165Hz refresh rate, as well as NVIDIA's G-Sync Technology*, this monitor's variable refresh rate capabilities virtually eliminate screen tearing and stuttering for unbelievably fluid gameplay during fast-paced action sequences. A juggernaut of cutting-edge display technology, this monitor features a 2560x1440 WQHD SuperClear® IPS-type panel for enhanced color accuracy and greater viewing angles. A quick response time lets you seize control of the action, while a low input lag provides smooth screen performance even in the most graphic-intensive sequences. For a game-winning competitive edge, a Game Mode featured optimizes visuals for FPS, RTS and MOBA. On top of that, a dark color enhancement function help you target enemies lurking in the dark, while the monitor maintains brilliantly rich colors and contrast. With a gamer-inspired ergonomic stand that features an integrated headphone hook and cable management functionality, the XG2703-GS has all you need to conquer your gaming quests.

Key Features:

WQHD Resolution
165Hz refresh rate*
SuperClear® IPS-type panel technology
NVIDIA G-SYNC technology
NVIDIA Ultra Low Motion Blur technology

Designed for:

Gaming
Entertainment

27" Fast Action 165Hz Gaming Monitor

XG2703-GS

Specifications

LCD	Size	27" (16:9)
	Panel Technology	IPS Technology
	Display Area	27"(596.74 x 335.66)
	Optimum Resolution	2560x1440 (WQHD)
	Brightness	350 cd/m ²
	Contrast Ratio	1000 :1 (Typ.)
	Dynamic Contrast Ratio	120,000,000 :1
	Viewing Angle	178° (H) / 178° (V)
	Response Time	4ms (GTG) in OD
	Panel Surface	Anti-Glare type, Hard-coating (3H)
	Light Source	30000 Hrs (Min.)
	Colours	16.7 M
INPUT	Digital	HDMI/DisplayPort
	Frequency	Fh = 15 ~ 140 kHz ; Fv = 24 ~ 138 Hz for HDMI Fh = 34 ~ 209 kHz ; Fv = 30 ~ 165 Hz for DP
COMPATIBILITY	Sync	TMDS
	PC	2560x1440 @ 144Hz (Overclocking to 165Hz)
CONNECTOR	Mac®	2560x1440 @ 144Hz (Overclocking to 165Hz)
	Digital	HDMI 1.4 x1 / DisplayPort 1.2a x1
AUDIO	Audio Out	3.5mm jack x1
	USB	4Port (up stream x1 / downstream x4 / USB 3.0 x2 / USB 2.0 x2)
	Power	External Power Adapter
POWER	Speaker	2W x2
	Voltage	AC 100-240V (Universal); 50/60 Hz
ERGONOMICS	Consumption	48W; Optimize: 40W; Conserve: 34W
	Save mode	≤0.5 W
OPERATING CONDITIONS	Tilt	15° ~ -5°
	Swivel	175° / 175°
	Rotation	90°
	Height Adjust	0 ~ 100 mm
DIMENSIONS	Temperature	32°F to 104°F (0°C to 40°C)
	Humidity	20% to 90% (no condensation)
WEIGHT	Physical with stand	624.4 (W) x 532.4 (H) x 250.4 (D)
REGULATIONS	Net with stand	7kg
WALL MOUNT	VESA	100x100mm
PACKAGE CONTENTS		LCD Display / AC/DC Adapter / Power Cable / DisplayPort Cable / USB3.0 Cable / Quick Start Guide