

PRODUCT REFERENCE GUIDE:

COMMERCIAL DISPLAYS

Connect and Collaborate.



IFP - ViewBoard Interactive Series: Connect, Collaborate, Share

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
IFP8650	86"	3840 x 2160	800 x 600 mm 16W (x2)	87.0 x 53.1 x 11.0	350 cd/m2	8ms	HDMI 1.4(x2), HDMI 2.0, HDMI Out, VGA, Display Port, Composite RCA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x3), Slot-in PC Slot, USB 3.0(x3), USB B Touch Port(x2), RS232 In, Ethernet LAN (RJ45), WIFI Module Slot, Expansion Slot
IFP7500	75"	3840 x 2160	400 x 600 mm 20W (x2)	78.35 x 51.77 x 13.78	450 cd/m2	8ms	HDMI(x4), VGA, YPbPr, Composite RCA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x2), OPS PC Slot, USB 2.0 OPS passthrough(x2), USB B Touch Port, RS232 In, RS232 Out, Ethernet LAN (RJ45), SDM Slot
IFP7550	75"	3840 x 2160	400 x 600 mm 16W (x2)	75.3 x 48.2 x 11.0	350 cd/m2	8ms	HDMI 1.4(x2), HDMI 2.0, HDMI Out, VGA, Display Port, Composite RCA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x3), Slot-in PC Slot, USB B Touch Port(x2), RS232 In, Ethernet LAN (RJ45), WIFI Module Slot, Expansion Slot
IFP6550	65"	3840 x 2160	400 x 600 mm 16W (x2)	66.81 x 42.17 x 8.66	350 cd/m2	8ms	HDMI 1.4(x2), HDMI 2.0, HDMI Out, VGA, Display Port, Composite RCA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x3), Slot-in PC Slot, USB 3.0(x3), USB B Touch Port(x2), RS232 In, Ethernet LAN (RJ45), WIFI Module Slot, Expansion Slot

CDE - Value Series: Large Format, Affordable Price

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
CDE8452T	84"	3840 x 2160	600 x 600 mm 10-watt (x2)	85.4 x 53.9 x 12.6	350 cd/m2	8ms	HDMI(x3), 4K2K HDMI, VGA Out, RCA Audio In(x3), RCA Audio Out, SPDIF Audio Out, USB 2.0(x3), Ethernet LAN (RJ45)
CDE7500	75"	3840 x 2160	400 x 600 mm 10W (x2)	78.35 x 51.77 x 13.78	450 cd/m2	8ms	HDMI(x4), HDMI Out, VGA, YPbPr, Composite RCA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x2), RS232 In, RS232 Out, Ethernet LAN (RJ45)
CDE7561T	75"	1920 x 1080	400 x 400 mm 10W (x2)	72.2 x 45.9 x 11	350 cd/m2	6ms	HDMI(x3), VGA Out, 3.5mm Audio In(x2), 3.5mm Audio Out(x2), USB 2.0(x2), RS232, Ethernet LAN (RJ45)
CDE7061T	70"	1920 x 1080	600 x 400 mm 10W (x2)	71.0 x 44.6 x 9.6	350 cd/m2	5ms	HDMI(x3), VGA(x3), VGA Out, RCA Audio In(x3), 3.5mm Audio Out, SPDIF, USB 2.0(x3), RS232, CVBS, Ethernet LAN (RJ45)
CDE6502	65"	1920 x 1080	400 x 400 mm 10W (x2)	63.7 x 40.8 x 8.8	350 cd/m2	8ms	HDMI, HDMI MHL, VGA, USB 2.0
CDE6561T	65"	1920 x 1080	600 x 400 mm 10-watt (x2)	66.8 x 42.2 x 8.7	350 cd/m2	8ms	HDMI(x3), VGA(x3), VGA Out, RCA Audio In(x3), 3.5mm Audio Out, SPDIF Audio Out, USB 2.0(x3), RS232 In, Ethernet LAN (RJ45)
CDE5502	55"	1920 x 1080	200 x 400 / 400 x 400 mm 10W (x2)	53.7 x 29.6 x 7.3	350 cd/m2	9ms	HDMI(x2), VGA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out
CDE5561T	55"	1920 x 1080	400 x 400 mm 10-watt (x2)	57.4 x 36.7 x 8.7	350 cd/m2	8ms	HDMI(x3), VGA, RCA Audio In(x3), SPDIF, USB 2.0(x3), RS232, CVBS, Ethernet LAN (RJ45)
CDE4803	48"	1920 x 1080	400 x 400 / 200 x 200 mm 10W (x2)	-	350 cd/m2	8ms	HDMI(x2), VGA, RCA Audio In, RCA Audio Out, USB 2.0
CDE4803-H	48"	1920 x 1080	400 x 400 / 200 x 200 mm	46.93" x 30.43" x 6.73"	350 cd/m2	8ms	HDMI(x2), VGA, SPDIF Audio Out, USB 2.0, RS232 In, HDBaseT (RJ45)
CDE4302	43"	1920 x 1080	400 x 400 / 200 x 200 mm 10W (x2)	42.1 x 27.4 x 6.3	350 cd/m2	8ms	HDMI(x2), VGA, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out
CDE3203	32"	1920 x 1080	10W (x2)	31.3 x 19.8 x 4.8 in.	320 cd/m2	8ms	HDMI 1.4(x2), DVI-D, VGA, YPbPr, 3.5mm Audio In, 3.5mm Audio Out, SPDIF Audio Out, SPDIF, USB 2.0, RS232 In, IR out
CDE3204	32"	1920 x 1080	200 x 200 mm 10W (x2)	54.01 x 37.48 x 8.78	350 cd/m2	8ms	HDMI 1.4(x2), DVI-D, VGA, YPbPr, 3.5mm Audio In, 3.5mm Audio Out, SPDIF, USB 2.0, RS232 In, IR out

CDP - Professional Series: 24/7 Reliability

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
CDP9800	98"	3840 x 2160	800 x 500 mm 10W (x2)	98.5 x 61.8 x 17.7	500 cd/m2	11ms	HDMI(x3), VGA, RCA Audio In, 3.5mm Audio In, 3.5mm Audio Out, RS232 In, RS232 Out, Ethernet LAN (RJ45)

CDX - Custom Series: High-impact Messaging

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
CDX5552	55"	1920 x 1080	400 x 400 mm 10W (x2)	61.1 x 37.8 x 17.7	500 cd/m2	12ms	HDMI 1.4(x2), DVI-D Out, VGA, Display Port, Display Port Out, YPbPr, Composite RCA, RCA Audio In, RCA Audio Out, USB 2.0, RS232 In, RS232 Out, Ethernet LAN (RJ45)
CDX4952	49"	1920 x 1080	400 x 400 mm 10W (x2)	53.8 x 35.3 x 14.4	450 cd/m2	12ms	HDMI 1.4(x2), DVI-D Out, VGA, Display Port, Display Port Out, YPbPr, Composite RCA, RCA Audio In, RCA Audio Out, USB 2.0, RS232 In, RS232 Out, Ethernet LAN (RJ45)

CDM - Commercial Grade Series: All-in-One Commercial Displays

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
CDM5500R	55"	1920 x 1080	400 x 400 mm 10W (x2)	54.0 x 37.4 x 8.7	450 cd/m2	12ms	HDMI 1.4(x2), DVI-I, DVI-I Out, Display Port, Display Port Out, RCA Audio In, RCA Audio Out, Speaker Out(x2), USB 2.0(x2), RS232 In, RS232 Out, Ethernet LAN (RJ45), SD Card Reader
CDM5500T	55"	1920 x 1080	400 x 400 mm 10W (x2)	54.0 x 37.4 x 8.7	450 cd/m2	12ms	HDMI 1.4(x2), DVI-I, DVI-I Out, Display Port, Display Port Out, 3.5mm Audio In, 3.5mm Audio Out, Speaker Out(x2), USB 2.0(x2), RS232 In, RS232 Out, Ethernet LAN (RJ45)
CDM4900R	49"	1920 x 1080	400 x 400 mm 10W (x2)	50.8 x 34.7 x 7.99	450 cd/m2	12ms	HDMI 1.4(x2), DVI-I, DVI-I Out, Display Port, Display Port Out, RCA Audio In, RCA Audio Out, Speaker Out(x2), USB 2.0(x2), RS232 In, RS232 Out, Ethernet LAN (RJ45), SD Card Reader
CDM4300R	43"	1920 x 1080	400 x 400 mm 10W (x2)	44.9 x 30.6 x 7.99	450 cd/m2	12ms	HDMI 1.4(x2), DVI-I, DVI-I Out, Display Port, Display Port Out, RCA Audio In, RCA Audio Out, Speaker Out(x2), USB 2.0(x2), RS232 In, RS232 Out, Ethernet LAN (RJ45), SD Card Reader

ePoster Series: Digital Kiosks & Billboards

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
EP5520	55"	1920 x 1080	10W (x2)	38.7x79.3x24.3	400 cd/m2	8ms	3.5mm Audio In, Ethernet LAN (RJ45), HDMI 1.4(x2), VGA, Control (RS232), USB 2.0 Type A(x3), USB 2.0 Type B

Product	Screen Size	Resolution	VESA Compatible Mount / Speakers	Dimensions W x H x D (in.)	Brightness Contrast	Video Response	Connectivity
EP5520T	55"	1920 x 1080	10W (x2)	38.7 x 79.3 x 24.3	400 cd/m2	8ms	3.5mm Audio In, Ethernet LAN (RJ45), HDMI 1.4(x2), VGA, Control (RS232), USB 2.0 Type A(x3), USB 2.0 Type B
EP4220	42"	1920 x 1080	2.5W (x2)	76.7 x 32.2 x 21.2	350 cd/m2	6.5ms	3.5mm Audio In, HDMI, Ethernet LAN (RJ45), VGA, Control (RS232), USB 2.0 Type A
EP1042T	10"	1280 x 800	75 x 75 mm 1W (x2)	13.2 x 3.9 x 8.9	300 cd/m2	25ms	3.5mm Audio In, HDMI Out, Micro USB

Network Media Players: Stream & Deliver

Product	Player Type	Processor	Graphics	RAM Internal Memory	Operating System	Network	Dimensions W x H x D (in./mm)
NMP-302W	Media Player	Rockchip RK3188	-	-	Android™ 4.4	10/100 BASE-T	4.2 x 1.0 x 2.7 in. / 107 x 25.3 x 68 mm
NMP-302WX	Media Player	Rockchip RK3188	-	8GB	Android™ 4.4	-	-
NMP012	Video Wall Player	Sigma Design ARM	-	-	Linux	-	-
NMP250-EL	Solstice Pod	Qualcomm Snapdragon™ S805, Krait 450	-	-	Android™ 5.1	-	-
NMP250-EU	Solstice Pod	Qualcomm Snapdragon™ S805, Krait 450	-	-	Android™ 5.1	-	-
NMP250-WL	Solstice Pod	Qualcomm Snapdragon™ S805, Krait 450	-	2GB	Android™ 5.1	-	-
NMP250-WU	Solstice Pod	Qualcomm Snapdragon™ S805, Krait 450	-	-	Android™ 5.1	-	-
NMP580-W	Media Player	Rockchip RK3188	Video In: HDMI 1.4 (720p), VGA	-	Android™ 4.4	10/100 BASE-T	5.45 x 5.04 x 1.19 in. / 138.6 x 128.1 x 30.2 mm
NMP711-P10	Slot-in PC	Intel® Core i5	-	4GB	Windows® 10 Pro 64 bit	-	-
NMP712-N	Slot-in PC	Intel® Core™ i7-4790S	-	8GB	FreeDOS	-	-