




VP2788-5K - 27" COLORPRO 5K MAC-COMPATIBLE MONITOR WITH 100W THUNDERBOLT 4, USB C, AND DCI-P3 COLOR GAMUT


Key Features



27
DISPLAY



IPS
PANEL



5120 x 2880
RESOLUTION



Product Description

Elevate your MacBook experience with the powerful ViewSonic® ColorPro® VP2788-5K, a sleek 27" monitor designed to integrate seamlessly into your Mac ecosystem. Featuring stunning 5K resolution and a 99% DCI-P3 color gamut, it provides vibrant and precise visuals to complement Apple’s renowned color performance. Seamless Thunderbolt 4 connectivity provides ultra-fast data transfer and up to 100W charging through a single cable, while also supporting daisy chaining of up to two 5K monitors for a seamless multi-display setup. Additional HDMI and DisplayPort options offer unmatched flexibility for various devices. In addition, an integrated USB-C and USB-A hub allows for connecting accessories and quick charging of your iPhone or iPad. A fully ergonomic stand allows you to customize height, tilt, and swivel for maximum comfort during long hours of use. Whether you're designing, editing, or enjoying media, this monitor’s exceptional performance transforms your workspace into a powerhouse of productivity with immersive visuals.

Specifications

	More Information
UPC	766907034998
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	5120 x 2880
Display Resolution	5K (5120 x 2880)
Static Contrast Ratio	2,000:1
Light Source	LED
Brightness	500 cd/m2
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	16:9

Response Time (Typical GTG)	14ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare, Low-Reflection, 48% Haze
Refresh Rate	75Hz
PC Resolution (max)	5120 x 2880
Mac® Resolution (max)	5120 x 2880
USB Type A	2
USB Type C	2 [1 upstream (15W) / 1 downstream (15W)]
HDMI 2.1 In	1
DisplayPort	1
Thunderbolt 4	2 [1 upstream(100W) / 1 downstream (15W)]
Internal Speakers	5W (x2)
Eco Mode (Conserve)	232 w/Audio/USB; 37 w/o Audio/USB
Eco Mode (optimized)	236 w/Audio/USB; 41 w/o Audio/USB
Consumption (typical)	242 w/Audio/USB; 47 w/o Audio/USB
Consumption (max)	245 w/Audio/USB; 50 w/o Audio/USB
Voltage	100-240 VAC
Stand-by	0.5
Power Supply	External
Cable Organization	No
Physical Controls	Joystick key: Up, Right, Down, Left, Center; Power
On Screen Display	Input Select, Color Mode, ViewMode, Audio Adjust, Setup Menu
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Height Adjust	120 mm / 4.7 in
Swivel	60º
Pivot (Right/Left)	90º / 90º
Tilt (Forward/Back)	5º / 22º
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC
Net (lbs)	14.0
Net Without Stand (lbs)	9.3
Gross (lbs)	23.4
Net (kg)	6.4
Net Without Stand (kg)	4.2

Gross (kg)	10.6
Packaging (in.)	28.7 x 20.3 x 6.3
Physical (in.)	24.13 x 16.72~21.44 x 8.26
Physical Without Stand (in.)	24.13 x 14.46 x 2.26
Packaging (mm)	730.0 x 515.0 x 159.0
Physical (mm)	612.94 x 424.73~544.55 x 209.91
Physical Without Stand (mm)	612.94 x 367.23 x 57.5
Package Contents	VP2788-5K x1, 3-pin Plug (IEC C13 / CEE22) x1, DisplayPort Cable (v1.4; Male-Male) x1, HDMI Cable (v2.1; Male-Male) x1, TBT4 Cable (Male-Male) x1, USB Type-C to Type-A 3.2 Gen2 Cable (Male-Male) x1, AC/DC Adapter x1, Quick Start Guide x1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907034998



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email: salesinfo@viewsonic.com