



VX2728J-2K - 27" 1440P 0.5MS 180HZ GAMING MONITOR WITH IPS, ADVANCED ERGONOMICS, FREESYNC PREMIUM, AND G-SYNC COMPATIBLE

Key Features



27"
DISPLAY



IPS
PANEL



2560 X 1440
RESOLUTION



GREAT VISUALS
For home entertainment and gaming



Product Description


The ViewSonic™ VX2728J-2K is a 27" QHD IPS gaming monitor built for gaming and entertainment. Featuring a 180Hz refresh rate and AMD FreeSync Premium technology, this monitor virtually eliminates screen tearing and stuttering for fluid game play during fast-paced action scenes. An ultra-fast 0.5ms (MPRT) response time also provides smooth screen performance free from blurring or ghosting. A fully adjustable ergonomic stand and a three-sided borderless design maximizes viewing size and an optimized set-up while minimizing frame distractions. Flexible connectivity options such as DisplayPort and HDMI allow you to connect to your dedicated graphics card and gaming console. The VX2728J-2K features all the perks needed to dominate your gaming and entertainment quests.

*180Hz refresh rate with DisplayPort

Specifications

	More Information
UPC	766907023169
Monitor Series	OMNI Gaming
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	1.07B
Color Space Support	10 bit (8 bit + FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	2.5ms
Response Time (MPRT)	0.5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	180Hz
Adaptive Sync	NVIDIA G-Sync Compatible
PC Resolution (max)	2560 X 1440
Mac® Resolution (max)	2560 X 1440
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	25W
Eco Mode (optimized)	29W
Consumption (typical)	34W
Consumption (max)	38W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3

Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
Frequency Horizontal	HDMI (v2.0): 30 ~ 218 KHz DisplayPort: 30 ~ 243 KHz
Frequency Vertical	HDMI (v2.0): 48 ~ 144 Hz DisplayPort: 48 ~ 165 Hz
Height Adjust	130 mm / 5.1 in
Swivel	30°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC, NRCan
Net (lbs)	10.4
Net Without Stand (lbs)	8.0
Gross (lbs)	14.3
Net (kg)	4.7
Net Without Stand (kg)	3.7
Gross (kg)	6.5
Packaging (in.)	26.8 x 18.1 x 6.8
Physical (in.)	24.2 x 17.24~22.36 x 8.1
Physical Without Stand (in.)	24.2 x 14.3 x 1.8
Packaging (mm)	680.0 x 460.0 x 173.0
Physical (mm)	615.0 x 438.0~568.0 x 207.0
Physical Without Stand (mm)	615.0 x 364.0 x 46.0
Package Contents	VX2728J-2K Display, Power Cable, Power Adapter, DisplayPort Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
UPC: 766907023169	



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email: salesinfo@viewsonic.com