
VIEWSONIC 15.6" 1080P PCAP TOUCH MONITOR WITH 24/7 OPERATION, VGA, HDMI, DISPLAYPORT | TD1601-XF


Key **Features**

• VERSATILE TOUCH MONITOR: 16 inch Full HD (1920x1080p) IPS open-frame display built for commercial integration with thin bezels and a 60Hz refresh rate.
• PCAP TOUCH TECHNOLOGY: Projected Capacitive (PCAP) technology delivers a smooth, accurate touch experience with every tap, pinch and swipe.
• EXTENDED 24/7 FUNCTIONALITY: Rated for 24/7 continuous operation with an advanced cooling system and burn-in prevention for graphics-rich content.
• ADVANCED DURABILITY: 3mm-thick glass with 7H hardness resists scratches and hard knocks while IP65-rated sealing keeps out dust, splashes and moisture.
• OPEN FRAME DESIGN: 75x75mm and 100x100mm mounting options enable secure installation in portrait or landscape modes.
• FLEXIBLE CONNECTIVITY: VGA, HDMI and DisplayPort inputs support a wide range of commercial deployments and source devices.







16"
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product **Description**

The ViewSonic TD1601-XF is a 15.6-inch open-frame touch monitor purpose-built for commercial integration in kiosks, ATMs, vending machines and food service environments. IP65-rated sealing protects against dust, splashes and moisture, backed by 24/7 continuous operation so deployments stay up and running around the clock. PCAP touch technology with 10-point touch delivers accurate, responsive performance across food service and industrial installations. With VGA, HDMI and DisplayPort inputs and flexible 75x75mm and 100x100mm VESA mounting, the TD1601-XF is designed to integrate cleanly into virtually any commercial setup.

Specifications

More Information

UPC	766907029932
Screen Size	16"
Viewable Area (in.)	15.6
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	800:1
Light Source	LED
Brightness	187 cd/m2
Colors	262K
Aspect Ratio	16:9
Response Time (Typical GTG)	30ms
Viewing Angles	170º horizontal, 170º vertical
Backlight Life (Hours)	15,000
Panel Surface	7H Scratch Resistant Surface Hardness
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
USB Type B	1
3.5mm Audio In	1
HDMI In	1
VGA	1
DisplayPort	1
Touch Technology	Projective Capacitive
Touch Points	PCT10 points touch supported
Consumption (typical)	7.14 W
Consumption (max)	9W
Voltage	AC-DC power (Input: 100V~240V / Output: DC 12V, 4.0 A)
Stand-by	1.69W
Power Supply	External
Cable Organization	No
Physical Controls	Auto, Menu, Left, Right, Exit, Power
On Screen Display	Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Reset
Temperature	32-122º F (0–50º C)
Humidity (non-condensing)	5-90%
VESA Compatible	75 x 75 / 100 x 100 mm
Net (lbs)	5.5 lbs

Gross (lbs)	8.4 lbs
Net (kg)	2.5 kg
Gross (kg)	3.8 kg
Packaging (in.)	18.31 x 13.19 x 5.12 in.
Physical Without Stand (in.)	15.39 x 9.49 x 1.38 in
Packaging (mm)	465 x 335 x 130 mm
Physical Without Stand (mm)	390.8 x 241.1 x 35 mm
Package Contents	USB A/B cable x 1, HDMI cable x 1, AC/DC adapter x 1, 3-pin power cord x 1, Quick Start Guide x 1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907029932







Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com