



VX2476-SMHD - 24" 1080P THIN-BEZEL IPS MONITOR WITH FREESYNC, HDMI, DISPLAYPORT, AND VGA


Key Features




What's in the box.



24"
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



*Power Cable varies by region



Product Description

Style and substance go hand-in-hand with the ViewSonic® VX2476-smhd 24" (23.8" viewable area) Full HD monitor. SuperClear® IPS panel technology, wide viewing angles, and best-in-class screen performance deliver outstanding visual clarity great for vibrant entertainment and gaming. A premium ID includes an ultra-slim profile, unique desktop stand, and a sleek edge-to-edge frameless screen, that when combined with vivid 1920x1080 resolution and dual speakers, deliver an immersive viewing experience for home entertainment and multimedia applications. Versatile HDMI, DisplayPort, and VGA inputs keep you connected to your favorite devices, while the modern, flush-mount frameless bezel design makes a standout statement in any home.

Specifications

	More Information
UPC	766907895216
Screen Size	24"
Viewable Area (in.)	23.8
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	80M:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	13W
Eco Mode (optimized)	15W
Consumption (typical)	18W
Consumption (max)	24W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power

On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	75 x 75 mm
Frequency Horizontal	Analog: 24 ~ 85KHz. Digital: 24 ~ 125KHz
Frequency Vertical	Analog: 48 ~ 75Hz. Digital: 48 ~ 100Hz
Analog Sync	Separate Sync, Composite Sync, SOG Sync
Digital Sync	TMDS, PCI-E
Tilt (Forward/Back)	17° / 5°
Regulations	cULus, FCC-B, ICES-003, EPEAT, Energy Star 7.0, NRCAN, UL-MXCoC, Mexico Energy, CE, WEEE, EEL, EAC
Net (lbs)	6.55
Net Without Stand (lbs)	5.58
Gross (lbs)	9.92
Net (kg)	2.97
Net Without Stand (kg)	2.53
Gross (kg)	4.5
Packaging (in.)	23.8 x 15.6 x 4.5
Physical (in.)	21.3 x 16.3 x 8.2
Physical Without Stand (in.)	21.3 x 12.7 x 1.3
Packaging (mm)	604 x 395 x 115
Physical (mm)	540 x 414.1 x 209
Physical Without Stand (mm)	540 x 323 x 34.1
Package Contents	VX2476-smhd Display, AC/DC Adapter, Power Cable, VGA Cable, HDMI Cable, Audio Cable, Quick Start Guide, ViewSonic Wizard CD-ROM
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907895216



Contact Sales
ViewSonic.com
888.881.8781
email:
salesinfo@viewsonic.com