


SD-Z225

## Key Features


- Teradici® Tera2321 CPU with hardware accelerated PCoIP
- True personal PC experience
- Dual display productivity
- Simplified and secure management
- Low total cost of ownership



22  
DISPLAY



PANEL



RESOLUTION



## Product Description

The ViewSonic SD-Z225 22" (21.5" viewable) Zero Client monitor is based on the Teradici Tera 2321 processor, with hardware accelerated PCoIP support. The SD-Z225 Zero Client is the perfect solution for companies seeking a seamless desktop experience, with ultra-high security and reliability in VMware-based networks. The SD-Z225 is a true Zero Client and features no local memory or moving parts for the ultimate in energy savings and reliability. The VMware-certified design guarantees performance and compatibility in your network. With the additional DVI output, flexible support is provided for dual monitor productivity. The eco-friendly design with LED display uses up to 80% less energy consumption than standard PCs.

## Specifications

### More Information

<b>Energy Star Compliant</b>	No
<b>UPC</b>	766907692716
<b>CPU Processor Type</b>	Teradici Tera2321
<b>RAM</b>	512MB
<b>Memory Type</b>	DDR3
<b>Protocols</b>	VMware PCoIP
<b>Static Contrast Ratio</b>	1,000:1
<b>Viewing Angles</b>	170° horizontal, 160° vertical
<b>Display Resolution</b>	1920 x 1080
<b>Viewable Area (in.)</b>	21,5

<b>Dynamic Contrast Ratio</b>	20,000,000:1
<b>Response Time (Typical GTG)</b>	5ms
<b>Light Source</b>	LED
<b>Brightness</b>	250 cd/m2
<b>Panel Surface</b>	Anti-glare, hard-coating (3H)
<b>Screen Size</b>	22
<b>Analog Sync</b>	Separate Sync
<b>USB 2.0 Type A</b>	4
<b>VGA</b>	1
<b>DVI-I Out</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>3.5mm Audio In</b>	1
<b>3.5mm Audio Out</b>	1
<b>3.5mm Mic In</b>	1
<b>Internal Speakers</b>	2W (x2)
<b>Voltage</b>	AC 90-240V (universal), 50-60Hz
<b>Physical Controls</b>	PCoIP, 2, Down, Up, 1, Power
<b>Consumption (typical)</b>	24W
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, AudioAdjust, Color Adjust, Information, Manual Image Adjust, SetupMenu, Memory Recall (See user guide for full OSD functionality)
<b>Ethernet LAN</b>	10/100/1000 Mbps
<b>Humidity (non-condensing)</b>	15-90%
<b>Kensington Lock Slot</b>	1
<b>Frequency Horizontal</b>	24~82kHz
<b>Frequency Vertical</b>	50~75Hz
<b>Gross (kg)</b>	6,2
<b>Net (kg)</b>	4,5
<b>Net Without Stand (kg)</b>	3,4
<b>Packaging (in.)</b>	22.5 x 17.4 x 6.2
<b>Packaging (mm)</b>	572 x 442 x 158
<b>Physical (mm)</b>	512.4 x 376.7 x 189.9
<b>Physical Without Stand (mm)</b>	512.4 x 316 x 54
<b>VESA Compatible</b>	100 x 100 mm
<b>Regulations</b>	FCC, CB, cTUVus, WEEE, RoHS Compliant, REACH Compliant
<b>Package Contents</b>	SD-Z225 Zero Client Monitor, power cord, power adapter, VGA cable, Quick Start Guide, ViewSonic Wizard CD
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.

<b>Part #</b>	SD-Z225_BK_US0
<b>Warranty</b>	Three-year limited warranty on parts and labor
<b>Classification</b>	Discontinued
<b>Physical (in.)</b>	20.2 x 14.8 x 7.5
<b>Physical Without Stand (in.)</b>	20.2 x 12.4 x 2.1
<b>Net (lbs)</b>	9,9
<b>Net Without Stand (lbs)</b>	7,4
<b>Gross (lbs)</b>	13,7

UPC: 766907692716



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 