

VA2709M - 27" 1080P IPS 100HZ VARIABLE REFRESH RATE MONITOR WITH HDMI, VGA


Key Features



27"
DISPLAY



IPS
PANEL



1920 X 1080
RESOLUTION



Product Description


Featuring enhanced wide-angle viewing, stunning resolution and flexible connectivity options, the VA2709m helps users bring clarity to their work. This 27" VA2709m monitor comes with SuperClear® IPS panel technology so you can experience stunning brightness and contrast at nearly any viewing angle. Enjoy greater productivity and see the bigger picture by adding additional monitors to your setup as this 27" monitor features a minimalist edge-to-edge screen and a frameless three-sided bezel. Connect laptops, PCs, gaming consoles and other multimedia devices using the versatile HDMI and VGA ports. And with powerful features like flicker-free technology and a blue light filter, you can easily work for longer with less strain. Enjoy a 3 year limited warranty, industry-leading pixel performance policy and so much more with the ViewSonic VA2709m monitor.

Specifications

	More Information
UPC	766907027082
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Response Time (MPRT)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	1920 X 1080
Mac® Resolution (max)	1920 X 1080
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	22w
Eco Mode (optimized)	26w
Consumption (typical)	30w
Consumption (max)	33w
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3w
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1

Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	VGA: 24 ~ 86 KHz / HDMI 1.4: 24 ~ 115 KHz
Frequency Vertical	VGA: 48 ~ 75 Hz / HDMI 1.4: 48 ~ 100 Hz
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC, NRCAN, NOM, Mexico Energy
Net (lbs)	9.3
Net Without Stand (lbs)	7.9
Gross (lbs)	13
Net (kg)	4.2
Net Without Stand (kg)	3.6
Gross (kg)	5.9
Packaging (in.)	27.4 " (W) x 18.1 " (H) x 5.7 " (D)
Physical (in.)	24.2 " (W) x 18.1 " (H) x 8 " (D)
Physical Without Stand (in.)	24.2 " (W) x 14.3 " (H) x 1.8 " (D)
Packaging (mm)	695 mm (W) x 460 mm (H) x 145 mm (D)
Physical (mm)	615 mm (W) x 460 mm (H) x 203 mm (D)
Physical Without Stand (mm)	615 mm (W) x 364 mm (H) x 46 mm (D)
Package Contents	LCD Display, Power Cable, HDMI Cable, AC/DC Adapter, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907027082



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com