



VA2719-SMH - 27" 1080P IPS MONITOR WITH HDMI, VGA, AND ENHANCED VIEWING COMFORT

Key Features

- 27 Inch Full HD (1920x1080p) IPS monitor with 60Hz refresh rate
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Optimized view settings offer "Game," "Movie," "Web," "Text," and "Mono" presets
- The VA2719-SMH supports laptops, PCs, Macs and more with HDMI and VGA inputs




What's in the box.



27"
DISPLAY



IPS
PANEL



1920 x 1080
RESOLUTION



VA2719-SMH Monitor

*Power Cable varies by region



Power Cable*



HDMI Cable



Quickstart Guide

Product Description

With flexible connectivity, wide-angle viewing, and amazing screen performance, the ViewSonic® VA2719-smh is a 27" monitor that delivers solid multimedia features at a great value. With a SuperClear IPS panel and slim bezel design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Whether for working at the office, or enjoying entertainment at home, the VA2719-smh also features an HDMI port for flexible connectivity to PCs, laptops, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2719-smh a great overall value choice.


Specifications

[More Information](#)

UPC	766907885415
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	300 cd/m2
Colors	16.7M
Color Space Support	6-Bit+ HI-FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	21W
Eco Mode (optimized)	26W
Consumption (typical)	31W
Consumption (max)	40W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%

VESA Compatible	100 x 100 mm
Frequency Horizontal	24 ~ 82KHz
Frequency Vertical	50 ~ 75Hz
Analog Sync	Separate Sync
Digital Sync	TMDS
Tilt (Forward/Back)	5° / 22°
Regulations	cULus, FCC-B, ICES003, Energy Star 7.0, EPEAT, UL-MX-CoC, Mexico Energy
Net (lbs)	12.4
Net Without Stand (lbs)	9.9
Gross (lbs)	15.7
Net (kg)	5.6
Net Without Stand (kg)	4.5
Gross (kg)	7.1
Packaging (in.)	27.4 x 18.5 x 5.4
Physical (in.)	24.4 x 17.5 x 9.8
Physical Without Stand (in.)	24.4 x 14.3 x 1.8
Packaging (mm)	695 x 470 x 136
Physical (mm)	620 x 444 x 250
Physical Without Stand (mm)	620 x 362 x 45
Package Contents	LCD Display, Power Cable, HDMI to HDMI (1.5m), Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907885415



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com