




VA2719-2K-SMHD - 24" 1440P IPS MONITOR WITH HDMI, DISPLAYPORT, AND ENHANCED VIEWING COMFORT

Key Features

- Wide Quad HD Resolution
- SuperClear® IPS Panel Technology
- The Power of HDMI
- Slim Bezel Design
- Optimized View Settings



Product Description

The ViewSonic® VA2719-2K-Smhd is a 27" WQHD monitor that delivers solid multimedia features at a great value with flexible connectivity, wide-angle viewing, and amazing screen performance. Featuring 2560 x 1440 resolution and a slim bezel design, this monitor provides a near-seamless viewing experience ideal for multi-monitor setups. Whether for working at the office, or enjoying entertainment at home, the VA2719-2K-Smhd also features DisplayPort and HDMI ports for flexible connectivity to PCs, laptops, and other multimedia devices. In addition, a 3-year limited warranty, along with one of the industry's best pixel performance policies, makes the VA2719-2K-Smhd a great overall value choice.


Specifications

[More Information](#)

UPC	766907899139
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	300 cd/m2
Colors	1.07B
Color Space Support	10-Bit
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
3.5mm Audio In	1
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	21W
Eco Mode (optimized)	27W
Consumption (typical)	33W
Consumption (max)	35W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, Down, Up, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)

Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 120KHz
Frequency Vertical	24 ~ 75Hz
Digital Sync	TMDS, PCI-E
Regulations	cTUVus, FCC, ICES003, Mexico Energy, MX-CoC, CE, REACH, EEL, WEEE, EAC, UkrSEPRO
Net (lbs)	12.4
Net Without Stand (lbs)	9.9
Gross (lbs)	15.7
Net (kg)	5.6
Net Without Stand (kg)	4.5
Gross (kg)	7.1
Packaging (in.)	27.4 x 18.5 x 5.4
Physical (in.)	24.4 x 17.5 x 9.8
Physical Without Stand (in.)	24.4 x 14.3 x 1.8
Packaging (mm)	695 x 470 x 136
Physical (mm)	620.2 x 443.8 x 250
Physical Without Stand (mm)	620.2 x 362.2 x 45.1
Package Contents	LCD Display, Power Cable , HDMI Cable , Audio Cable , Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907899139



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com