



LS800HD - 1920 X 1080 RESOLUTION, 5,000 ANSI LUMENS, 1.2-1.9 THROW RATIO

Key Features


- 5000 Lumen Brightness
 - Ultra-high Contrast Ratio
 - Long-lasting Laser Phosphor Light Source
 - One-wire HDBT Input
 - 360-degree Orientation
 - Portrait Mode Projection
 - 5-Year Warranty
-



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1200
RESOLUTION



Product Description

Bright and versatile for any professional installation, the ViewSonic® LS800HD 1080p laser projector delivers everything you need for big screens in big venues. Delivering 5,000 lumens of advanced high brightness, 100,000:1 contrast ratio, and up to 30,000 hours of light source life, this projector is ideal for auditoriums, lecture halls, large boardrooms, houses of worship, and more. Thanks to SuperColor™ technology, content is brought to life with captivating color, crisp graphics, and stunning videos no matter the environment. This top-notch performer is also easy to deploy and manage with its wide 1.65x optical zoom, vertical/horizontal keystone, 4-corner adjustment, and a vertical/horizontal lens shift feature that provides extreme flexibility in even the most challenging installations. Thanks to the built-in HDBT receiver, the projector is capable of receiving uncompressed HD video and audio from over 200 feet away via network cable. Moreover, 360-degree tilt angle projection, portrait mode, and 24/7 operation allow for extreme mounting flexibility. The ViewSonic® LS800HD is the ideal 1080p laser projector for professional installations, large venues, and business and education environments.

Specifications

	More Information
UPC	766907932317
Light Source	DLP Laser
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	5,000 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m

Throw Distance	4.1 - 41 ft / 1.3 - 12.5 m
Throw Ratio	1.2-1.9
Keystone	Vertical (+/- 25°) / Horizontal (+/- 30°)
Lens	1.65x optical zoom
Light Source (watt)	Laser bank x 4
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	100,000:1
Aspect Ratio	16:9
Input Lag	37ms
Lens Shift	Horizontal (-2.5% +2.5%) / Vertical (-2.9% +11.8%)
Operation Rating	24/7
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1200
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1200
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS-232)	1
HDMI In	3
VGA In	1
VGA Out	1
Composite RCA Video In	1
Mini USB	1
RCA Audio In (L/R)	1
RCA Audio Out	1
3D VESA	1
HDBT	1
Internal Speakers	5W (x2)
Voltage	100-240V +/- 10%, 50/60Hz AC
Consumption (typical)	430W

Stand-by	<0.5W
Physical Controls	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
On Screen Display	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
IP Code	IP6X
Kensington Lock Slot	1
Net (lbs)	24.3
Gross (lbs)	30.0
Net (kg)	11.0
Gross (kg)	13.6
Packaging (in.)	22.0 x 11.9 x 18.5
Physical (in.)	14.2 x 6.3 x 17.3
Packaging (mm)	559.0 x 301.0 x 469.0
Physical (mm)	360.0 x 161.0 x 440.0
AV Control	AMX Certified, ATEN Certified, Crestron Certified
Regulations	FCC, UL/CUL, ROHS
Package Contents	LS800HD projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Five-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907932317



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com