



M1 - PORTABLE LED PROJECTOR WITH HARMON KARDON SPEAKERS AND USB C

Key Features


- 360-degree projection with Smart Stand
- Dual Harman Kardon Speakers
- USB Type-C for Video and Power
- Built-in Battery and 16GB Internal Storage
- Advanced LED Light Source



24 - 100 in. / 0.6 - 2.54 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

The ViewSonic® M1 is an ultra-portable LED projector that delivers convenient entertainment in nearly any room. With a built-in battery and over 30,000 hours of operational life, this projector will deliver years of multimedia entertainment wherever it goes. Weighing less than two pounds, the M1's compact and lightweight design makes it ideal for moving from room to room, or for indoor/outdoor usage. An integrated smart stand provides for simple 360-degree setup, while also doubling as a lens cover. Once the lens is uncovered, the projector automatically powers on with full brightness for instant entertainment. A built-in safety feature temporarily turns off the lens when objects are detected too close to the projector. Dual Harman Kardon speakers provide crisp and clear sound for multimedia content, while a short throw lens can display large images in small spaces. What's more, versatile connectivity options include a MicroSD card slot, USB Type-A, and USB Type-C - making the M1 a great option for sharing and displaying videos and other multimedia content.

Specifications

UPC	766907000658
Light Source	LED
Display Resolution	WVGA (854x480)
Display Resolution	854 x 480
Brightness (Lumens)	250
Screen Size	24 - 100 in. / 0.6 - 2.54 m
Throw Distance	40 in / 1.0 m
Throw Ratio	1.2
Keystone	Vertical (+/- 40°)
Lens	Fixed Zoom
Light Source Life, Normal (hours)	30000
Color Depth	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio	120,000:1
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15h~135kHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
USB 3.1 Type C	1
Card Reader	Micro SD
3.5mm Audio Out	1
HDMI 1.4 In	1
Internal Speakers	3W (x2)
Voltage	100-240 VAC
Consumption (typical)	55W
Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
Net (lbs)	1.7

Gross (lbs)	3.7
Net (kg)	0.8
Gross (kg)	1.7
Packaging (in.)	16.0 x 9.2 x 15.0
Physical (in.)	5.7 x 1.6 x 5.0
Packaging (mm)	406.0 x 233.0 x 380.0
Physical (mm)	146.0 x 40.0 x 126.0
Regulations	FCC, cTUVus, ROHS, TUV-S, NOM, UL2054
Package Contents	M1 Projector, Power Cable, USB Type C Cable, Remote Control, Projector Case, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Battery Chemistry	Lithium-ion
Portability	Portable, Mobile

UPC: 766907000658



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com