

VIEWSONIC 32" 1440P THIN-BEZEL IPS MONITOR WITH HDMI, DP, AND MINI DP | VX3276-2K-MHD

Key Features


- Versatile Monitor: 32 Inch QHD (2560x1440p) IPS monitor with thin bezels and 75Hz refresh rate
- Enhanced Viewing Comfort: Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- Optimized View Settings: Offers "Game," "Movie," "Web," "Text," and "Mono" presets
- Flexible Connectivity: The VX3276-2K-MHD supports laptops, PCs, and Macs with HDMI, DisplayPort, and Mini DisplayPort inputs




WQHD (2560x1440p) Resolution




32"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description


The ViewSonic® VX3276-2K-mhd is a sleek 32" (31.5" viewable) WQHD monitor with a modern and minimalist style perfect for home use. With IPS Panel technology, this monitor offers best-in-class screen performance with ultra-wide viewing angles. A premium ID includes an ultra-slim profile and unique desktop stand. A sleek edge-to-edge frameless design combined with a stunning 2560 x 1440 resolution provides 70% more on-screen content than Full HD monitors, making project management and multitasking easier than before. Versatile HDMI, DisplayPort, and Mini DisplayPort inputs offer flexible connectivity options for both computing and gaming, while an exclusive ViewMode™ feature provides intuitive presets for optimized screen performance in different applications. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment that combines style and high performance for the home.

Specifications

	More Information
UPC	766907953633
Screen Size	32"
Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,200:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED
Brightness	250 cd/m2
Colors	1.07B
Color Space Support	10 Bit
Aspect Ratio	16:9
Response Time (Typical GTG)	8ms
Response Time (GTG w/OD)	4ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Mini DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	36W
Eco Mode (optimized)	41W
Consumption (typical)	43W
Consumption (max)	48W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
Frequency Horizontal	HDMI: 15 ~ 113KHz, DP / Mini DP: 24 ~ 113KHz
Frequency Vertical	HDMI: 24 ~ 75Hz, DP / Mini DP: 50 ~ 75Hz
Digital Sync	TMDS for HDMI, PCI-E for DP / Mini DP
Tilt (Forward/Back)	4° / 15°
Regulations	cTUVus, FCC-B with ICES003, MX-CoC, Mexico Energy
Net (lbs)	13.6
Net Without Stand (lbs)	12.3
Gross (lbs)	18.1
Net (kg)	6.2
Net Without Stand (kg)	5.6
Gross (kg)	8.2
Packaging (in.)	30.9 x 19.6 x 4.4
Physical (in.)	28.1 x 19.8 x 9.1
Physical Without Stand (in.)	28.1 x 16.4 x 1.5
Packaging (mm)	785.0 x 498.0 x 112.0
Physical (mm)	712.9 x 503.9 x 230.0
Physical Without Stand (mm)	712.9 x 416.4 x 38.2
Package Contents	VX3276-2K-mhd Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907953633



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com