


CDE5010 - 50" DISPLAY, 3840 X 2160 RESOLUTION, 350 CD/M2 BRIGHTNESS, 16/7

## Key Features


- Ultra HD Resolution
- Built-in Multi-Core Media Player with 8GB Storage
- Embedded LAN, Optional Wi-Fi, Internet Browser
- ViewBoard® Cast Content Sharing Software
- Free Bundled vController™ Software



50  
DISPLAY



PANEL



RESOLUTION



## Product Description

The ViewSonic® CDE5010 is a 50'' (50'' viewable) 4K Ultra HD commercial display purpose-built to deliver eye-catching imagery for hotels, restaurants, retail, business, and more. With stunning 3840x2160 resolution, 350-nit high brightness, wide viewing angles, and dual 10W speakers, this display provides immersive, high-impact messaging wherever needed. In addition to HDMI, DVI, and VGA inputs to connect with various high definition devices, this display utilizes an integrated multi-core processor and 8GB of internal memory, allowing customers to playback multimedia content via USB without the need for a PC. To make life even easier, the bundled vController software offers easy maintenance and intuitive interfaces for remote management via a PC server or laptop, and flicker-free and blue light filter technologies help provide a comfortable viewing environment.

## Specifications

### More Information

<b>UPC</b>	766907990416
<b>Media Player Type</b>	Yes
<b>CPU</b>	Quad Core - Cortex A53
<b>Memory</b>	2GB
<b>Storage</b>	8GB eMMC
<b>Built-in Software</b>	OSD / Remote Control
<b>Internal Speakers</b>	10W (x2)
<b>HDMI 2.0 In</b>	2
<b>DVI-D</b>	1

<b>VGA</b>	1
<b>RCA Audio Out</b>	1
<b>3.5mm Audio In</b>	1
<b>USB 3.0</b>	1
<b>USB 2.0</b>	1
<b>RS232</b>	1
<b>RS232 Out</b>	1
<b>Ethernet LAN (RJ45)</b>	1
<b>Micro SD Card Slot</b>	1
<b>IR in</b>	1
<b>IR out</b>	1
<b>Voltage</b>	100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz
<b>Consumption (max)</b>	175W
<b>Consumption (typical)</b>	140W
<b>Stand-by</b>	<0.5W
<b>Temperature</b>	41-104° F (5 - 40° C)
<b>Humidity (non-condensing)</b>	20-80%
<b>Net (lbs)</b>	32.9
<b>Net Without Stand (lbs)</b>	28.7
<b>Gross (lbs)</b>	36.4
<b>Net (kg)</b>	14.9
<b>Net Without Stand (kg)</b>	13.0
<b>Gross (kg)</b>	16.5
<b>Packaging (in.)</b>	50.5 x 33.3 x 8.0
<b>Physical (in.)</b>	44.2 x 27.0 x 13.0
<b>Physical Without Stand (in.)</b>	44.2 x 25.5 x 2.7
<b>Packaging (mm)</b>	1282.0 x 845.0 x 203.0
<b>Physical (mm)</b>	1123.6 x 685.9 x 329.6
<b>Physical Without Stand (mm)</b>	1123.6 x 646.7 x 67.8
<b>VESA Compatible</b>	400 x 400 mm
<b>Screw Size</b>	M6
<b>Screw Length (mm)</b>	10
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Package Contents</b>	CDE5010, Remote control, CD User Manual, Quick Start Guide, Power cables, VGA cable, RS232 cable, IR sensor cable, RS232 daisy chain cable
<b>Regulations</b>	cULus, FCC, Energy Star 7.0, UL-MX-CoC, Mexico Energy

<b>Screen Size</b>	50
<b>Viewable Area (in.)</b>	50
<b>Light Source</b>	DLED
<b>Display Resolution</b>	3840 x 2160
<b>Aspect Ratio</b>	16:9
<b>Static Contrast Ratio</b>	4,000:1
<b>Backlight Life (Hours)</b>	30,000
<b>Brightness</b>	350 cd/m2
<b>Response Time (Typical GTG)</b>	8ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Panel Surface</b>	Anti-glare, Hard coating (3H)
<b>Operation Rating</b>	16/7

UPC: 766907990416



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 