



PS700W - 3300 LUMENS WXGA ULTRA SHORT THROW PROJECTOR WITH HV KEYSTONE

Key Features


- Bright Images in any Environment
- Large Images in Small Spaces
- Horizontal and Vertical Keystone Correction
- SonicExpert/SonicMode
- PortAll



87 – 120 in. / 2.21 - 3.05 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description

Featuring 1280x720 WXGA resolution and 3,300 lumens of brightness, the ViewSonic® PS700W ultra-short throw projector is an ideal projection solution for education environments. An ultra-short throw lens enables the projector to be placed just inches away from a wall or screen, making it flexible enough to be ceiling-mounted or simply placed on the tabletop. With horizontal/vertical keystone correction, the PS700W makes installation a hassle-free experience. PortAll®, a neatly designed and enclosed HDMI/MHL dongle compartment, features an integrated micro USB cable for easy charging - allowing teachers to present interesting lesson content via wireless dongles and PC sticks. Crestron and AMX certification delivers network management capabilities, while exclusive SuperColor™ technology offers a wider color range for true-to-life images in any classroom.

Specifications

More Information	
UPC	766907904215
Light Source	DLP Lamp

Display Resolution	WXGA (1280x800)
Display Resolution	1280 x 800
Brightness (Lumens)	3,300 ANSI
Screen Size	87 - 120 in. / 2.21 - 3.05 m
Throw Distance	0.3 - 0.8 ft / 0.1 - 0.2 m
Throw Ratio	0.23
Keystone	Vertical ($\pm 30^\circ$) / Horizontal ($\pm 30^\circ$)
Lens	Fixed Zoom
Light Source (watt)	240
Light Source Life, Normal (hours)	3000
Light Source Life, Dynamic Eco-Mode (hours)	7500
Color Depth	1.07B Color (R/G/B 10bit)
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K~102KHz
Frequency Vertical	23~120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	2
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI In	2
HDMI 1.4 (with HDCP 1.4)	1
VGA In	2
VGA Out	1
Composite RCA Video In	1
S-Video In	1
Mini USB	1
RCA Audio In (L/R)	1
Internal Speakers	10W (x2)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	410W

Stand-by	<0.5W
Physical Controls	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	13.4
Gross (lbs)	18.7
Net (kg)	6.1
Gross (kg)	8.5
Packaging (in.)	23.2 x 19.7 x 10.8
Physical (in.)	17.1 x 15.3 x 6.0
Packaging (mm)	590.0 x 500.0 x 275.0
Physical (mm)	434.0 x 388.0 x 153.0
AV Control	AMX Certified, ATEN Certified, Crestron Certified, Extron Certified, PJ Link Certified
Regulations	FCC, cTUVus, ROHS
Package Contents	PS700W Projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907904215



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com