



PX703HD - 1080P HOME THEATER PROJECTOR WITH 3500 LUMENS AND LOW INPUT LAG

Key Features


- Stunning Resolution & Brightness
- Bright Images in Any Environment
- Long Lamp Life
- Reduced Input Latency



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



1920 x 1080
RESOLUTION



Product Description


For an incredible audiovisual experience at a great value, the ViewSonic® PX703HD projector delivers. Perfect for home entertainment, this projector features 3500 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, while a 10W speaker delivers incredibly clear and audible sound. An ultra-low input latency provides faster frame-by-frame action, while a Sports Mode feature delivers stunning detail so you can enjoy fast-action sports on the big screen. Full HD 3D compatibility lets you enjoy 3D movies and games. What's more, an energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours.* With a shorter throw ratio, 1.3x optical zoom, smart design, and extensive connectivity, the PX703HD provides flexible and quick set-up in any home.

Specifications

	More Information
UPC	766907001778
Light Source	DLP Lamp
Display Resolution	Full HD (1920x1080)
Display Resolution	1920 x 1080
Brightness (Lumens)	3,500 ANSI
Screen Size	30 - 300 in. / 0.76 - 7.62 m
Throw Distance	2.4 - 32.0 ft / 0.7 - 9.8 m
Throw Ratio	1.13-1.47
Keystone	Vertical (+/- 40°)
Light Source (watt)	203
Light Source Life, Normal (hours)	5000
Light Source Life, Dynamic Eco-Mode (hours)	20000
Color Depth	1.07B Color (R/G/B 10bit)
Aspect Ratio	16:9
Input Lag	37ms
Frequency Horizontal	15K-102KHz
Frequency Vertical	23-120Hz
PC Resolution (max)	1920 x 1080
PC Resolution (min)	640 x 480
Mac® Resolution (max)	1920 x 1080
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
3.5mm Audio Out	1
3.5mm Audio In	1
Control (RS232)	1
HDMI 1.4 In	1
HDMI 1.4 (with HDCP 1.4)	1
VGA In	1
VGA Out	1
Internal Speakers	10W (x1)
Voltage	100-240 VAC
Consumption (typical)	300W
Stand-by	<0.5W

On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	0-90%
Kensington Lock Slot	1
Net (lbs)	5.8
Gross (lbs)	8.3
Net (kg)	2.6
Gross (kg)	3.8
Packaging (in.)	16.3 x 6.6 x 11.7
Physical (in.)	12.3 x 8.7 x 4.3
Packaging (mm)	415.0 x 168.0 x 297.0
Physical (mm)	312.0 x 222.0 x 108.0
Regulations	FCC, cTUVus, ROHS
Package Contents	PX703HD projector, power cable, VGA cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907001778



Contact Sales
ViewSonic.com
 888.881.8781
 email:
salesinfo@viewsonic.com