CDE6512 - 65" DISPLAY, 3840 X 2160 RESOLUTION, 290 CD/M2 BRIGHTNESS, 16/7

# Key **Features**

- Ultra HD Resolution
- POWERFUL EMBEDDED SOC PLATFORM
- EMBEDDED LAN AND USB WIRELESS CONNECTIVITY
- VIEWBOARD ® CAST CONTENT SHARING SOFTWARE
- Remote Content Sharing from Anywhere
- Remote Monitoring and Display Management Made Simple



65"
**DISPLAY**



**PANEL**



**RESOLUTION**

# Product **Description**

The ViewSonic® CDE6512 is a 65” 4K Ultra HD large format wireless presentation display. With features including a razor-sharp resolution of 3840 x 2160, 290-nit high brightness, 178-degree ultra-wide viewing angles, 2 x 10W speakers, and wireless screen sharing, the CDE6512 transforms meeting rooms into a dynamic communications hub. The built-in ViewBoard® Cast screen sharing software* (along with the optional ViewSonic vCastSender app), and myViewBoard Display software, enables both on-site and online users to participate in conferences and simultaneously share content. Equipped with a 1.5GHz Quad-core embedded SoC processor, 2GB RAM, and 16GB of internal memory, the CDE6512 can play multimedia from internal storage or a USB flash drive 16 hours a day, seven days a week. And with remote configuration and content management system support, the ViewSonic® CDE6512 is also suitable for a wide array of diverse signage applications.

# Specifications

| More Information | |
|---|---|
| **UPC** | 766907017656 |
| **Media Player Type** | Yes |
| **Operating System** | Android 9.0 |
| **CPU** | Quad-core, 1.5GHz, MT9632/ARM Cortex-A53 |
| **GPU** | Dual Core, G52MP2 |
| **Memory** | 2GB DDR4 |
| **Storage** | 16GB (eMMC) |
| **Internal Speakers** | 10W (x2) |
| **HDMI 2.0 In** | 2 |
| **RCA Audio In** | 1 |
| **3.5mm Audio Out** | 1 |
| **SPDIF Audio Out** | 1 |
| **USB 2.0** | 1 |
| **USB-C (15W PD)** | 1 |
| **Ethernet LAN (RJ45)** | 1 |
| **Voltage** | 100-240 VAC +/- 10% Wide Range, 50-60Hz +/-3 Hz |
| **Consumption (max)** | 300W |
| **Consumption (typical)** | 220W |
| **Stand-by** | <0.5W |
| **On Screen Display** | Picture, Screen, Audio, Time, Advanced Options, About |
| **Temperature** | 32-104º F (0 - 40º C) |
| **Humidity (non-condensing)** | 20-80% |
| **Net (lbs)** | 44.8 |
| **Gross (lbs)** | 59.1 |
| **Net (kg)** | 20.3 |
| **Gross (kg)** | 26.8 |
| **Packaging (in.)** | 62.4 x 37.28 x 7.09 |
| **Physical (in.)** | 57.54 x 33.2 x 3.17 |
| **Packaging (mm)** | 1585 x 947 x 180 |
| **Physical (mm)** | 1461.4 x 843.2 x 80.4 |
| **VESA Compatible** | 300 x 200 mm |
| **Warranty** | Three-year limited warranty on parts, labor and backlight |
| **Recycle/Disposal** | Please dispose of in accordance with local, state or federal laws. |

| | |
|---|---|
| **Package Contents** | CDE6512, Remote control with batteries, Wi-Fi adapter, Quick Start Guide, Power cable, HDMI Cable, Wall Mount Screws and RS232 adapter |
| **Regulations** | cTUVus, FCC, Energy Star, EPEAT (Bronze), RoHS |
| **Screen Size** | 65" |
| **Viewable Area (in.)** | 64.5 |
| **Colors** | 1.07B |
| **Light Source** | DLED |
| **Display Resolution** | 3840 x 2160 |
| **Aspect Ratio** | 16:9 |
| **Static Contrast Ratio** | 1,200:1 |
| **Dynamic Contrast Ratio** | 5,000:1 |
| **Backlight Life (Hours)** | 30,000 |
| **Brightness** | 290 cd/m2 |
| **Response Time (Typical GTG)** | 8ms |
| **Bezel Width (in.)** | 0.63/0.63/0.63/0.87 in |
| **Bezel Width (mm)** | 16/16/16/22 mm |
| **Viewing Angles** | 178º horizontal, 178º vertical |
| **Panel Surface** | Hard Coat - Anti-Glare, 2% Haze, 3H with anti-glare treatment |
| **Operation Rating** | 16/7 |

UPC: 766907017656

**Contact Sales**

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com