VIEWSONIC 24" 1080P VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO COMPATIBLE IR WEBCAM, 90W USB-C, RJ45 | VG2457V

# Key **Features**

- Versatile Monitor: 24 Inch Full HD (1920x1080p) IPS monitors with thin bezels and 100Hz refresh rate
- Feature-Packed Camera: Ergonomic pop-up full hd camera with adjustable LED that is Zoom and Windows Hello certified
- Video Conferencing Monitor: Built-in microphone, front-firing 5W speakers, and a 1080p camera
- Ditch The Dock: Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 90W charging over one cable
- Ergonomic Stand: Advanced ergonomics (40-degree tilt, swivel, rotate and height) for all-day comfort
- Flexible Connectivity: Supports PC, Mac and more with USB-C, HDMI 14, DisplayPort, and USB Type A inputs

24
**DISPLAY**

IPS
**PANEL**

1920 X 1080
**RESOLUTION**

# Product **Description**

ViewSonic VG2457V video conferencing monitor is a docking monitor with premium features such as a pop-up webcam that will help maintain productive meetings whether in the office or working from home, with secure features like a Windows Hello compatible IR camera and Zoom certification for peace of mind on security and reliable conferencing. Premium webcam features to improve visual and audio aspects of video calls such as built in LED lighting, and a front firing speaker bar. The IR camera allows for secure and easy sign-on with Windows Hello. Full docking functionality (daisy chain, USB-C single cable connectivity with 90W power delivery, reliable ethernet connectivity) simplifies accessories needed to deploy for IT infrastructure.

# Specifications

More Information

| | |
|---|---|
| **UPC** | 766907024340 |
| **Screen Size** | 24 |
| **Viewable Area (in.)** | 23.8 |
| **Panel Type** | IPS |
| **Display Resolution** | 1920 x 1080 |
| **Display Resolution** | Full HD (1920x1080) |
| **Static Contrast Ratio** | 1,300:1 |
| **Dynamic Contrast Ratio** | 80M:1 |

| | |
|---|---|
| **Light Source** | LED |
| **Brightness** | 250 cd/m2 |
| **Color Space Support** | 8 bit (6 bit + FRC) |
| **Aspect Ratio** | 16:9 |
| **Response Time (Typical GTG)** | 5ms |
| **Viewing Angles** | 178º horizontal, 178º vertical |
| **Backlight Life (Hours)** | 30,000 |
| **Panel Surface** | Anti-Glare type, Hard-coating (3H), Haze 25% |
| **Refresh Rate** | 100Hz |
| **PC Resolution (max)** | 1920 X 1080 |
| **Mac® Resolution (max)** | 1920 X 1080 |
| **USB Type A** | 2 |
| **USB Type C** | 2 |
| **3.5mm Audio Out** | 1 |
| **Ethernet LAN (RJ45)** | 1 |
| **HDMI 1.4 In** | 1 |
| **DisplayPort** | 1 |
| **DisplayPort Out** | 1 |
| **Internal Speakers** | 5W (x2) |
| **Eco Mode (Conserve)** | 119 |
| **Eco Mode (optimized)** | 121.8 |
| **Consumption (typical)** | 124.4 |
| **Consumption (max)** | 167.8 |
| **Voltage** | 100-240 VAC, 50-60Hz |
| **Stand-by** | 0.5 |
| **Power Supply** | Internal |
| **Cable Organization** | No |
| **Kensington Lock Slot** | 1 |
| **Webcam** | Yes |
| **Physical Controls** | Key 1 (eye), Key 2, Key 3, Key 4, Key 5, Key 6 (power) |
| **On Screen Display** | Input Select, Conference Mode, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| **Temperature** | 32-104º F (0 - 40º C) |
| **Humidity (non-condensing)** | 20-90% |
| **VESA Compatible** | 100 x 100 mm |
| **Frequency Horizontal** | 15 ~ 110 KHz |
| **Frequency Vertical** | Fv = 50 ~ 100 Hz |

| | |
|---|---|
| **Height Adjust** | 110 mm / 4.3 in |
| **Swivel** | 60º |
| **Pivot (Right/Left)** | 90º / 90º |
| **Tilt (Forward/Back)** | 5º / 40º |
| **Regulations** | cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy |
| **Net (lbs)** | 15.1 |
| **Net Without Stand (lbs)** | 10 |
| **Gross (lbs)** | 21.3 |
| **Net (kg)** | 6.9 |
| **Net Without Stand (kg)** | 4.6 |
| **Gross (kg)** | 9.7 |
| **Packaging (in.)** | 23.9 " (W) x 16.2 " (H) x 8.3 " (D) |
| **Physical (in.)** | 21.22 " (W) x 15.82~20.15 " (H) x 7.96 " (D) |
| **Physical Without Stand (in.)** | 21.22 " (W) x 13.74 " (H) x 2.2 " (D) |
| **Packaging (mm)** | 606 mm (W) x 411 mm (H) x 210 mm (D) |
| **Physical (mm)** | 539.04 mm (W) x 401.83~511.83 mm (H) x 202.18 mm (D) |
| **Physical Without Stand (mm)** | 539.04 mm (W) x 349 mm (H) x 55.8 mm (D) |
| **Package Contents** | LCD Display, Power Cable, DisplayPort to DisplayPort Cable, USB Type-C Cable (Male-Male; with Type-A adapter), Quick Start Guide |
| **Recycle/Disposal** | Please dispose of in accordance with local, state or federal laws. |
| **Warranty** | Three-year limited warranty on parts, labor and backlight |

UPC: 766907024340

## Contact Sales

**ViewSonic.com**
888.881.8781
email: salesinfo@viewsonic.com