



VA2714-H - 27" 1080P IPS MONITOR WITH HDMI, VGA

Key Features

- Wide-angle viewing with SuperClear® IPS technology
- Three-sided frameless design
- HDMI and VGA connectivity
- Variable refresh rate technologies deliver smoother images
- Full HD 1080p resolution

27
DISPLAYIPS
PANEL1920 x 1080
RESOLUTION

Product Description

Experience flexible connectivity, wide-angle viewing, and stunning screen performance with the 27" ViewSonic® VA2714-H monitor. This three-sided frameless display features state-of-the-art IPS panel technology which enables users to enjoy powerful brightness and impressive contrast from nearly any viewing angle. The VA2714-H includes a VGA port, an HDMI port, and an HDMI cable, ensuring flexible connectivity to PCs, laptops, and gaming consoles. Enjoy a smoother viewing experience with built-in variable refresh rate technology that virtually eliminates screen tearing and stuttering. Upgrade the way you work and play with the ViewSonic VA2714-H monitor today.

Specifications

More Information

UPC	766907029055
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	1920 x 1080
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	300 cd/m ²
Colors	16.7M

Color Space Support	6 bit + FRC
Aspect Ratio	16:9
Response Time (Typical GTG)	4ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	100Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
HDMI 1.4 In	1
Eco Mode (Conserve)	15W
Eco Mode (optimized)	17W
Consumption (typical)	19W
Consumption (max)	28W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 1.4: 24 ~ 115 KHz; RGB Analog: 24 ~ 86 KHz
Frequency Vertical	HDMI 1.4: 48 ~100 Hz; RGB Analog: 48 ~75 Hz
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, NOM, Mexico Energy, RoHS, WEEE
Net (lbs)	10.6
Net Without Stand (lbs)	9.0
Gross (lbs)	14.1
Net (kg)	4.8
Net Without Stand (kg)	4.1


Gross (kg)	6.4
Packaging (in.)	26.8 x 17.5 x 5.6
Physical (in.)	24.1 x 17.1x 9.5
Physical Without Stand (in.)	24.1 x 14.3 x 1.9
Packaging (mm)	680.0 x 445.0 x 143.0
Physical (mm)	611.9 x 434.6 x 242.2
Physical Without Stand (mm)	611.9 x 364.2 x 49.1
Package Contents	VA2714-H Display, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907029055



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 