



VG3457CV - 34" UWQHD CURVED VIDEO CONFERENCING MONITOR WITH WINDOWS HELLO COMPATIBLE IR WEBCAM, 100W USB-C, RJ45 ETHERNET


Key Features



34
DISPLAY



MVA
PANEL



3440 X 1440
RESOLUTION



Product Description

ViewSonic VG3457CV video conferencing monitor is an ultrawide docking monitor with premium features such as a Zoom certified pop-up webcam that will help maintain productive meetings whether in the office or working from home. Premium webcam features to improve visual and audio aspects of video calls such as built in LED lighting, and powerful speakers. The IR camera allows for secure and easy sign-on with Windows Hello. The 21:9 aspect ratio provides extra screen space, while the 1500R curved screen offers an immersive viewing experience. Reliable network connectivity is ensured with an integrated Ethernet port, and the latest USB Type-C connectivity provides up to 100W power delivery to your laptop. Additionally, the integrated USB hub allows for easy connecting and charging of peripherals and accessories.

Specifications

| More Information | |
|------------------------------------|-----------------------|
| UPC | 766907031096 |
| Screen Size | 34 |
| Viewable Area (in.) | 34 |
| Panel Type | MVA |
| Display Resolution | 3440 x 1440 |
| Display Resolution | UWQHD (3440x1440) |
| Static Contrast Ratio | 3,000:1 |
| Dynamic Contrast Ratio | 80,000,000:1 |
| Brightness | 350 cd/m ² |
| Colors | 1.07B |
| Color Space Support | 10 bit (8 bit + FRC) |
| Aspect Ratio | 21:9 |
| Response Time (Typical GTG) | 5ms |

| | |
|----------------------------------|--|
| Viewing Angles | 178° horizontal, 178° vertical |
| Backlight Life (Hours) | 30,000 |
| Panel Surface | Anti-Glare type, Hard-coating (3H), Haze 25% |
| Curvature | 1500R |
| Refresh Rate | 100Hz |
| PC Resolution (max) | 3440 X 1440 |
| Mac® Resolution (max) | 3440 X 1440 |
| USB Type A | 4 |
| USB Type C | 100W x 1, 15W x 1 |
| 3.5mm Audio Out | 1 |
| Ethernet LAN (RJ45) | 1 |
| HDMI 2.0 In | 2 |
| DisplayPort | 1 |
| Internal Speakers | 5W (x2) |
| Eco Mode (Conserve) | 35W |
| Eco Mode (optimized) | 40W |
| Consumption (typical) | 45W |
| Consumption (max) | 210W |
| Voltage | AC 100-240V (universal), 50-60Hz |
| Stand-by | 0.5W |
| Power Supply | Internal |
| Cable Organization | No |
| Kensington Lock Slot | 1 |
| Temperature | 32-104° F (0 - 40° C) |
| Humidity (non-condensing) | 20-90% |
| VESA Compatible | 100 x 100 mm |
| Frequency Horizontal | HDMI 2.0, DisplayPort, USB Type C: 30 ~ 150 KHz |
| Frequency Vertical | HDMI 2.0, DisplayPort, USB Type C: 48 ~ 100 Hz |
| Height Adjust | 110 mm / 4.3 in |
| Swivel | 120° |
| Tilt (Forward/Back) | 5° / 40° |
| Regulations | cTUVus, FCC-B ICES003, Energy Star, EPEAT, CEC, NOM, Mexico Energy |
| Net (lbs) | 20.9 |
| Net Without Stand (lbs) | 15.4 |
| Gross (lbs) | 34.2 |
| Net (kg) | 9.5 |


| | |
|-------------------------------------|--|
| Net Without Stand (kg) | 7.0 |
| Gross (kg) | 15.5 |
| Packaging (in.) | 39 x 19.5 x 9.4 |
| Physical (in.) | 31.81 x 16.68~21.01 x 9.3 |
| Physical Without Stand (in.) | 31.81 x 15.4 x 4.53 |
| Packaging (mm) | 990.0 x 495.0 x 238.0 |
| Physical (mm) | 808.0 x 423.7~533.7 x 236.2 |
| Physical Without Stand (mm) | 808.0 x 31.3 x 4.53 |
| Package Contents | VG3457CV Display, Power Cable, HDMI to HDMI Cable, USB Type-C Cable (with USB Type A adaptor), Quick Start Guide |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |
| Warranty | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |

UPC: 766907031096



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 