



ViewBoard® IFP51 Series

Make every lesson more dynamic with the energy-efficient, EDLA-Certified ViewBoard® IFP51 Series. Ranging from 55" to 98", it effortlessly fits any classroom setup. Start annotating instantly with Write Away and enjoy natural, precise 50-point touch. Personalized settings and cloud-stored files are instantly accessible with the ViewSonic Launcher, while integrated ViewSonic Education Software offers a rich toolbox to elevate teaching and learning.



Enjoy a Natural Writing Experience

Experience instant responsiveness with Write Away, pinned annotations, and palm rejection.



Sign in with One Step

Access cloud profiles with NFC and SSO sign-in for a smooth start to every lesson.



Enrich Learning with Android 14 EDLA

Enjoy robust security and access to thousands of educational apps on Google Play fit for every learner.



Enrich Classes with Education Software

Use myViewBoard for collaborative whiteboarding and AirSync for screen casting, while Manager simplifies remote device control.



Immerse in Rich Audio

Transform engagement with an 8-mic array featuring noise reduction, dual 25W speakers, and a booming 20W subwoofer.



Save Energy

Cut costs with an energy-efficient solution that uses 20% less power than the previous generation.



Explore the ViewBoard IFP51 Series

Specifications and availability are subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. Copyright © 2025, ViewSonic Corporation. All rights reserved.

Model	IFP5551	IFP6551	IFP7551	IFP8651	IFP9851
Panel Size	55"	65"	75"	86"	98"
Panel Type	TFT LCD Module with DLED Backlight				
Display Area (mm)	1209.6mm (H) x 680.4mm (V) (54.6" diagonal)	1428.48(H) x 803.52 (V) (64.5" diagonal)	1650.24 (H) x 928.26 (V) (74.5" diagonal)	1895.04 (H) x 1065.96 (V) (86.5" diagonal)	2158.85mm(H) x1214.35mm(V) (97.5" diagonal)
Aspect Ratio	16:9				
Resolution	UHD 3840x2160				
Colors	1.07B colors				
Brightness	400 nits(typ.)				
Contrast Ratio	1200:1 (typ.) 5000:1 (DCR)				
Response Time	6.5ms		8ms		6.5ms
Viewing Angles	H = 178, V = 178 typ.				
Backlight Life	50,000 Hours (8 hours of use per day)				
Surface Treatment	Hardness: 9H, AG+AF				
Orientation	Landscape				
Processor	Octa-Core CPU				
RAM	16GB DDR4				
Storage	128GB				
Type/ Tech	Ultra Fine Touch Technology (IR Recognition)				
Touch Resolution	32767 x 32767				
Touch Point	EDLA/Android/Windows: 50 points of touch				
Palm Rejection	Yes				
HDMI	x4 (Front x2: [HDMI 2.1 with CEC, HDCP x2]; Rear x2: [HDMI 2.1 with CEC, HDCP x1 + HDMI 2.1 with CEC, HDCP, ARC x1])				
RGB / VGA	x1				
DisplayPort	x1				
Audio	x1 (PC Audio In)				
RS232	x1				
SD/SDHC	x1 TF Card Slot(Micro SD)				
OPS slot	x1 (Optional Intel Standard OPS)				
WiFi Slot	x1				
HDMI	x1 (HDMI 2.1, HDCP 1.x)				
Audio	x1 (Line out)				
SPDIF	x1 (Optical)				
RJ45	x2				
Type A	x5 (Front x2 + Rear x2: USB 3.2 Gen 1 with SmartPort support; Rear x1: USB 2.0 for system update)				
Type B	x2 (Front x1 + Rear x1: USB 3.2 Gen 1 for touch)				
Type C	x3 (Front x1: [USB 3.2 Gen 1 with DP 1.2, Ethernet 100M, PD 65W]; Rear x1: [USB 3.2 Gen 1 with DP 1.2, Ethernet 100M, PD 15W]; Top x1: [USB 3.2 Gen 1 with PD 15W])				
SPEAKERS	25W x 2 front soundbar + 20W x 1 subwoofer				
MICROPHONE	Built-in 8-array microphone				
TOP CAMERA PLATE	Yes				
EMBEDDED OS	EDLA-certified Android 14				
BUNDLED SOFTWARE	myViewBoard, AirSync, Manager				
All-in-one USB port	USB 3.2 Gen 1 "SmartPort USB" to all channels				
Simple LAN sharing between IFP and slot-in device	10/100/1000M (USB Type-C 10/100M, Android & PC 10/100/1000M)				
Sensor	Light Sensor, NFC Sensor, Pen Sensor				
Voltage	100-240VAC +/- 10% Wide Range				
Consumption	On: 75.51W (Energy star)	On: 94.51W (Energy star)	On: 99.84W (Energy star)	On: 111.08W (Energy star)	On: 143.12W (Energy star)
Wall Mount (VESA ^A)	400 x 200	600 x 400	800 x 400	800 x 600	
Temperature (°C)	0°C to 40°C				
Humidity	20% - 80% RH non-condensing				
Physical (inch / mm)	49.99 x 31.08 x 3.3 in / 1269.8 x 789.3 x 83.7 mm	58.6 x 35.99 x 3.36 in / 1488.4 x 914.2 x 85.3 mm	67.29 x 40.85 x 3.36 in / 1709.1 x 1037.5 x 85.5 mm	77.05 x 46.36 x 3.36 in / 1957 x 1177.6 x 85.5 mm	87.39 x 52.1 x 3.35 in / 2219.6 x 1323.3 x 85.1 mm
Packaging (inch / mm)	55.16 x 34.57 x 8.66 in / 1401 x 878 x 220 mm	64.09 x 40.16 x 7.28 in / 1628 x 1020 x 185 mm	73.35 x 45.79 x 8.86 in / 1863 x 1163 x 225 mm	83.07 x 51.34 x 8.86 in / 2110 x 1304 x 225 mm	94.72 x 58.46 x 11.02 in / 2406 x 1485 x 280 mm
Net (lb / kg)	57.01lb / 25.86kg	76.15 lb / 34.54 kg	101.54 lb / 46.06 kg	128.88 lb / 58.46 kg	184.53 lb / 83.7 kg
Gross (lb / kg)	69.69lb / 31.61kg	93.28 lb / 42.31 kg	126.88 lb / 57.55 kg	156.59 lb / 71.03 kg	230.49 lb / 104.55 kg
REGULATIONS	cTUVus, FCC/ICES003, Energy Star 8.0, EMC/CE, CB/LVD, GOST-R/EAC, UkrSEPRO, EPEAT, Mexico NOM, Mexico Energy, UKCA, UK-EEL, BSMI, BIS, LBL(Low Blue Light Certification), Flicker Free, Green BOM, RoHS, ErP-Eco, REACH, SCIP, WEEE, TPCH, Packing waste, CA65, PAIA				
01. Power Cord x1 3 meters	06. RS232 adapter x1		11. Remote controller x1		
02. USB Type-C cable x1 1.8 meters, USB-IF certified	07. Clamp x 5		12. AAA battery x2		
03. USB Touch cable x1 3 meters	08. Camera Plate x1		13. Compliance statement		
04. Touch pen (Passive pen) x 2	09. Screw x 8 (camera 2+2, wall mount 4)		14. Warranty card (only for VSCN)		
05. Quick Start Guide	10. HDMI cable x1 3 meters (HDMI LA certified)				
SLOT-IN PC	VPCF5-W33-G1, VPC37-W53-G1, VPC35-W53-G1, VPC-A31-O1				
WiFi Module	VB-WIFI-001,VB-WIFI-005, VSB050				
Camera / Document Camera	VB-CAM-001, VB-CAM-002, VB-CAM-201, UMB202				
Stand/Trolley Cart	VB-STND-001,VB-STND-002, VB-STND-003,VB-STND-004, VB-STND-005, VB-STND-007, VB-STND-008, VB-STND-009			VB-STND-001,VB-STND-002, VB-STND-004, VB-STND-005, VB-STND-007, VB-STND-008,VB-STND-009	