

VX2718-2KPC-MHD - 27" CURVED 1440P 1MS 180HZ GAMING MONITOR WITH FREESYNC PREMIUM


Key Features



27
DISPLAY



MVA
PANEL



2560 x 1440
RESOLUTION



Product Description

With an immersive 1500R curved screen and stunning WQHD 2560 x 1440 resolution, the ViewSonic® VX2718-2KPC-MHD monitor provides an incredible viewing experience for work or play. With features including a high 180Hz* refresh rate, 1ms (MPRT) response time and FreeSync Premium technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX2718-2KPC-MHD also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for different home entertainment applications such as watching movies, editing files, or playing video games. Two HDMI (v2.0) inputs, and one DisplayPort (v1.2) input offers flexible connectivity for both general use and entertainment. *180Hz refresh rate with DisplayPort

Specifications

More Information

UPC	766907013771
Screen Size	27
Viewable Area (in.)	27
Panel Type	MVA
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bit (6 bit+FRC)

Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Response Time (MPRT)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	3,0000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Curvature	1500R
Refresh Rate	165Hz
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	23.5W
Eco Mode (optimized)	27.5W
Consumption (typical)	32.5W
Consumption (max)	40W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	75 x 75 mm
Frequency Horizontal	HDMI (v2.0): 30 ~ 222 KHz, DisplayPort (v1.2): 30 ~ 243 KHz
Frequency Vertical	HDMI (v2.0): 48 ~ 144 Hz, DisplayPort (v1.2): 48 ~ 180 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.4)
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Net (lbs)	8.6
Net Without Stand (lbs)	7.3
Gross (lbs)	12.1

Net (kg)	3.9
Net Without Stand (kg)	3.3
Gross (kg)	5.5
Packaging (in.)	27.0 x 17.4 x 6.1
Physical (in.)	24.0 x 18.7 x 8.8
Physical Without Stand (in.)	24.0 x 14.3 x 2.9
Packaging (mm)	687.0 x 443.0 x 156.0
Physical (mm)	611.0 x 475.0 x 225.0
Physical Without Stand (mm)	611.0 x 363.0 x 75.0
Package Contents	VX2718-2KPC-MHD, Power Cable, AC/DC Adapter, DisplayPort Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907013771



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com