




VG1655 - 15.6" PORTABLE 1080P IPS MONITOR WITH 60W USB C AND MINI-HDMI


Key **Features**



15.6"
DISPLAY



IPS
PANEL



1920 X 1080
RESOLUTION





Product **Description**

The ViewSonic® VG1655 is a portable 15.6" monitor designed for productivity on the go. Built for business travelers, remote workers, and digital nomads, the VG1655 can serve as a complementary screen to a laptop or tablet for boosted productivity. With an anti-glare screen and Full HD 1080p resolution, this monitor delivers a crystal-clear viewing experience so users can see more and do more for a more efficient workflow. A USB Type-C port enables quick and easy transmission of video, and audio. A second USB Type-C port also delivers up to 60W of two-way power: a connected laptop can power the VG1655, OR the VG1655 can power a connected laptop via a USB-C power bank or AC adapter and outlet. Measuring less than an inch thick and weighing under two pounds, the ultra-slim VG1655 perfectly fits into any bag, briefcase, or backpack so you can work wherever life takes you.

Specifications

UPC	766907010152
Screen Size	15.6"
Viewable Area (in.)	15.6
Panel Type	IPS
Display Resolution	1920 x 1080
Display Resolution	Full HD (1920x1080)
Static Contrast Ratio	800:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.2M
Color Space Support	8 bit (6 bit+FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	6.5ms
Viewing Angles	178º horizontal, 178º vertical
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	1920 X 1080
Mac® Resolution (max)	1920 X 1080
USB Type C	60W x 2
Mini HDMI	1
Internal Speakers	0.8W (x2)
Eco Mode (Conserve)	5.1W
Eco Mode (optimized)	6.0W
Consumption (typical)	7.6W
Consumption (max)	9.6W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Power Supply	Wall type (detachable type-C)
Cable Organization	No
Physical Controls	1, 2, 3, 4, 5 (Power)
On Screen Display	Image Adjust, Contrast, Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
Frequency Horizontal	15 ~ 82KHz

Frequency Vertical	50 ~ 75Hz
Digital Sync	TMDS for miniHDMI (v1.4), Micro-Packet for USB-type C
Tilt (Forward/Back)	0° / 60°
Regulations	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT, CEC, MX-CoC, Mexico Energy
Net (lbs)	1.8
Net Without Stand (lbs)	1.8
Gross (lbs)	4.8
Net (kg)	0.8
Net Without Stand (kg)	0.8
Gross (kg)	2.2
Packaging (in.)	17.3 x 11.3 x 3.5
Physical (in.)	14.0 x 8.8 x 0.6
Physical Without Stand (in.)	14.0 x 8.8 x 0.6
Packaging (mm)	440.0 x 288.0 x 89.0
Physical (mm)	355.0 x 223.0 x 16.0
Physical Without Stand (mm)	355.0 x 223.0 x 16.0
Package Contents	VG1655 Display, USB type-C to type-C cable, USB type-C to type-A cable, Mini HDMI Cable, Power Adapter, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
Portability	Portable, Mobile
UPC: 766907010152	



Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email:

salesinfo@viewsonic.com