

VG2756-4K - 27" 4K UHD ERGONOMIC IPS DOCKING MONITOR WITH 90W USB C AND RJ45


Key Features



27
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756-4K is a 27" 4K Ultra HD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the latest USB Type-C connectivity makes setup a breeze. That's not all, the integrated USB hub also provides single-cable simplicity for connecting and charging your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

Specifications

	More Information
UPC	766907011432
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	50,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	8+2 bits

Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
USB Type A	2
USB Type B	1
USB Type C	90W x 1
Ethernet LAN (RJ45)	1
HDMI 2.0 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	16.8W
Eco Mode (optimized)	21.2W
Consumption (typical)	30.7W
Consumption (max)	70.0W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1,2,3,4,5,6 (Power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 150 KHz
Frequency Vertical	24 ~ 75 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2), Micro-Packet for USB Type C
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Tilt (Forward/Back)	40° / 5°

Regulations	cTUVus, FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy
Net (lbs)	16.5
Net Without Stand (lbs)	11.2
Gross (lbs)	23.6
Net (kg)	7.5
Net Without Stand (kg)	5.1
Gross (kg)	10.7
Packaging (in.)	27.2 x 8.6 x 16.9
Physical (in.)	24.1 x 16.0 x 8.0
Physical Without Stand (in.)	24.1 x 14.3 x 2.0
Packaging (mm)	692.0 x 218.0 x 430.0
Physical (mm)	613.0 x 406.0 x 202.0
Physical Without Stand (mm)	613.0 x 363.0 x 52.0
Package Contents	VG2756-4K x1, 3-pin Plug x1, HDMI Cable (v2.0; Male-Male) x1, USB Type-C Cable (Male-Male) x1, USB A/B Cable (v3.2; Male-Male) x1, Quick Start Guide x1
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907011432



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com