

VP2756-2K - 27" COLORPRO™ 1440P IPS MONITOR WITH 60W USB C, SRGB AND PANTONE VALIDATED

Key Features

**27
DISPLAY****IPS
PANEL****2560 x 1440
RESOLUTION**

Product Description

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-2K QHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-2K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-2K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.

Specifications

More Information

UPC	766907017601
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit
Aspect Ratio	16:9

Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	2
USB Type B	1
USB Type C	60W x 1
HDMI 1.4 In	1
DisplayPort	1
Eco Mode (Conserve)	34.5W
Eco Mode (optimized)	38.5W
Consumption (typical)	40W
Consumption (max)	121W
Voltage	100-240 VAC
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 130 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy
Net (lbs)	15.1
Net Without Stand (lbs)	9.8
Gross (lbs)	21.0
Net (kg)	6.9
Net Without Stand (kg)	4.4

Gross (kg)	9.5
Packaging (in.)	29.1 x 18.3 x 8.9
Physical (in.)	24.1 x 16.15~21.27 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	740.0 x 465.0 x 225.0
Physical (mm)	613.0 x 410.0~540.0 x 215.0
Physical Without Stand (mm)	613.0 x 363.0 x 53.0
Package Contents	VP2756-2K, Power Cable, USB-C Cable, HDMI cable, UAB-A/B Cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907017601



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com