


VX3276-4K-MHD - 32" 4K UHD THIN-BEZEL MONITOR WITH HDMI, DP, AND MINI DP

Key Features

**32
DISPLAY****MVA
PANEL****3840 x 2160
RESOLUTION**

Product Description

The ViewSonic® VX3276-4K-mhd is a sleek 32" (31.5" viewable) 4K UHD monitor with a modern and minimalist style perfect for home use. With SuperClear® MVA panel technology and 80M:1 dynamic contrast ratio, this monitor offers best-in-class screen performance with ultra-wide viewing angles. A sleek edge-to-edge frameless design, combined with stunning 3840 x 2160 resolution, provides incredibly sharp and detailed visuals, while HDR10 content support delivers a high dynamic range of vivid color and contrast for incredible screen performance. Versatile HDMI, DisplayPort, and Mini DisplayPort inputs offer flexible connectivity options for both computing and gaming, while an exclusive ViewMode™ feature provides intuitive presets for optimized screen performance in different applications. With ViewSonic's industry-leading 3-year limited warranty, this monitor is a solid long-term investment that combines style and high performance for the home.

Specifications

	More Information
UPC	766907005820
Screen Size	32
Viewable Area (in.)	31.5
Panel Type	MVA
Display Resolution	3840 x 2160
Display Resolution	4K (3840x2160)
Static Contrast Ratio	2,500:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	WLED
Brightness	300 cd/m2
Colors	16.7M
Color Space Support	8 bit
Aspect Ratio	16:9

Response Time (Typical GTG)	8ms
Response Time (GTG w/OD)	3ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating 3H
PC Resolution (max)	3840 x 2160
Mac® Resolution (max)	3840 x 2160
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Mini DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	24W
Eco Mode (optimized)	34W
Consumption (typical)	53W
Consumption (max)	56W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	Internal
Cable Organization	No
Physical Controls	1,2,3,4,5,6 (power)
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI: 15 ~ 140 KHz, DisplayPort / Mini DP: 24 ~ 140 KHz
Frequency Vertical	HDMI: 24 ~ 75 Hz, DisplayPort / Mini DP: 50 ~ 75 Hz
Digital Sync	TMDS for HDMI (v2.0), PCI-E for DisplayPort (v1.2) and Mini DP (v1.2)
Tilt (Forward/Back)	4° / 15°
Regulations	EPEAT, CEC, MX-CoC, Mexico Energy, CE, CE EMC, CB
Net (lbs)	15.0
Net Without Stand (lbs)	13.7
Gross (lbs)	19.8
Net (kg)	6.8
Net Without Stand (kg)	6.2

Gross (kg)	9.0
Packaging (in.)	33.0 x 20.2 x 4.6
Physical (in.)	28.1 x 19.9 x 9.1
Physical Without Stand (in.)	28.1 x 16.5 x 1.6
Packaging (mm)	838.0 x 514.0 x 118.0
Physical (mm)	713.0 x 507.0 x 230.0
Physical Without Stand (mm)	713.0 x 418.0 x 42.0
Package Contents	VX3276-4K-mhd, Power Cable, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907005820



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 