

VX3211-2K-MHD - 32" 1440P IPS MONITOR WITH HDMI, DISPLAYPORT, VGA AND SRGB

Key Features



32
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description

Whether for office use or home entertainment, the ViewSonic® VX3211-2K-mhd monitor is designed to take your viewing experience to a higher level. The VX3211-2K-mhd is a 32" QHD monitor loaded with solid multimedia features, flexible connectivity options, wide-angle viewing, and amazing screen performance with 99% sRGB color coverage. Featuring stunning 2560 x 1440 resolution and a slim bezel design, this monitor provides 70% more on-screen content than Full HD monitors, making project management and multitasking easier than before. Versatile HDMI, DisplayPort, and VGA* inputs keep you connected to your favorite devices.

*VGA support for up to 1080p resolution only

Specifications

More Information

| | |
|-------------------------------|-----------------|
| UPC | 766907950311 |
| Screen Size | 32 |
| Viewable Area (in.) | 31.5 |
| Panel Type | IPS |
| Display Resolution | 2560 x 1440 |
| Display Resolution | QHD (2560x1440) |
| Static Contrast Ratio | 1,200:1 |
| Dynamic Contrast Ratio | 80M:1 |
| Light Source | LED |
| Brightness | 250 cd/m2 |
| Colors | 1.07B |
| Color Space Support | 10-Bit |

| | |
|------------------------------------|--|
| Aspect Ratio | 16:9 |
| Response Time (Typical GTG) | 8ms |
| Response Time (GTG w/OD) | 3ms |
| Viewing Angles | 178° horizontal, 178° vertical |
| Backlight Life (Hours) | 30,000 |
| Panel Surface | Anti-glare, Hard coating (3H) |
| PC Resolution (max) | 2560 x 1440 |
| Mac® Resolution (max) | 2560 x 1440 |
| 3.5mm Audio In | 1 |
| 3.5mm Audio Out | 1 |
| VGA | 1 |
| HDMI 1.4 In | 1 |
| DisplayPort | 1 |
| Internal Speakers | 2.5W (x2) |
| Eco Mode (Conserve) | 35W |
| Eco Mode (optimized) | 42W |
| Consumption (typical) | 55W |
| Consumption (max) | 65W |
| Voltage | AC 100-240V (universal), 50-60Hz |
| Stand-by | 0.3W |
| Cable Organization | No |
| Kensington Lock Slot | 1 |
| Physical Controls | 1, 2, 3, 4, 5, Power |
| On Screen Display | Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality) |
| Temperature | 32-104° F (0 - 40° C) |
| Humidity (non-condensing) | 20-90% |
| VESA Compatible | 100 x 100 mm |
| Frequency Horizontal | 24 ~ 99KHz |
| Frequency Vertical | 24 ~ 75Hz |
| Analog Sync | Separate Sync / Composite Sync / Sync on Green |
| Digital Sync | TMDS, PCI-E |
| Tilt (Forward/Back) | 5° / 13° |
| Regulations | cULus, FCC-B, ICES003, UL-MX-CoC, Mexico Energy, CE, REACH, EEL, WEEE, EAC, UkrSEPRO |
| Net (lbs) | 15.5 |
| Net Without Stand (lbs) | 13.6 |

| | |
|-------------------------------------|--|
| Gross (lbs) | 22.6 |
| Net (kg) | 7.0 |
| Net Without Stand (kg) | 6.2 |
| Gross (kg) | 10.2 |
| Packaging (in.) | 33.0 x 24.2 x 11.1 |
| Physical (in.) | 28.7 x 19.5 x 9.1 |
| Physical Without Stand (in.) | 28.7 x 17.0 x 2.3 |
| Packaging (mm) | 838 x 615 x 282 |
| Physical (mm) | 729.7 x 495.5 x 230.0 |
| Physical Without Stand (mm) | 729.7 x 432.8 x 58.3 |
| Package Contents | LCD Display, Power Cable , HDMI Cable , Audio Cable , Quick Start Guide |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |
| Warranty | *Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor. |

UPC: 766907950311



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com