


PG701WU - 3500 LUMENS WUXGA PROJECTOR WITH LOW INPUT LAG AND VERTICAL KEYSTONE

## Key Features


---



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



1920 x 1200  
**RESOLUTION**

Flexible connectivity for your favorite devices.



1.1x Optical zoom lens



- x2 HDMI 1.4 (HDCP 1.4)
- x2 VGA (In/Out)
- x1 USB 2.0 Type A
- x1 Ethernet Lan (RJ45)
- x1 S-Video In
- x2 3.5mm Audio In/Out
- x1 RS232 In
- x1 Kensington Lock Slot

## Product Description

---

The ViewSonic® PG701WU WUXGA projector features 3,500 lumens, 1920x1200 native resolution, an intuitive, user-friendly design, and a sleek white chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. With vertical keystone correction, and extensive connectivity options, the PG701WU provides flexible and quick set-up. What's more, an energy-saving SuperEco™ feature reduces power consumption and extends the lamp life by up to 20,000 hours. The PG701WU is the ideal projector for both high-definition presentations and vibrant multimedia entertainment.


## Specifications

---

<b>UPC</b>	766907005875
<b>Light Source</b>	DLP Lamp
<b>Display Resolution</b>	WUXGA (1920x1200)
<b>Display Resolution</b>	1920 x 1200
<b>Brightness (Lumens)</b>	3,500 ANSI
<b>Screen Size</b>	30 - 300 in. / 0.76 - 7.62 m
<b>Throw Distance</b>	3.3 - 36.0 ft / 1.0 m - 11.0 m
<b>Throw Ratio</b>	1.5-1.65
<b>Keystone</b>	Vertical (+/- 40°)
<b>Lens</b>	1.1x optical zoom
<b>Light Source (watt)</b>	203
<b>Light Source Life, Normal (hours)</b>	5000
<b>Light Source Life, Dynamic Eco-Mode (hours)</b>	20000
<b>Color Depth</b>	1.07B Color (R/G/B 10bit)
<b>Aspect Ratio</b>	16:10
<b>Input Lag</b>	37ms
<b>Frequency Horizontal</b>	15K~102KHz
<b>Frequency Vertical</b>	23~120Hz
<b>PC Resolution (max)</b>	1920 x 1200
<b>PC Resolution (min)</b>	640 x 480
<b>Mac® Resolution (max)</b>	1920 x 1200
<b>Mac® Resolution (min)</b>	640 x 480
<b>USB 2.0 Type A</b>	1
<b>3.5mm Audio Out</b>	1
<b>3.5mm Audio In</b>	1
<b>Control (RS232)</b>	1
<b>HDMI 1.4 In</b>	1
<b>HDMI 1.4 (with HDCP 1.4)</b>	1
<b>Internal Speakers</b>	2W (x1)
<b>Consumption (typical)</b>	300W
<b>Stand-by</b>	<0.5W
<b>Physical Controls</b>	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
<b>On Screen Display</b>	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	0-90%

<b>Kensington Lock Slot</b>	1
<b>Net (lbs)</b>	5.7
<b>Gross (lbs)</b>	8.2
<b>Net (kg)</b>	2.6
<b>Gross (kg)</b>	3.7
<b>Packaging (in.)</b>	16.3 x 6.6 x 11.7
<b>Physical (in.)</b>	12.3 x 8.7 x 4.3
<b>Packaging (mm)</b>	415.0 x 168.0 x 297.0
<b>Physical (mm)</b>	312.0 x 222.0 x 108.0
<b>Regulations</b>	FCC, cTUVus, ROHS
<b>Package Contents</b>	PG701WU projector, Power Cable, VGA Cable, Remote Control, Quick Start Guide
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.

UPC: 766907005875



**Contact Sales**  
[ViewSonic.com](http://ViewSonic.com)  
 888.881.8781  
 email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)