


# MYPODIUM™ ID2456 - 24" TOUCH DISPLAY WITH ACTIVE STYLUS AND ADVANCED ERGONOMICS


## Key Features



24  
DISPLAY



PANEL



RESOLUTION



## Product Description

With responsive PCAP touch technology and an MPP2.0 active stylus, the ViewSonic® myPodium™ ID2456 interactive pen display delivers precise control for more productive workspaces and collaborative classrooms. With high-performance touchscreen, this 24" (23.8" viewable) Full HD display provides smooth and responsive touch and pen tracking, along with amazing screen performance, within a sleek and bezel-less design. USB 3.1 Type-C connectivity offers a single-cable plug-and-play solution for laptops and Chromebooks, while HDMI output enables easy screen mirroring or extended desktops ideal for office productivity and podium applications in classrooms. A magnetic stylus pen with 4096 pressure sensitivity and +/- 50-degree tilt lets you write or draw on screen with precision, and easily attaches to the display bezel for secure storage. So whether used on its own on office desktops, as a collaboration station in corporate huddle spaces, or as a front-of-classroom interactive teaching hub, the myPodium™ ID2456 helps to boost efficiency and productivity.

## Specifications

More Information	
<b>UPC</b>	766907019070
<b>Screen Size</b>	24
<b>Viewable Area (in.)</b>	23.8
<b>Display Resolution</b>	1920 x 1080
<b>Static Contrast Ratio</b>	1,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	250 cd/m2
<b>Colors</b>	16.7M
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	14ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical

<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-Glare type, Hardness 6H
<b>Refresh Rate</b>	60Hz
<b>USB Type A</b>	2
<b>USB Type B</b>	1
<b>USB Type C</b>	1
<b>3.5mm Audio In</b>	1
<b>3.5mm Audio Out</b>	1
<b>VGA</b>	1
<b>HDMI 1.4 In</b>	1
<b>Touch Technology</b>	Projective Capacitive
<b>Touch Points</b>	10-Point Touch
<b>Internal Speakers</b>	3W (x2)
<b>Consumption (typical)</b>	33
<b>Consumption (max)</b>	36
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5
<b>Cable Organization</b>	No
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	10-85%
<b>VESA Compatible</b>	100 x 100 mm
<b>Regulations</b>	cTUVus, FCC, Energy Star 8.0, CEC, CE RoHS, REACH, WEEE, BSMI, NOM or UL Mexico CoC (Addendum), Mexico Energy
<b>Net (lbs)</b>	11
<b>Gross (lbs)</b>	17
<b>Net (kg)</b>	5
<b>Gross (kg)</b>	7.7
<b>Packaging (in.)</b>	23.82" (W) x 4.92" (H) x 15.94" (D)
<b>Physical (in.)</b>	13.11" (W) x 1.7" (H) x 21.44" (D)
<b>Packaging (mm)</b>	605mm (W) x 125mm (H) x 405mm(D)
<b>Physical (mm)</b>	333 mm (W) x 43 mm (H) x 545 mm (D)
<b>Package Contents</b>	ID2456, Power cable (1.8m), Type-C cable (1.8m), HDMI cable (1.8m), USB cable (1.8m), MPP2.0 ACP, Pen tether, Pen tip, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907019070



## Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781 

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com) 