

VP3268-4K - 32" FRAMELESS 4K UHD SRGB COLORPRO™ IPS MONITOR

Key Features


- Seamless Viewing Experience
- 4K UHD Resolution
- Loaded with Connectivity
- Ultimate Color Accuracy
- Professional Color Processing Capability



32"
DISPLAY



IPS
PANEL



3840 x 2160
RESOLUTION



Product Description

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP3268-4K UHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek frameless design, the VP3268-4K provides a near-seamless viewing experience ideal for multi-monitor setups. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for incredible color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Add to that 6-axis color adjustment functionality, and this monitor provides the ultimate color processing capability for professional applications. What's more, productivity-boosting features include an advanced ergonomic design. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

[Download the ColorPro brochure.](#)

Specifications

	More Information
UPC	766907903614
Screen Size	32"
Viewable Area (in.)	31.5
Panel Type	IPS
Display Resolution	3840 x 2160
Static Contrast Ratio	1,300:1
Dynamic Contrast Ratio	20M:1
Light Source	LED
Brightness	350 cd/m2
Colors	1.07B
Color Space Support	10bit (8bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	7ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	3840 x 2160
USB Type A	4
USB Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
HDMI 2.0 (with HDCP 2.2)	2
DisplayPort	1
Mini DisplayPort	1
Internal Speakers	5W (x2)
Eco Mode (Conserve)	38W
Eco Mode (optimized)	43W
Consumption (typical)	51W
Consumption (max)	55W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.3W
Cable Organization	No

Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Advanced Image Adjust, Setup Menu, Memory Recall (See user guide for complete OSD functionality)
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~135KHz
Frequency Vertical	24 ~ 75Hz
Digital Sync	Mini-Packet, TMDS for HDMI 2.0
Height Adjust	130 mm / 5.1 in
Swivel	120°
Pivot (Right/Left)	90° / 90°
Regulations	UL, cUL, FCC-B, Mexico CoC, EPEAT Certified, Energy Star, Mexico Energy, CE, CB, RoHS, ErP, REACH, EEL, WEEE, CU/EAC/Ukr (VES apply)
Net (lbs)	22.8
Net Without Stand (lbs)	14.2
Gross (lbs)	32.3
Net (kg)	10.3
Net Without Stand (kg)	6.4
Gross (kg)	14.7
Packaging (in.)	32.9 x 20.8 x 12.6
Physical (in.)	28.1 x 25.0 x 10.5
Physical Without Stand (in.)	28.1 x 16.1 x 2.1
Packaging (mm)	835 x 528 x 320
Physical (mm)	713.6 x 636.1 x 265.3
Physical Without Stand (mm)	713.6 x 410.0 x 52.5
Package Contents	VP3268-4K Display, Power Cable, DP Cable (mini DP to DP), HDMI 2.0 Cable, USB 3.0 UP Stream Cable (Type B to A), Audio Cable (3.5mm audio male to male), Quick Start Guide, ViewSonic Wizard CD-ROM
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907903614



Contact Sales
ViewSonic.com
888.881.8781
email: salesinfo@viewsonic.com