



# VIEWSONIC 4,000 LUMENS WXGA PROJECTOR WITH HDMI AND VERTICAL KEYSTONE | PA503W

## Key Features


- High Brightness DLP Lamp Projector: WXGA (1280x800p) resolution with a 1.5-1.7 throw ratio and 4,000 ANSI lumens for clear, detailed images in any space
- Vibrant Colors: SuperColor technology delivers a wide color gamut and stunningly beautiful images.
- Designed for Fast Paced Content: A low 16ms input latency and 120Hz refresh rate provides faster frame-by-frame action for smooth images with minimal delay
- Large Screen Projection: Projects screen sizes from 80" to 150" with a throw distance of 8.8 ft - 16.4 ft; displays a 100" image from 11 ft
- Easy Setup & Image Adjustment: Features 1.1x optical zoom, 0.8x-2.0x digital zoom, and vertical keystone
- Installation Options: This projector is ceiling mountable; compatible with ViewSonic mount PJ-WMK-007



30 - 300 in. / 0.76 - 7.62 m  
**DISPLAY**



**PANEL**



VGA(640 x 480) to FullHD(1920 x 1080)  
**RESOLUTION**



## Product Description

The ViewSonic® PA503W price-performance projector features 4,000 lumens, native WXGA 1280x800 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wider color range for lifelike image projection. The PA503W also features extensive connectivity including HDMI, 2 x VGA in, Composite Video, 1 x VGA output, and Audio in/out. An energy-saving SuperEco™ feature reduces power consumption by up to 70%, and extends the lamp life by up to 15,000 hours\*. With advanced audiovisual features, flexible connectivity options, and an affordable price, the PA503W is ideal for use in education and small business environments.

\*Energy consumption and lamp life may vary based on actual usage and other factors.

## Specifications

### More Information

<b>UPC</b>	766907904918
<b>Light Source</b>	DLP Lamp
<b>Display Resolution</b>	WXGA (1280x800)
<b>Display Resolution</b>	1280 x 800
<b>Brightness (Lumens)</b>	4,000 ANSI
<b>Screen Size</b>	30 - 300 in. / 0.76 - 7.62 m

<b>Throw Distance</b>	3.28 - 36.02 ft / .99 - 10.98 m
<b>Throw Ratio</b>	1.55~1.70
<b>Keystone</b>	Vertical (+/- 40°)
<b>Lens</b>	1.1x optical zoom
<b>Light Source (watt)</b>	200
<b>Light Source Life, Normal (hours)</b>	6000
<b>Light Source Life, Dynamic Eco-Mode (hours)</b>	15000
<b>Color Depth</b>	30 bits, 1.07B Color (10+10+10)
<b>Dynamic Contrast Ratio</b>	22,000:1
<b>Aspect Ratio</b>	16:10
<b>Input Lag</b>	37ms
<b>Frequency Horizontal</b>	15K~102KHz
<b>Frequency Vertical</b>	23~120MHz
<b>PC Resolution (max)</b>	VGA(640 x 480) to FullHD(1920 x 1080)
<b>Mac® Resolution (max)</b>	VGA(640 x 480) to FullHD(1920 x 1080)
<b>3.5mm Audio Out</b>	1
<b>3.5mm Audio In</b>	1
<b>Control (RS232)</b>	1
<b>HDMI In</b>	1
<b>VGA In</b>	2
<b>VGA Out</b>	1
<b>Composite RCA Video In</b>	1
<b>Mini USB</b>	1
<b>Internal Speakers</b>	2W (x1)
<b>Voltage</b>	100-240V +/- 10%, 50/60Hz AC
<b>Consumption (typical)</b>	260W
<b>Stand-by</b>	<0.5W
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Net (lbs)</b>	4.9
<b>Gross (lbs)</b>	7.1
<b>Net (kg)</b>	2.2
<b>Gross (kg)</b>	3.2
<b>Packaging (in.)</b>	14.4 x 7.4 x 11.8
<b>Physical (in.)</b>	11.6 x 4.3 x 8.6
<b>Packaging (mm)</b>	365 x 188 x 300
<b>Physical (mm)</b>	294 x 110 x 218

**Regulations**

FCC (including ICES003), cTUVus, NOM, TUV-Rheinland S Mark

**Package Contents**

PA503W projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide

**Warranty**

Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

**Recycle/Disposal**

Please dispose of in accordance with local, state or federal laws.

UPC: 766907904918



**Contact Sales**

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)