





VP2785-2K - 27" 1440P ADOBERGB COLORPRO™ IPS MONITOR W/ USB C & FOGRA CERT

Key Features


- Wide QHD resolution
- Amazing Color Accuracy
- Frameless design
- Excellent Screen Uniformity
- Professional Color Processing Capability
- Loaded with Connectivity



27"
DISPLAY



IPS
PANEL



2560 x 1440
RESOLUTION



Product Description

Covering 100% of the Adobe RGB color space and 96% DCI-P3, the ViewSonic® VP2785-2K QHD monitor meets the high color standards of photographers, graphic designers, video editors, print departments, and other design professionals. With a sleek and modern design, the VP2785-2K features future-proof USB Type-C ports, as well as DisplayPort and HDMI. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E<2 value for incredible color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. What's more, productivity-boosting features include an advanced ergonomic design, a built-in ambient light and presence sensor, and a KVM switch. Hardware calibration is also available with the optional ViewSonic Colorbration Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, content creation, and other color-critical applications.

[Download the ColorPro brochure.](#)

Specifications

	More Information
UPC	766907004571
Screen Size	27"
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	WLED
Brightness	300 cd/m2
Colors	1.07B
Color Space Support	10-bit (8 bit + A-FRC)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare, Hard coating (3H)
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	2
USB Type B	1
USB Type C	1
USB Type C - Downstream	1 (15W)
3.5mm Audio Out	1
HDMI 1.4 In	1
DisplayPort	1
DisplayPort Out	1
Eco Mode (Conserve)	30W
Eco Mode (optimized)	35W
Consumption (typical)	40W
Consumption (max)	53W
Voltage	DC 19V

Stand-by	0.5W
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, 3, 4, 5, Power
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu, (See user guide for complete OSD functionality)
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~130KHz
Frequency Vertical	24 ~ 120Hz
Digital Sync	TMDS for HDMI (v1.4), PCI-E for DisplayPort (v1.2), Micro-Packet for Type C
Height Adjust	130 mm / 5.1 in
Swivel	120º
Pivot (Right/Left)	90º / 90º
Regulations	EPEAT, Energy Star
Net (lbs)	14.7
Net Without Stand (lbs)	9.0
Gross (lbs)	22.4
Net (kg)	6.7
Net Without Stand (kg)	4.1
Gross (kg)	10.2
Packaging (in.)	28.3 x 18.1 x 10.6
Physical (in.)	24.1 x 21.5 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	720.0 x 460.0 x 268.0
Physical (mm)	612.0 x 545.0 x 215.0
Physical Without Stand (mm)	612.0 x 363.0 x 55.0
Package Contents	VP2785-2K, AC/DC Adapter + Power Cable, DisplayPort to DisplayPort Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Classification	Discontinued

UPC: 766907004571



Contact Sales
[ViewSonic.com](https://www.viewsonic.com)
888.881.8781
email:
salesinfo@viewsonic.com