

VX2785-2K-MHDU - 27" 1440P THIN-BEZEL IPS FREESYNC MONITOR WITH 60W USB C, HDMI, AND DP

Key Features


- 27 Inch QHD (2560x1440p) IPS monitor with thin bezels and 75Hz refresh rate
- USB-C connectivity for fast data, audio and video transfer, and 60W charging over one cable
- Ergonomic tilt and swivel stand for all-day comfort
- AMD FreeSync technology enables fluid and tear-free gameplay
- The VX2785-2K-MHDU supports laptops, PCs, and Macs with USB C, HDMI, and DisplayPort inputs



27
DISPLAY



IPS
PANEL



2560 X 1440
RESOLUTION



Product Description

Designed for the modern-day home office, the ViewSonic® VX2785-2K-mhdu is a 27" Quad HD IPS monitor that combines style with optimal versatility and functionality. Whether for gaming, streaming, or editing, these sleek and slim displays are engineered with the everyday user in mind. Equipped with AMD FreeSync™ technology*, this monitor's variable refresh rate capabilities virtually eliminate screen tearing and stuttering for a smoother viewing experience. With a three-sided borderless design, thin profile, and thoughtful cable management features, this display transforms the desktop into a streamlined and clutter-free workspace. What's more, a unique ergonomic stand allows you to easily tilt and swivel the screen for maximum comfort. The latest USB 3.2 Type-C connectivity delivers charging power, video, and audio over a single cable, while HDMI and DisplayPort inputs keep you connected to your favorite devices.

*AMD FreeSync supported via HDMI only

Specifications

More Information

UPC	766907003932
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	QHD (2560x1440)
Static Contrast Ratio	1,000:1

Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	300 cd/m ²
Colors	16.7M
Color Space Support	8 Bit (True)
Aspect Ratio	16:9
Response Time (Typical GTG)	14ms
Response Time (GTG w/OD)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	2560 X 1440
Mac® Resolution (max)	2560 X 1440
USB 3.2 Gen 1 Type C	1
3.5mm Audio Out	1
HDMI 1.4 (with HDCP 1.4)	1
DisplayPort	1
Internal Speakers	3W (x2)
Eco Mode (Conserve)	21W
Eco Mode (optimized)	24W
Consumption (typical)	27W
Consumption (max)	108W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
Swivel	30°
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT, CEC, NRCAN, MX-CoC, Mexico Energy
Net (lbs)	11.1
Net Without Stand (lbs)	7.9

Gross (lbs)	15.2
Net (kg)	5.0
Net Without Stand (kg)	3.6
Gross (kg)	6.9
Packaging (in.)	27.6 x 17.2 x 4.9
Physical (in.)	24.1 x 17.6 x 9.8
Physical Without Stand (in.)	24.1 x 14.3 x 2.0
Packaging (mm)	700.0 x 438.0 x 125.0
Physical (mm)	613.0 x 446.0 x 250.0
Physical Without Stand (mm)	613.0 x 364.0 x 50.0
Package Contents	VX2785-2K-mhdu, AC/DC Power Adapter, HDMI Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Final Sale. Sold AS-IS with no warranty on parts or labor. 30-day DOA policy for full refund.

UPC: 766907003932



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com