


VIEWSONIC 22" 1080P IPS DUAL PACK HEAD-ONLY MONITORS WITH FREESYNC, HDMI AND VGA | VA2256-MHD_H2

Key Features

- Versatile Monitors: 22 Inch Full HD (1920x1080p) IPS monitor with thin bezels and 75Hz refresh rate
- Two Monitors: Sold as a dual pack without monitor stands for easy dual-screen installation
- Enhanced Viewing Comfort: Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- No Image Tearing: FreeSync technology enables smooth frame rates to aid you in battle
- Optimized View Settings: Offers "Game," "Movie," "Web," "Text," and "Mono" presets
- Flexible Connectivity: The VA2256-MHD_H2 supports laptops, PCs, Macs and more with HDMI, DisplayPort, and VGA inputs



22
DISPLAY



IPS
PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® VA2256-mhd_H2 dual monitor pack delivers an efficient end-to-end enterprise experience. From easy installation, to recycling, to long-term reliability, this dual monitor solution reduces the total cost of ownership beyond the initial purchase price. Sold as a dual pack of monitors without monitor stands, the VA2256-mhd_H2 ships in biodegradable packaging to minimize recycling costs and waste. Standard VESA-compatible mounting offers easy dual-screen installation, while a 3-sided thin bezel design provides a seamless viewing experience for multi-monitor setups. SuperClear® IPS panel technology delivers wide-angle viewing and incredibly vivid colors. Extensive connectivity options include VGA, HDMI, and DisplayPort so that you can connect to a variety of HD and analog devices – today and tomorrow.

Specifications

| More Information | |
|-------------------------------|---------------------|
| UPC | 766907009873 |
| Screen Size | 22 |
| Viewable Area (in.) | 21.5 |
| Panel Type | IPS |
| Display Resolution | 1920 x 1080 |
| Display Resolution | Full HD (1920x1080) |
| Static Contrast Ratio | 1,000:1 |
| Dynamic Contrast Ratio | 50,000,000:1 |

| | |
|-------------------------------------|-------------------------------------------------------------------------------------|
| Light Source | LED |
| Brightness | 250 cd/m2 |
| Colors | 16.7M |
| Aspect Ratio | 16:9 |
| Response Time (Typical GTG) | 5ms |
| Viewing Angles | 178° horizontal, 178° vertical |
| Backlight Life (Hours) | 30,000 |
| Panel Surface | Anti-glare |
| PC Resolution (max) | 1920x1080 |
| Mac® Resolution (max) | 1920x1080 |
| 3.5mm Audio In | 1 |
| 3.5mm Audio Out | 1 |
| HDMI In | 1 |
| VGA | 1 |
| Internal Speakers | 2W (x2) |
| Eco Mode (Conserve) | 18W |
| Eco Mode (optimized) | 22W |
| Consumption (typical) | 23W |
| Consumption (max) | 31W |
| Voltage | 100-240 VAC, 50-60Hz |
| Stand-by | 0.5W |
| Power Supply | Internal |
| Cable Organization | No |
| Physical Controls | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power) |
| On Screen Display | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu |
| Temperature | 32-104° F (0 - 40° C) |
| Humidity (non-condensing) | 20-90% |
| VESA Compatible | 100 x 100 mm |
| Regulations | cULus FCC-B, ICES003, Energy Star Certified, EPEAT Certified, MX-CoC, Mexico Energy |
| Net Without Stand (lbs) | 12.8 |
| Gross (lbs) | 18.5 |
| Net Without Stand (kg) | 5.8 |
| Gross (kg) | 8.4 |
| Packaging (in.) | 21.4 x 15.7 x 7.1 |
| Physical Without Stand (in.) | 19.3 x 11.7 x 1.9 |
| Packaging (mm) | 544.0 x 400.0 x 180.0 |

| | |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|
| Physical Without Stand (mm) | 490.0 x 297.0 x 48.0 |
| Package Contents | VA2256-MHD_H x2, 3-pin Plug (IEC C13 / CEE22) x2, HDMI Cable (v1.4; Male-Male) x1, DisplayPort Cable (v1.2; Male-Male) x1, Quick Start Guide x2 |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |
| Warranty | Three-year limited warranty on parts, labor and backlight |

UPC: 766907009873



Contact Sales

ViewSonic.com

888.881.8781 

email: salesinfo@viewsonic.com 