



VIEWSONIC 27" COLORPRO™ 1440P IPS MONITOR WITH 60W USB-C, SRGB AND PANTONE VALIDATED | VP2756-2K

Key Features

- 27 Inch QHD (2560x1440p) IPS monitor with thin bezels and 60Hz refresh rate
- In addition to fast data, audio and video transfer, USB-C also provides quick 60W charging over a single cable
- Advanced ergonomics (tilt, swivel, pivot and height) for all-day comfort
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, and Rec. 709 color spaces and Delta E<2 accuracy
- This monitor has been certified as capable of reproducing Pantone Matching System colors
- The VP2756-2K supports laptops, PCs, Macs and more with USB-C, HDMI, USB and DisplayPort inputs

**27
DISPLAY****IPS
PANEL****2560 x 1440
RESOLUTION**

Product Description

Engineered to deliver unmatched color accuracy crucial for professional applications, the ViewSonic® VP2756-2K QHD monitor displays your work with the vivid and lifelike color it deserves. With a SuperClear® IPS panel and a sleek 3-sided frameless design, the VP2756-2K provides a near-seamless viewing experience ideal for multi-monitor setups. The VP2756-2K is equipped with USB-C for single cable connectivity to deliver video, audio, and 60W of power delivery. To ensure precise, uniform color, each of our monitors is factory calibrated to deliver an amazing Delta E <2, so you can be confident what you see on screen is what your clients and customers will see as well.

Specifications

More Information

UPC	766907012965
Screen Size	27
Viewable Area (in.)	27
Panel Type	IPS
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	1,000:1
Dynamic Contrast Ratio	20,000,000:1

Light Source	LED
Brightness	350 cd/m2
Colors	16.7M
Color Space Support	8 bit
Aspect Ratio	16:9
Response Time (Typical GTG)	5ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
PC Resolution (max)	2560 x 1440
Mac® Resolution (max)	2560 x 1440
USB Type A	2
USB Type B	1
USB Type C	60W x 1
HDMI 1.4 In	1
DisplayPort	1
Eco Mode (Conserve)	34.5W
Eco Mode (optimized)	38.5W
Consumption (typical)	40W
Consumption (max)	121W
Voltage	100-240 VAC
Stand-by	0.3W
Power Supply	Internal
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (power), Key 2, Key 3, Key 4, Key 5 (favorite)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	15 ~ 130 KHz
Frequency Vertical	24 ~ 75 Hz
Height Adjust	130 mm / 5.1 in
Swivel	60°
Pivot (Right/Left)	90° / 90°
Regulations	cTUVus, FCC-B, ICES003, CEC, MX-CoC, Mexico Energy

Net (lbs)	15.1
Net Without Stand (lbs)	9.8
Gross (lbs)	21.0
Net (kg)	6.9
Net Without Stand (kg)	4.4
Gross (kg)	9.5
Packaging (in.)	29.1 x 18.3 x 8.9
Physical (in.)	24.1 x 16.15~21.27 x 8.5
Physical Without Stand (in.)	24.1 x 14.3 x 2.1
Packaging (mm)	740.0 x 465.0 x 225.0
Physical (mm)	613.0 x 410.0~540.0 x 215.0
Physical Without Stand (mm)	613.0 x 363.0 x 53.0
Package Contents	VP2756-2K, Power Cable, USB-C Cable, HDMI cable, UAB-A/B Cable
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907012965



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com