




## VIEWSONIC 38" COLORPRO™ 21:9 CURVED WQHD+ IPS MONITOR WITH 90W USB-C, RJ45 AND SRGB | VP3881A


### Key Features

---


- 38 Inch ultrawide 21:9 WQHD+ (3840x1600p) 2300R curved monitor with IPS, thin bezels and HDR10
- Ethernet RJ45 and USB-C connectivity for fast data, audio and video transfer, 90W charging over one cable
- Advanced ergonomics (tilt, swivel, and height) for all-day comfort
- Flicker-Free technology and Blue Light Filter for reduced eye fatigue
- 100% sRGB, EBU, SMPTE-C, Rec. 709, DCI-P3, and DICOM-SIM color spaces and Delta E<2 accuracy
- Hardware calibrated to ensure that the color displayed perfectly matches the original file
- The VP3881A supports laptops, PCs, Macs and more with USB C, HDMI, USB and DisplayPort inputs



38"  
**DISPLAY**



IPS  
**PANEL**



3840 x 1600  
**RESOLUTION**



### Product Description

---


With an immersive curved screen and stunning WQHD+ 3840x1600 resolution, the ViewSonic® VP3881a monitor elevates your viewing experience from flat to panoramic. Delivering incredible detail and vivid colors across wide viewing angles, this monitor is engineered to provide incredible color accuracy, while HDR10 content support delivers a wide dynamic range of vivid colors and rich contrast. Thanks to an expansive 38" (37.5" viewable) frameless screen, ultra-wide 21:9 aspect ratio, and integrated speakers, this monitor is ideal for video editing, content development, and other color-critical applications. With a sleek and modern design, the VP3881a features a future-proof USB Type-C port as well as DisplayPort technology, and HDMI. What's more, HDCP 2.2 content protection is standard across all ports to provide secure 4K content playback, streaming and gaming. The VP3881a provides an amazing Delta E<2 value precise color accuracy. An integrated color uniformity function ensures consistent chromaticity across the screen, while a 14-bit 3D look-up table generates a stunningly smooth palette of 4.39 trillion colors. Hardware calibration is also available with the optional ViewSonic Colorbration™ Kit, which allows you to quickly and easily calibrate the monitor for photography, graphic design, and other professional applications.

# Specifications

|                             | More Information                             |
|-----------------------------|----------------------------------------------|
| UPC                         | 766907013573                                 |
| Screen Size                 | 38"                                          |
| Viewable Area (in.)         | 37.5                                         |
| Panel Type                  | IPS                                          |
| Display Resolution          | 3840 x 1600                                  |
| Static Contrast Ratio       | 1,000:1                                      |
| Dynamic Contrast Ratio      | 20,000,000:1                                 |
| Light Source                | LED                                          |
| Brightness                  | 300 cd/m2                                    |
| Color Space Support         | 10 bit (8 bit + A-FRC)                       |
| Aspect Ratio                | 21:9                                         |
| Response Time (Typical GTG) | 5ms                                          |
| Viewing Angles              | 178º horizontal, 178º vertical               |
| Backlight Life (Hours)      | 30,000                                       |
| Panel Surface               | Anti-Glare type, Hard-coating (3H), Haze 25% |
| PC Resolution (max)         | 3840 x 1600                                  |
| Mac® Resolution (max)       | 3840 x 1600                                  |
| USB Type A                  | 2                                            |
| USB Type B                  | 1                                            |
| USB Type C                  | 90W x 1                                      |
| 3.5mm Audio Out             | 1                                            |
| Ethernet LAN (RJ45)         | 1                                            |
| HDMI 2.0 In                 | 2                                            |
| DisplayPort                 | 1                                            |
| Internal Speakers           | 5W (x2)                                      |
| Eco Mode (Conserve)         | 36W                                          |
| Eco Mode (optimized)        | 41W                                          |
| Consumption (typical)       | 52W                                          |
| Consumption (max)           | 217W                                         |
| Voltage                     | 100-240 VAC, 50-60Hz                         |
| Stand-by                    | 0.3W                                         |
| Power Supply                | External                                     |
| Cable Organization          | No                                           |

|                                     |                                                                                         |
|-------------------------------------|-----------------------------------------------------------------------------------------|
| <b>Kensington Lock Slot</b>         | 1                                                                                       |
| <b>Physical Controls</b>            | Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)                                    |
| <b>On Screen Display</b>            | Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu     |
| <b>Temperature</b>                  | 32-104° F (0 - 40° C)                                                                   |
| <b>Humidity (non-condensing)</b>    | 20-90%                                                                                  |
| <b>VESA Compatible</b>              | 100 x 100 mm                                                                            |
| <b>Frequency Horizontal</b>         | 15 ~ 135 KHz                                                                            |
| <b>Frequency Vertical</b>           | 24 ~ 75 Hz                                                                              |
| <b>Height Adjust</b>                | 130 mm / 5.1 in                                                                         |
| <b>Swivel</b>                       | 120°                                                                                    |
| <b>Tilt (Forward/Back)</b>          | 1° / 21°                                                                                |
| <b>Regulations</b>                  | cTUVus, FCC-B, ICES003, Energy Star certified, CEC, NOM, Mexico Energy                  |
| <b>Net (lbs)</b>                    | 27.7                                                                                    |
| <b>Net Without Stand (lbs)</b>      | 17.4                                                                                    |
| <b>Gross (lbs)</b>                  | 41.8                                                                                    |
| <b>Net (kg)</b>                     | 12.6                                                                                    |
| <b>Net Without Stand (kg)</b>       | 7.9                                                                                     |
| <b>Gross (kg)</b>                   | 18.9                                                                                    |
| <b>Packaging (in.)</b>              | 41.2 x 23.2 x 14.8                                                                      |
| <b>Physical (in.)</b>               | 35.5 x 19.6~24.8 x 11.8                                                                 |
| <b>Physical Without Stand (in.)</b> | 35.3 x 15.7 x 4.1                                                                       |
| <b>Packaging (mm)</b>               | 1046.0 x 590.0 x 375.0                                                                  |
| <b>Physical (mm)</b>                | 896.0 x 499.0~699.0 x 299.0                                                             |
| <b>Physical Without Stand (mm)</b>  | 896.0 x 398.0 x 103.0                                                                   |
| <b>Package Contents</b>             | VP3881a, AC Adapter, HDMI Cable, DisplayPort Cable, USB Type-C Cable, Quick Start Guide |
| <b>Recycle/Disposal</b>             | Please dispose of in accordance with local, state or federal laws.                      |
| <b>Warranty</b>                     | Three-year limited warranty on parts, labor and backlight                               |

UPC: 766907013573



## Contact Sales

[ViewSonic.com](https://www.viewsonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)