



VIEWSONIC 6,000 LUMENS WUXGA SHORT THROW LASER PROJECTOR W PORTRAIT MODE AND DUAL HDMI | LS921WU

Key Features


- Short Throw Laser Projector: WUXGA (1920x1200p) resolution with a 0.8 throw ratio and 6,000 ANSI lumens for bright, detailed images in compact spaces
- Vibrant Colors & HDR Support: SuperColor technology and HDR/HGL compatibility deliver a wide color gamut with enhanced contrast and visual depth
- Golf Mode for Realistic Simulation: Designed for immersive play, Golf Mode supports major golf simulators for lifelike play on world-class virtual courses
- Designed for Fast Paced Content: A low 16ms input latency and 120Hz refresh rate provides faster frame-by-frame action for smooth images with minimal delay
- Large Screen Projection: Projects screen sizes from 30" to 200" with a throw distance of 3.4 ft - 11.5 ft; displays a 100" image from 5.7 ft
- Easy Setup & Image Adjustment: 1.1x optical zoom, 0.8x-2.0x digital zoom, H/V keystone, 360-degree projection, portrait mode, and 4-corner adjustment
- Advanced LAN Control: Remotely schedule and manage the projector via Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic vController
- Installation Options: This projector is ceiling mountable; compatible with ViewSonic mount PJ-WMK-007



30 - 300 in. / 0.76 - 7.62 m
DISPLAY



PANEL



3840 x 2160
RESOLUTION



Product Description

Bright and versatile for any professional installation, the ViewSonic® LS921WU WUXGA short throw laser projector delivers everything you need for big screens in big venues. Delivering 6,000 ANSI lumens of advanced high brightness, up to 20,000 hours* of light source life, and a screen size of up to 200", this projector is ideal for auditoriums, restaurants, gyms and other large venues. This top-notch performer is also easy to deploy and manage with its short-throw lens, 1.1x optical zoom adjustment, wide lens shift, 360° projection, and portrait mode that provide extreme flexibility in even the most challenging installations. Dual HDMI 2.0b / HDCP 2.2 ports ensure access to original 4K quality content with HDR/HLG support. In addition, its compact size and built-in HDBaseT deliver the perfect mix of high-quality projection and cost-effectiveness. *Light source life may vary based on actual usage and other factors.

Specifications

More Information

| | |
|---------------------|--------------|
| UPC | 766907008739 |
| Light Source | Laser |

| | |
|--|--|
| Display Resolution | WUXGA (1920x1200) |
| Display Resolution | 1920 x 1200 |
| Brightness (Lumens) | 6,000 ANSI |
| Screen Size | 30 - 300 in. / 0.76 - 7.62 m |
| Throw Distance | 1.04-3.83m (100"@1.74m) |
| Throw Ratio | 0.81-0.89 |
| Keystone | Vertical (+/- 40°) / Horizontal (+/- 40°) |
| Lens | 1.1x optical zoom |
| Light Source (watt) | Nichia 74W x 2 |
| Light Source Life, Normal (hours) | 20000 |
| Color Depth | 1.07 Billion Colors |
| Dynamic Contrast Ratio | 3,000,000:1 |
| Aspect Ratio | 16:10 |
| Input Lag | 37ms |
| Lens Shift | Horizontal (50%, -50%) / Vertical (+23%, -23%) |
| Frequency Horizontal | 15K~135KHz |
| Frequency Vertical | 23-120Hz |
| PC Resolution (max) | 3840 x 2160 |
| PC Resolution (min) | 640 x 480 |
| Mac® Resolution (max) | 3840 x 2160 |
| Mac® Resolution (min) | 640 x 480 |
| USB 2.0 Type A | 1 |
| Ethernet LAN (RJ45) | 1 |
| 3.5mm 12V Trigger | 1 |
| 3.5mm Audio Out | 1 |
| 3.5mm Audio In | 1 |
| Control (RS232) | 1 |
| HDMI 2.0 (with HDCP 2.2) | 2 |
| VGA In | 1 |
| VGA Out | 1 |
| Composite RCA Video In | 1 |
| RCA Audio In (L/R) | 1 |
| 3D VESA | 1 |
| HDBT | 1 |
| Internal Speakers | 10W (x2) |
| Voltage | 100-120V+/- 10%, 50/60Hz |

| | |
|------------------------------|---|
| Consumption (typical) | 450W |
| Stand-by | <0.5W |
| Physical Controls | Keypad, Power key |
| On Screen Display | Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality) |
| Temperature | 32-104° F (0 - 40° C) |
| Kensington Lock Slot | 1 |
| Net (lbs) | 14.3 |
| Gross (lbs) | 19.8 |
| Net (kg) | 6.5 |
| Gross (kg) | 9.0 |
| Packaging (in.) | 20.3 x 19.3 x 10.9 |
| Physical (in.) | 15.9 x 12.0 x 5.7 |
| Packaging (mm) | 515.0 x 490.0 x 276.0 |
| Physical (mm) | 405.0 x 305.0 x 145.0 |
| Regulations | cTUVus |
| Package Contents | LS921WU projector, power cable, remote control, Quick Start Guide |
| Warranty | Five-year limited warranty on parts and labor, 1-year limited warranty on the light source, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration). |
| Recycle/Disposal | Please dispose of in accordance with local, state or federal laws. |

UPC: 766907008739



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com