


VX3218C-2K - 32" CURVED 1440P 1MS 165HZ GAMING MONITOR WITH FREESYNC PREMIUM

Key Features



31.5"
DISPLAY



MVA
PANEL



2560x1440
RESOLUTION



GREAT VISUALS
For home entertainment and gaming

Product Description

With an immersive 1500R curved screen and stunning WQHD 2560 x 1440 resolution, the ViewSonic® VX3218C-2K monitor provides an incredible viewing experience for work or play. With features including a 165Hz* refresh rate, 1ms (MPRT) response time and AMD FreeSync technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. The VX3218C-2K also comes equipped with ViewSonic exclusive ViewMode™ presets, which deliver optimized screen performance for enhanced home entertainment. Enjoy watching movies, editing files and playing video games like never before. Two HDMI (v2.0) inputs and one DisplayPort (v1.2) input offer flexible connectivity for both general use and entertainment. *165Hz refresh rate with DisplayPort

Specifications

UPC	766907022162
Screen Size	31.5"
Viewable Area (in.)	31.5
Panel Type	MVA
Display Resolution	2560 x 1440
Display Resolution	WQHD (2560x1440)
Static Contrast Ratio	3,500:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Aspect Ratio	16:9
Response Time (Typical GTG)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-glare
Curvature	1500R
Refresh Rate	165Hz
PC Resolution (max)	2560x1440
Mac® Resolution (max)	2560x1440
3.5mm Audio Out	1
HDMI 1.4 In	2
DisplayPort	1
Internal Speakers	2W (x2)
Eco Mode (Conserve)	23W
Eco Mode (optimized)	28W
Consumption (typical)	34W
Consumption (max)	43W
Voltage	AC 100-240V (universal), 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)

Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI (v1.4): 30 ~ 230KHz, DisplayPort (v1.4): 30 ~230KHz
Frequency Vertical	HDMI (v1.4): 48 ~ 144Hz, DisplayPort (v1.4): 48 ~ 165Hz
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC, NRCAN, NOM, Mexico Energy, CE, CE EMC, CB, RoHS
Net (lbs)	10.6
Net Without Stand (lbs)	9.3
Gross (lbs)	15.0
Net (kg)	4.8
Net Without Stand (kg)	4.2
Gross (kg)	6.8
Packaging (in.)	38.2 x 20.6 x 6.7
Physical (in.)	27.9 x 20.2 x 9.0
Physical Without Stand (in.)	27.9 x 16.6 x 3.8
Packaging (mm)	970.0 x 523.0 x 170.0
Physical (mm)	709.0 x 513.0 x 228.0
Physical Without Stand (mm)	709.0 x 421.0 x 96.0
Package Contents	VX3218C-2K, 3-pin Plug (1EC C13 / CEE22), DisplayPort Cable (1.2; Male-Male), AC/DC Adapter, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907022162



Contact Sales

ViewSonic.com

888.881.8781

email:

salesinfo@viewsonic.com