

VX3418-2K - 34" 1440P 1MS 165HZ ERGONOMIC GAMING MONITOR WITH FREESYNC PREMIUM

Key Features



34
DISPLAY



MVA
PANEL



3440 x 1440
RESOLUTION



Product Description

Featuring QHD 3440 x 1440p resolution, an enhanced ergonomic design, and an ultrawide 21:9 aspect ratio, the ViewSonic VX3418-2K monitor helps elevate both work and play. With features including a rapid-fire 165Hz* refresh rate, 1ms (MPRT) response time and AMD FreeSync Premium™ technology, this monitor virtually eliminates screen tearing and stuttering for a fluid gaming experience. Plus, with an expansive 34" display, this monitor gives you the big-picture clarity you need to get the job done whether you're looking at virtual battlefields or spreadsheets. The VX3418-2K also comes equipped with ViewSonic exclusive ViewMode™ presets, which offer optimized screen performance for movie watching, file editing, video games and so much more. Two HDMI (v2.0) inputs, one DisplayPort (v1.4) input, and one USB-A (v2.0) input offer flexible connectivity so you can directly connect your keyboard, mouse and other peripherals.

Change the way you work and play with the VX3418-2K monitor today.

*165Hz refresh rate with DisplayPort only

Specifications

	More Information
UPC	766907031072
Screen Size	34
Viewable Area (in.)	34
Panel Type	MVA
Display Resolution	3440 x 1440
Display Resolution	UWQHD (3440x1440)
Static Contrast Ratio	4,000:1
Dynamic Contrast Ratio	80,000,000:1
Light Source	LED
Brightness	300 cd/m2

Colors	16.7M
Color Space Support	8 bit true
Aspect Ratio	21:9
Response Time (Typical GTG)	3ms
Response Time (MPRT)	1ms
Viewing Angles	178° horizontal, 178° vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	165Hz
PC Resolution (max)	3440 x 1440
Mac® Resolution (max)	3440 x 1440
USB Type A	1
3.5mm Audio Out	1
HDMI 2.0 In	2
DisplayPort	1
Eco Mode (Conserve)	24W
Eco Mode (optimized)	32W
Consumption (typical)	43W
Consumption (max)	45W
Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5W
Power Supply	External
Cable Organization	No
Physical Controls	Key 1 (favorite), Key 2, Key 3, Key 4, Key 5, Key 6 (power)
On Screen Display	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 2.0: 24 ~ 150 KHz, DisplayPort 1.4: 30 ~ 254 KHz
Frequency Vertical	HDMI 2.0: 48 ~ 100 Hz, DisplayPort 1.4: 48 ~ 165 Hz
Height Adjust	140 mm / 5.5 in
Swivel	90°
Tilt (Forward/Back)	5° / 20°
Regulations	cTUVus, FCC-B, ICES003, CEC, RoHS, WEEE
Net (lbs)	15.6
Net Without Stand (lbs)	11.3

Gross (lbs)	21.5
Net (kg)	7.1
Net Without Stand (kg)	5.1
Gross (kg)	9.8
Packaging (in.)	36.7 x 19.6 x 8.4
Physical (in.)	32.1 x 18.8-23 x 10.4
Physical Without Stand (in.)	32.1 x 14 x 1.6
Packaging (mm)	993.0 x 498.0 x 213.0
Physical (mm)	814.2 x 478.1-584.0 x 264.3
Physical Without Stand (mm)	814.2 x 356.0 x 41.7
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907031072



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com