


VIEWSONIC 5,000 ANSI LUMENS WUXGA ULTRA SHORT THROW LASER INSTALLATION PROJECTOR | LS832WU

Key Features


- Ultra-Short Throw Laser Projector: WUXGA (1920x1200p) resolution with a 0.25 throw ratio and 5,000 ANSI lumens for bright, detailed images in compact spaces
- Vibrant Colors & HDR Support: SuperColor technology and HDR/HGL compatibility deliver a wide color gamut with enhanced contrast and visual depth
- Flexible Screen Size & Throw Range: Projects screen sizes from 30" to 150" with a throw distance of 6" - 19"; displays a 100" image from 11 inches away
- Easy Setup & Image Adjustment: Features 0.8x-2.0x digital zoom, horizontal/vertical keystone, and 4-corner correction for flexible setup
- Advanced LAN Control: Remotely schedule and manage the projector via Crestron, AMX, Extron, PJ Link, ATEN, and ViewSonic vController
- Instant Power On/Off: Enables quick startup and shutdown with optional settings for automatic power control
- Versatile Installation Options: Supports table or ceiling installation and is compatible with ViewSonic mounts PJ-WMK-305 and PJ-WMK-007



87 - 120 in. / 2.21 - 3.05 m
DISPLAY



PANEL



3840 x 2160
RESOLUTION



Product Description

The ViewSonic® ultra-short throw LS832WU projector is the ultimate digital signage solution for public and commercial spaces such as auditoriums, museums, storefronts, shopping malls and airports. Featuring laser phosphor technology, the LS832WU projector delivers 5,000 ANSI lumens of brightness to ensure crisp images even in spaces with ambient lighting. Enjoy a maintenance-free projection experience without having to deal with complicated lamp replacements. An ultra-short throw ratio enables this projector to create 100" images from just 11" away. Enjoy screen sizes up to 170" at a lower cost-per-inch compared to commercial displays. The LS832WU laser projector comes loaded with features like H/V keystone, automated four corner adjustment and flexible installation options. Enjoy comprehensive LAN control for centralized management and compatibility with Crestron, AMX, Extron and PJ Link AV control systems.

Specifications

	More Information
UPC	766907021912
Light Source	Laser
Display Resolution	WUXGA (1920x1200)
Display Resolution	1920 x 1200

Brightness (Lumens)	5,000 ANSI
Screen Size	87 - 120 in. / 2.21 - 3.05 m
Throw Distance	0.17-0.66m (100"@0.28m)
Throw Ratio	0.253
Keystone	Vertical (+/- 10°) / Horizontal (+/- 10°)
Lens	Fixed Zoom
Light Source (watt)	Laser
Light Source Life, Normal (hours)	20000
Light Source Life, Dynamic Eco-Mode (hours)	30000
Color Depth	1.07 Billion Colors
Dynamic Contrast Ratio	3,000,000:1
Aspect Ratio	16:10
Input Lag	37ms
Frequency Horizontal	15K- 91KHz
Frequency Vertical	24- 85Hz
PC Resolution (max)	3840 x 2160
PC Resolution (min)	640 x 480
Mac® Resolution (max)	3840 x 2160
Mac® Resolution (min)	640 x 480
USB 2.0 Type A	1
USB 2.0 Type B	1
Ethernet LAN (RJ45)	1
3.5mm Audio Out	1
3.5mm Audio In	1
3.5mm Mic In	1
Control (RS232)	1
HDMI 2.0 (with HDCP 2.2)	2
VGA In	1
VGA Out	1
Internal Speakers	10W (x1)
Voltage	100-240V+/- 10%, 50/60Hz AC
Consumption (typical)	328W
Stand-by	<0.5W
Physical Controls	Keypad, Power key
On Screen Display	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Temperature	32-104° F (0 - 40° C)
Kensington Lock Slot	1
Net (lbs)	12.8
Gross (lbs)	17.9
Net (kg)	5.8
Gross (kg)	8.1
Packaging (in.)	20.4 x 16.5 x 12.3
Physical (in.)	15.0 x 12.5 x 5.2
Packaging (mm)	518.0 x 420.0 x 313.0
Physical (mm)	382.0 x 318.0 x 132.0
Regulations	cTUVus
Package Contents	LS832WU projector, power cable, remote control, Quick Start Guide
Warranty	Three-year limited warranty on parts and labor, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.

UPC: 766907021912



Contact Sales

ViewSonic.com

888.881.8781

email: salesinfo@viewsonic.com