VIEWSONIC 22" 1080P SINGLE POINT RESISTIVE TOUCH MONITOR WITH USB, HDMI, DVI AND VGA | TD2211

Key **Features**

• 22 Inch Full HD (1920x1080p) LED touch monitor with 75Hz refresh rate


• Robust single-point resistive touch technology feature a robust, pressure-sensing touchscreen

• 20M:1 MEGA Dynamic Contrast Ratio delivers sharp, crisp images


• MacOS users can access touch and gesture controls on touch displays connected to their Apple devices using ViewSonic's vTouch driver. Not available for iPhone and iPad

• The TD2211 supports laptops, PCs, Macs and POS Systems with USB, DVI-D, HDMI, and VGA inputs






22"
DISPLAY



MVA
PANEL



1920 x 1080
RESOLUTION



Product **Description**

Featuring a robust 22” touchscreen, the ViewSonic® TD2211 touch display is ideal for use in retail, POS and commercial environments.

Each display comes equipped with resistive touch technology, making it responsive to hands, gloves and styluses alike.

The TD2211 combines Full HD resolution with a 20M:1 dynamic contrast ratio to deliver crystal clear images.

Enjoy flexible connectivity options including HDMI, VGA, DVI and USB ports as well as a VESA-compatible mount design that makes it easy to transform your device into a wall mounted display.

Specifications

More Information	
UPC	766907022988
Screen Size	22"
Viewable Area (in.)	21.5
Panel Type	MVA
Display Resolution	1920 x 1080
Static Contrast Ratio	3,000:1
Dynamic Contrast Ratio	20,000,000:1
Light Source	LED
Brightness	250 cd/m2
Colors	16.7M
Color Space Support	8 bits
Aspect Ratio	16:9
Response Time (Typical GTG)	6.8ms
Viewing Angles	178º horizontal, 178º vertical
Backlight Life (Hours)	30,000
Panel Surface	Anti-Glare type, Hard-coating (3H), Haze 25%
Refresh Rate	75Hz
PC Resolution (max)	1920 x 1080
Mac® Resolution (max)	1920 x 1080
USB Type A	2
USB Type B	1
3.5mm Audio In	1
3.5mm Audio Out	1
VGA	1
DVI-D	1
HDMI 1.4 In	1
Touch Technology	Resistive
Touch Points	1-Point Touch
Internal Speakers	2W (x2)
Eco Mode (Conserve)	18w
Eco Mode (optimized)	21w
Consumption (typical)	23.5w
Consumption (max)	26.8w

Voltage	100-240 VAC, 50-60Hz
Stand-by	0.5w
Cable Organization	No
Kensington Lock Slot	1
Physical Controls	1, 2, Up, Down, Power
On Screen Display	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
Temperature	32-104º F (0 - 40º C)
Humidity (non-condensing)	20-90%
VESA Compatible	100 x 100 mm
Frequency Horizontal	HDMI 1.4 = 24 ~ 84 KHz / RGB Analog / DVI-D = 24 ~ 82 KHz
Frequency Vertical	HDMI 1.4 / RGB Analog / DVI-D = 50 ~75 Hz
Tilt (Forward/Back)	5º / 20º
Regulations	cTUVus, FCC-B, ICES003, Energy Star, EPEAT Silver, CEC, NOM, Mexico Energy
Net (lbs)	9.6
Net Without Stand (lbs)	7.7
Gross (lbs)	13.4
Net (kg)	4.4
Net Without Stand (kg)	3.5
Gross (kg)	6.1
Packaging (in.)	22.8 " (W) x 17.5 " (H) x 7.9 " (D)
Physical (in.)	20.4 " (W) x 14.8 " (H) x 9.4 " (D)
Physical Without Stand (in.)	20.4 " (W) x 12.1 " (H) x 2.2 " (D)
Packaging (mm)	580 mm (W) x 445 mm (H) x 200 mm (D)
Physical (mm)	519 mm (W) x 377 mm (H) x 240 mm (D)
Physical Without Stand (mm)	519 mm (W) x 308 mm (H) x 55 mm (D)
Package Contents	LCD Display, Power Cable, HDMI Cable, USB Type A/B cable, Audio Cable, Quick Start Guide
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Warranty	Three-year limited warranty on parts, labor and backlight

UPC: 766907022988







Contact Sales
ViewSonic.com
888.881.8781
email: salesinfo@viewsonic.com