


## VIEWSONIC 22" 1080P SINGLE POINT RESISTIVE TOUCH MONITOR WITH USB, HDMI, DVI AND VGA | TD2211

### Key Features

---

- 22 Inch Full HD (1920x1080p) LED touch monitor with 75Hz refresh rate
- Robust single-point resistive touch technology feature a robust, pressure-sensing touchscreen
- 20M:1 MEGA Dynamic Contrast Ratio delivers sharp, crisp images
- MacOS users can access touch and gesture controls on touch displays connected to their Apple devices using ViewSonic's vTouch driver. Not available for iPhone and iPad
- The TD2211 supports laptops, PCs, Macs and POS Systems with USB, DVI-D, HDMI, and VGA inputs



22"  
DISPLAY



MVA  
PANEL



1920 x 1080  
RESOLUTION



### Product Description

---

Featuring a robust 22" touchscreen, the ViewSonic® TD2211 touch display is ideal for use in retail, POS and commercial environments.

Each display comes equipped with resistive touch technology, making it responsive to hands, gloves and styluses alike.

The TD2211 combines Full HD resolution with a 20M:1 dynamic contrast ratio to deliver crystal clear images.

Enjoy flexible connectivity options including HDMI, VGA, DVI and USB ports as well as a VESA-compatible mount design that makes it easy to transform your device into a wall mounted display.

# Specifications

---

	More Information
<b>UPC</b>	766907022988
<b>Screen Size</b>	22"
<b>Viewable Area (in.)</b>	21.5
<b>Panel Type</b>	MVA
<b>Display Resolution</b>	1920 x 1080
<b>Static Contrast Ratio</b>	3,000:1
<b>Dynamic Contrast Ratio</b>	20,000,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	250 cd/m2
<b>Colors</b>	16.7M
<b>Color Space Support</b>	8 bits
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	6.8ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-Glare type, Hard-coating (3H), Haze 25%
<b>Refresh Rate</b>	75Hz
<b>PC Resolution (max)</b>	1920 x 1080
<b>Mac® Resolution (max)</b>	1920 x 1080
<b>USB Type A</b>	2
<b>USB Type B</b>	1
<b>3.5mm Audio In</b>	1
<b>3.5mm Audio Out</b>	1
<b>VGA</b>	1
<b>DVI-D</b>	1
<b>HDMI 1.4 In</b>	1
<b>Touch Technology</b>	Resistive
<b>Touch Points</b>	1-Point Touch
<b>Internal Speakers</b>	2W (x2)
<b>Eco Mode (Conserve)</b>	18w
<b>Eco Mode (optimized)</b>	21w
<b>Consumption (typical)</b>	23.5w
<b>Consumption (max)</b>	26.8w

<b>Voltage</b>	100-240 VAC, 50-60Hz
<b>Stand-by</b>	0.5w
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1, 2, Up, Down, Power
<b>On Screen Display</b>	Auto Image Adjust, Contrast/Brightness, Input Select, Audio Adjust, Color Adjust, Information, Manual Image Adjust, Setup Menu, Memory Recall
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	HDMI 1.4 = 24 ~ 84 KHz / RGB Analog / DVI-D = 24 ~ 82 KHz
<b>Frequency Vertical</b>	HDMI 1.4 / RGB Analog / DVI-D = 50 ~ 75 Hz
<b>Tilt (Forward/Back)</b>	5° / 20°
<b>Regulations</b>	cTUVus, FCC-B, ICES003, Energy Star, EPEAT Silver, CEC, NOM, Mexico Energy
<b>Net (lbs)</b>	9.6
<b>Net Without Stand (lbs)</b>	7.7
<b>Gross (lbs)</b>	13.4
<b>Net (kg)</b>	4.4
<b>Net Without Stand (kg)</b>	3.5
<b>Gross (kg)</b>	6.1
<b>Packaging (in.)</b>	22.8 " (W) x 17.5 " (H) x 7.9 " (D)
<b>Physical (in.)</b>	20.4 " (W) x 14.8 " (H) x 9.4 " (D)
<b>Physical Without Stand (in.)</b>	20.4 " (W) x 12.1 " (H) x 2.2 " (D)
<b>Packaging (mm)</b>	580 mm (W) x 445 mm (H) x 200 mm (D)
<b>Physical (mm)</b>	519 mm (W) x 377 mm (H) x 240 mm (D)
<b>Physical Without Stand (mm)</b>	519 mm (W) x 308 mm (H) x 55 mm (D)
<b>Package Contents</b>	LCD Display, Power Cable, HDMI Cable, USB Type A/B cable, Audio Cable, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	Three-year limited warranty on parts, labor and backlight

UPC: 766907022988



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)