

# VG2756A-2K - 27" 1440P ERGONOMIC IPS DOCKING MONITOR WITH 100W USB C, RJ45 AND DAISY CHAIN

## Key Features



27  
DISPLAY



IPS  
PANEL



2560 X 1440  
RESOLUTION



## Product Description

Designed to boost productivity and maximize output, the ViewSonic® VG2756a-2K is a 27" QHD docking monitor that transforms your desktop into a streamlined and efficient workspace. Enjoy reliable and flexible network connectivity with the integrated gigabit Ethernet port, while the USB Type-C connectivity allows easy single-cable connectivity to provide data, audio, video and up to 100w power delivery. DisplayPort out allows easy Daisy Chain capability for a dual monitor set-up for additional screen real estate. That's not all, the integrated USB hub allows easy connectivity for your peripherals and accessories. A best-in-class ergonomic design features 40-degree tilt and bi-directional pivot so your screen and workspace are as comfortable as you need. In addition, the included vDisplay software gives you quick and easy OSD control, as well as customized screen templates for easy multi-tasking. This monitor is also shipped in eco-friendly biodegradable packaging, along with an easy-to-install quick release stand that makes for quick deployment and a lower total cost of ownership.

## Specifications

More Information	
<b>UPC</b>	766907024487
<b>Screen Size</b>	27
<b>Viewable Area (in.)</b>	27
<b>Panel Type</b>	IPS
<b>Display Resolution</b>	2560 x 1440
<b>Display Resolution</b>	QHD (2560x1440)
<b>Static Contrast Ratio</b>	1,000:1
<b>Dynamic Contrast Ratio</b>	80,000,000:1
<b>Light Source</b>	LED
<b>Brightness</b>	350 cd/m2
<b>Colors</b>	16.7M

<b>Color Space Support</b>	8 bit true
<b>Aspect Ratio</b>	16:9
<b>Response Time (Typical GTG)</b>	5ms
<b>Viewing Angles</b>	178° horizontal, 178° vertical
<b>Backlight Life (Hours)</b>	30,000
<b>Panel Surface</b>	Anti-glare, Hard coating (3H)
<b>PC Resolution (max)</b>	2560 X 1440
<b>Mac® Resolution (max)</b>	2560 X 1440
<b>USB Type A</b>	2
<b>USB Type B</b>	1
<b>USB Type C</b>	98W x 1
<b>Ethernet LAN (RJ45)</b>	1
<b>HDMI 1.4 In</b>	1
<b>DisplayPort</b>	1
<b>DisplayPort Out</b>	1
<b>Internal Speakers</b>	2W (x2)
<b>Eco Mode (Conserve)</b>	20.8W
<b>Eco Mode (optimized)</b>	25.1W
<b>Consumption (typical)</b>	30.7W
<b>Consumption (max)</b>	74W
<b>Voltage</b>	AC 100-240V (universal), 50-60Hz
<b>Stand-by</b>	0.5W
<b>Power Supply</b>	Internal
<b>Cable Organization</b>	No
<b>Kensington Lock Slot</b>	1
<b>Physical Controls</b>	1,2,3,4,5,6 (Power)
<b>On Screen Display</b>	Input Select, Audio Adjust, ViewMode, Color Adjust, Manual Image Adjust, Setup Menu
<b>Temperature</b>	32-104° F (0 - 40° C)
<b>Humidity (non-condensing)</b>	20-90%
<b>VESA Compatible</b>	100 x 100 mm
<b>Frequency Horizontal</b>	HDMI (v1.4): 15 ~ 90 KHz, DisplayPort: 15 ~ 90 KHz, USB-C: 15 ~ 90 KHz
<b>Frequency Vertical</b>	HDMI (v1.4): 49 ~ 75 Hz, DisplayPort: 49 ~ 75 Hz, USB-C: 49 ~ 75 Hz
<b>Height Adjust</b>	130 mm / 5.1 in
<b>Swivel</b>	120°
<b>Pivot (Right/Left)</b>	90° / 90°
<b>Tilt (Forward/Back)</b>	5° / 40°

<b>Regulations</b>	cTUVus, FCC-B, ICES003, Energy Star 8.0, EPEAT Silver, CEC, MX-CoC, Mexico Energy
<b>Net (lbs)</b>	16.7
<b>Net Without Stand (lbs)</b>	11.6
<b>Gross (lbs)</b>	23.5
<b>Net (kg)</b>	7.6
<b>Net Without Stand (kg)</b>	5.3
<b>Gross (kg)</b>	10.7
<b>Packaging (in.)</b>	27.2 x 16.9 x 8.6
<b>Physical (in.)</b>	24.1 x 15.99~20.99 x 8.0
<b>Physical Without Stand (in.)</b>	24.1 x 14.2 x 2.0
<b>Packaging (mm)</b>	692 x 430 x 218
<b>Physical (mm)</b>	612 x 406.19~533.24 x 202
<b>Physical Without Stand (mm)</b>	612 x 362 x 52
<b>Package Contents</b>	VG2756a-2K-S Display, Power Cable, DP to DP Cable, USB Type C cable, USB A/B Cable, Quick Start Guide
<b>Recycle/Disposal</b>	Please dispose of in accordance with local, state or federal laws.
<b>Warranty</b>	*Refurbished. 30-day DOA policy for full refund, with a 90-day repair warranty on parts and labor.

UPC: 766907024487



### Contact Sales

[ViewSonic.com](http://ViewSonic.com)

888.881.8781

email: [salesinfo@viewsonic.com](mailto:salesinfo@viewsonic.com)