


LDS138-151 - 138" ALL-IN-ONE MOBILE DIRECT VIEW LED DISPLAY

Key Features


- Easy Setup in Just Minutes
- Mounted on Motorized Stand and Packed in Custom Flight Case For Easy Transport
- Durable and Reliable Design
- User-Friendly Integrated Control Bar
- Hot-Swappable LED Modules



138
DISPLAY



PANEL



1920x1080
RESOLUTION



Product Description

The ViewSonic® LDS138-151 is an all-in-one commercial Direct View LED display that brings big-screen visuals to high-end venues like boardrooms, auditoriums, and more. This mobile LED display is easy to transport and set up thanks to an innovative 138" foldable screen pre-assembled in a protective flight case. What truly sets this display apart is a patent-pending hinge design that stands up to heavy usage. Unlike standard foldable displays, this patent-pending hinge design provides smoother operation when folding and unfolding the screen. In addition, Glue-on-Board (GOB) technology helps protect against impacts, dust, and moisture. A commercial-grade motorized stand ensures smooth, stable height adjustment, while versatile connectivity options guarantee seamless compatibility with various devices. With 600-nit brightness, a 6,500:1 contrast ratio, and dual 30W speakers, this large format LED display delivers vivid visuals and immersive sound for an exceptional viewing experience.

Specifications

UPC	766907031386
OS	Android 9.0
GPU	ARM Mali-T860MP4
CPU	RK3399
Memory	4GB DDR4
Storage	Total 32GB (26GB available storage)
Internal Speakers	30W x 2
PC Resolution (max)	1920x1080
Mac® Resolution (max)	1920x1080
HDMI 2.0 (with HDCP 2.2)	4
HDMI 1.4 Out (with HDCP 1.4)	1
3.5mm Audio Out	2
SPDIF	1
USB 3.0	1
USB 2.0	2
USB Type C	1 (data only)
RS232	1
Ethernet LAN (RJ45)	2
IR in	1
Intel® OPS Slot In (80-pin)	1
Voltage	100-120V+/- 10%, 50/60Hz, 20A
Consumption (max)	1,745W
Consumption (typical)	581W
Stand-by	<0.5W
On Screen Display	Yes
Remote Control	Yes
Temperature	32-104° F (0 - 40° C)
Humidity (non-condensing)	20-80%
Net (lbs)	511
Gross (lbs)	919
Net (kg)	250
Gross (kg)	417
Packaging (in.)	81.5x78.6x33.4 inches
Physical (in.)	62.2x76.7x30.7in(min) 120.6x102.3x30.7in(max)
Packaging (mm)	2070x1996x847 mm
Physical (mm)	1850.81x1948.4x780mm(min.) 3064x2598x780 mm(max.)

Warranty	3-year limited warranty on parts and labor, on-site service
Recycle/Disposal	Please dispose of in accordance with local, state or federal laws.
Package Contents	Power Cord, Remote Control, QSG, LD-MK-004 x 1, LD-MK-006 x 1, LAN Cable (Cat 5E) x 1, IR Extender Cable x 1
Regulations	cTUVus, FCC, RoHS
Wifi	2.4G/5G Hz
Display Type	Direct View LED
Screen Size	138
Viewable Area (in.)	138
Orientation	Landscape
Light Source	Fine Pixel Pitch LED
LED Pitch Size (mm)	1.588
LED Grayscale	13 bits
Display Resolution	1920 x 1080
Refresh Rate	3,840Hz
Aspect Ratio	16:9
Static Contrast Ratio	6,500:1
Backlight Life (Hours)	100,000
Brightness	600 nits (100 levels adjustable)
Viewing Angles	170° horizontal, 170° vertical

UPC: 766907031386



Contact Sales
ViewSonic.com

888.881.8781
 email:
salesinfo@viewsonic.com