

PRODUCT REFERENCE GUIDE:

# PROJECTORS

Own the room every time.



## PA - Value Series: Advanced Features, Affordable Price

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PA502S	DLP Lamp	SVGA (800x600)	800 x 600	3,500 ANSI lm 22,000:1	4:3	1.97 ~ 2.17	1.1x optical zoom	USB Type A (5V 2A) , Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In, Composite RCA Video In, RGB Input
PA502X	DLP Lamp	XGA (1024x768)	1024 x 768	3,500 ANSI lm 22,000:1	4:3	1.97 ~ 2.17	1.1x optical zoom	USB Type A (5V 2A) , Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In, Composite RCA Video In, RGB Input
PA503S	DLP Lamp	SVGA (800x600)	800 x 600	3,600 ANSI lm 22,000:1	4:3	1.96 ~ 2.15	1.1x optical zoom	Mini USB Type B, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In
PA503W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,600 ANSI lm 22,000:1	16:10	1.55~1.70	1.1x optical zoom	3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PA503X	DLP Lamp	XGA (1024x768)	1024 x 768	3,600 ANSI lm 22,000:1	4:3	1.96 ~ 2.15	1.1x optical zoom	Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In
PA505W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	1.5-1.7	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB

# PG - Business/Education Series: Boardroom & Classroom Projection

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PG603W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,600 ANSI lm 22,000:1	16:10	1.55-1.70	1.1x optical zoom	USB 2.0 Type A(x2), USB Reader, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI, VGA In, VGA Out, Composite RCA Video In, Mini USB, PJ-WPD-200 (Optional)
PG603X	DLP Lamp	XGA (1024x768)	1024 x 768	3,600 ANSI lm 22,000:1	4:3	1.96-2.15	1.1x optical zoom	USB 2.0 Type A(x2), USB Reader, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI, VGA In, VGA Out, Composite RCA Video In, Mini USB, PJ-WPD-200 (Optional)
PG700WU	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	3,500 ANSI lm 12,000:1	16:10	1.5 - 1.7	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In, VGA Out, Mini USB
PG701WU	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	3,500 ANSI lm	16:10	1.5-1.65	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4)
PG703W	DLP Lamp	WXGA (1280x800)	1280 x 800	4,000 ANSI lm 22,000:1	16:10	1.55~1.70	1.1x optical zoom	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, HDMI MHL, VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB, 3D VESA
PG703X	DLP Lamp	XGA (1024x768)	1024 x 768	4,000 ANSI lm 22,000:1	16:10	1.96~2.15	1.1x optical zoom	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, HDMI MHL, VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB
PG705HD	DLP Lamp	HD (1920x1080)	1920 x 1080	4,000 ANSI lm 12,000:1	16:9	1.5 - 1.8	1.2x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB
PG705WU	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	4,000 ANSI lm 12,000:1	16:10	1.49-1.76	1.2x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB
PG706HD	DLP Lamp	HD (1920x1080)	1920 x 1080	4,000 ANSI lm	16:9	1.5-1.65	1.1x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In, VGA Out, Composite RCA Video In, S-Video In
PG706WU	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	4,000 ANSI lm 12,000:1	16:10	1.5-1.65	1.1x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In, VGA Out, Composite RCA Video In, S-Video In
PG800HD	DLP Lamp	HD (1920x1080)	1920 x 1080	5,000 ANSI lm 5,000:1	16:9	1.15-1.5	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In(x2), Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R), 3D VESA, IR out
PG800W	DLP Lamp	WXGA (1280x800)	1280 x 800	5,000 ANSI lm 5,000:1	16:10	1.2 - 1.6	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In(x2), Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R), 3D VESA, IR out

# PX - Home Theater (1080p) Series: True Cinema Experience

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PX700HD	DLP Lamp	HD (1920x1080)	1920 x 1080	3,500 ANSI lm 12,000:1	16:9	1.5 - 1.65	1.1x optical zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Mini USB
PX706HD	DLP Lamp	HD (1920x1080)	1920 x 1080	3,000 ANSI lm 22,000:1	16:9	0.69-0.83	1.2x optical zoom	USB 3.1 Type C, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In, Composite RCA Video In, Mini USB
PX725HD	DLP Lamp	HD (1920x1080)	1920 x 1080	2,000 ANSI lm 22,000:1	16:9	1.5~1.65	1.1x Manual optical zoom / manual optical focus	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In, Composite RCA Video In, Mini USB, RCA Audio In (L/R)
PX727-4K	DLP Lamp	4K (3840x2160)	3840 x 2160	2,200 ANSI lm 12,000:1	16:9	1.5 - 1.8	1.2x optical zoom	USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, Mini USB
PX747-4K	DLP Lamp	4K (3840x2160)	3840 x 2160	3,500 ANSI lm 12,000:1	16:9	1.47 - 1.76	1.2x optical zoom	USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, Mini USB
PX800HD	DLP Lamp	HD (1920x1080)	1920 x 1080	2,000 ANSI lm 100,000:1	16:9	0.23	Manual optical focus	USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In(x2), Control (RS232), HDMI 1.4(x2), HDMI 1.4/MHL 2.0, Composite RCA Video In, RGB Input(x2)

# PS - Ultra Short Throw (Interactive) Series: Big Images Anywhere

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PS501W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	0.49	Fixed Zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PS501X	DLP Lamp	XGA (1024x768)	1024 x 768	3,500 ANSI lm 22,000:1	4:3	0.61	Fixed Zoom	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PS600W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	0.5	Fixed Zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PS600X	DLP Lamp	XGA (1024x768)	1024 x 768	3,500 ANSI lm 22,000:1	4:3	0.6	Fixed Zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
PS700W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,300 ANSI lm	16:10	0.23	Fixed Zoom	USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), HDMI 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R)
PS700X	DLP Lamp	XGA (1024x768)	1024 x 768	3,300 ANSI lm 10,000:1	4:3	0.29	Fixed Zoom	USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), HDMI 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R)

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PS750HD	DLP Lamp	HD (1920x1080)	1920 x 1080	3,300 ANSI lm 10,000:1	16:9	0.22	Manual optical focus	USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, RS232 Out, HDMI, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB(x2), RCA Audio In (L/R)
PS750W	DLP Lamp	WXGA (1280x800)	1280 x 800	3,300 ANSI lm 10,000:1	16:10	0.23	Manual optical focus	USB 2.0 Type A, USB Type A (5V 2A) , Mini USB Type B(x2), Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4/MHL 2.0, VGA Out, Composite RCA Video In, S-Video In, RCA Audio In (L/R), RGB Input(x2)

## LS - Laser Series: Long-Lasting Laser Projection

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
LS620X	DLP Laser	XGA (1024x768)	1024 x 768	3,200 ANSI lm 100,000:1	4:3	0.61	Digital optical focus	USB Type A (5V 2A) , Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, HDMI 1.4/MHL 2.0, VGA Out, RGB Input(x2)
LS625W	DLP Laser	WXGA (1280x800)	1280 x 800	3,200 ANSI lm 100,000:1	16:10	0.52	Fixed Zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4)(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB
LS625X	DLP Lamp	XGA (1024x768)	1024 x 768	3,200 ANSI lm	4:3	0.49	Fixed Zoom	Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB
LS700-4K	DLP Laser	4K (3840x2160)	3840 x 2160	3,300 ANSI lm 3,000,000:1	16:9	1.13~1.47	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB
LS700HD	DLP Laser	HD (1920x1080)	1920 x 1080	3,500 ANSI lm 3,000,000:1	16:9	1.13~1.47	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Video In, Mini USB
LS800HD	DLP Laser	HD (1920x1080)	1920 x 1080	5,000 ANSI lm 100,000:1	16:9	1.2-1.9	1.65x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT
LS800WU	DLP Laser	WUXGA (1920x1200)	1920 x 1200	5,500 ANSI lm 100,000:1	16:10	1.2 - 1.9	1.65x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT
LS810	DLP Laser	WXGA (1280x800)	1280 x 800	5,200 ANSI lm 100,000:1	16:10	0.23	Digital optical focus	USB 2.0 Type A, USB Type A (5V 2A) , Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, Mini USB, Micro USB
LS820	DLP Laser	HD (1920x1080)	1920 x 1080	3,500 ANSI lm 100,000:1	16:9	0.23	Digital optical focus	USB 2.0 Type A, USB Type A (5V 2A) , USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, S-Video In, Mini USB, Micro USB, RCA Audio In (L/R), 3D VESA, RGB Input(x2)

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
LS830	DLP Laser	HD (1920x1080)	1920 x 1080	4,500 ANSI lm 100,000:1	16:9	0.23	Digital optical focus	USB 2.0 Type A, USB Type A (5V 2A) , USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, Mini USB, Micro USB, 3D VESA, RGB Input(x2)
LS850WU	DLP Laser	WUXGA (1920x1200)	1920 x 1200	5,000 ANSI lm 3,000,000:1	16:10	1.36 - 2.18	1.6x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R), 3D VESA
LS900WU	DLP Laser	WUXGA (1920x1200)	1920 x 1200	6,000 ANSI lm 100,000:1	16:10	1.2 - 1.9	1.65x optical zoom	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT

## Pro Series: Bright & Versatile for Pro Installations

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PRO10100	DLP Lamp	XGA (1024x768)	1024 x 768	6,000 ANSI lm 4,400:1	4:3 (native)	1.26-1.28	Lens sold separately	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI, VGA In, VGA Out, Composite RCA Video In, 15-pin mini D-sub
PRO10100-SD	-	XGA (1024x768)	1024 x 768	6,000 ANSI lm	4:3 (native)	LEN-009: 1.26 - 1.58	-	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI, VGA In, VGA Out, Composite RCA Video In, 15-pin mini D-sub
PRO7827HD	DLP Lamp	HD (1920x1080)	1920 x 1080	2,200 ANSI lm 22,000:1	16:9	1.1~1.5	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4, HDMI MHL(x2), Composite RCA Video In, Mini USB, Micro USB, 15-pin mini D-Sub (x1)
PRO8510L	DLP Lamp	XGA (1024x768)	1024 x 768	5,200 ANSI lm	4:3 (native)	1.41 ~ 2.25	1.6x Manual optical zoom / manual optical focus	USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4(x3), HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, Micro USB
PRO8530HDL	DLP Lamp	HD (1920x1080)	1920 x 1080	5,200 ANSI lm	16:9	1.07~1.71:1	1.6x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4(x3), VGA In, VGA Out, Micro USB
PRO8800WUL	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	5,200 ANSI lm	16:10	1.07~1.71:1	1.6x Manual optical zoom / manual optical focus	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4(x3), HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Micro USB, 3D VESA, Wired Remote Out, 5-BNC
PRO9510L	DLP Lamp	XGA (1024x768)	1024 x 768	6,200 ANSI lm 8,000:1	4:3	1.3 - 2.21:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC
PRO9520WL	DLP Lamp	WXGA (1280x800)	1280 x 800	5,200 ANSI lm 8,000:1	16:10	1.32 - 2.24:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PRO9800WUL	DLP Lamp	WUXGA (1920x1200)	1920 x 1200	5,500 ANSI lm 15,000:1	16:10	1.25 - 2.13:1	1.7x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC

## PJD7 - Multimedia Series: Immersive Multimedia

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PJD7828HDL	DLP Lamp	HD (1920x1080)	1920 x 1080	3,200 ANSI lm	16:9	1.15~1.5	1.3x Manual optical zoom / manual optical focus	USB 2.0 Type A, USB Micro B (5V 2A) , 3.5mm Audio Out, 3.5mm Audio In, 3.5mm Mic In, HDMI 1.4, HDMI MHL, VGA Out, Composite RCA Video In, S-Video In, 15-pin mini D-Sub (x1)

## PJD6 - Networkable Series: Facility-wide Control

Product	Type	Resolution Type	Resolution	Brightness / Contrast	Aspect Ratio	Throw Ratio	Lens	Connectivity
PJD6352	DLP Lamp	XGA (1024x768)	1024 x 768	22,000:1	4:3 (native)	1.51-1.97	1.3x Manual optical zoom / manual optical focus	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI, HDMI 1.4, HDMI MHL, Composite RCA Video In, Mini USB
PJD6552LW	DLP Lamp	WXGA (1280x800)	1280 x 800	3,500 ANSI lm 22,000:1	16:10	1.21~1.57	1.3x Manual optical zoom / manual optical focus	Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2)