

PRODUCT REFERENCE GUIDE:

# PROJECTORS

Own the room every time.



## PA - Value Series: Advanced Features, Affordable Price

| Product | Type     | Resolution Type | Resolution | Brightness / Contrast     | Aspect Ratio | Throw Ratio | Lens              | Connectivity  |
|---------|----------|-----------------|------------|---------------------------|--------------|-------------|-------------------|---|
| PA502S  | DLP Lamp | SVGA (800x600)  | 800 x 600  | 3,500 ANSI lm<br>22,000:1 | 4:3          | 1.97 ~ 2.17 | 1.1x optical zoom | Mini USB Type B, Control (RS232), HDMI 1.4, VGA In, Composite RCA Video In, RGB Input   |
| PA502X  | DLP Lamp | XGA (1024x768)  | 1024 x 768 | 3,500 ANSI lm<br>22,000:1 | 4:3          | 1.97 ~ 2.17 | 1.1x optical zoom | Mini USB Type B, Control (RS232), HDMI 1.4, VGA In, Composite RCA Video In, RGB Input   |
| PA503S  | DLP Lamp | SVGA (800x600)  | 800 x 600  | 3,600 ANSI lm<br>22,000:1 | 4:3          | 1.96 ~ 2.15 | 1.1x optical zoom | Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In |
| PA503W  | DLP Lamp | WXGA (1280x800) | 1280 x 800 | 3,600 ANSI lm<br>22,000:1 | 16:10        | 1.55~1.70   | 1.1x optical zoom | 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB                     |
| PA503X  | DLP Lamp | XGA (1024x768)  | 1024 x 768 | 3,600 ANSI lm<br>22,000:1 | 4:3          | 1.96 ~ 2.15 | 1.1x optical zoom | Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In |
| PA505W  | DLP Lamp | WXGA (1280x800) | 1280 x 800 | 3,500 ANSI lm<br>22,000:1 | 16:10        | 1.5-1.7     | 1.1x optical zoom | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB |

# PG - Business/Education Series: Boardroom & Classroom Projection

| Product | Type     | Resolution Type      | Resolution  | Brightness / Contrast     | Aspect Ratio | Throw Ratio | Lens  | Connectivity   |
|---------|----------|----------------------|-------------|---------------------------|--------------|-------------|---|--|
| PG603W  | DLP Lamp | WXGA (1280x800)      | 1280 x 800  | 3,600 ANSI lm<br>22,000:1 | 16:10        | 1.55-1.70   | 1.1x optical zoom                               | USB 2.0 Type A(x2), USB Reader, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI, VGA In, VGA Out, Composite RCA Video In, Mini USB, PJ-WPD-200 (Optional)   |
| PG603X  | DLP Lamp | XGA (1024x768)       | 1024 x 768  | 3,600 ANSI lm<br>22,000:1 | 4:3          | 1.96-2.15   | 1.1x optical zoom                               | USB 2.0 Type A(x2), USB Reader, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI, VGA In, VGA Out, Composite RCA Video In, Mini USB, PJ-WPD-200 (Optional)   |
| PG700WU | DLP Lamp | WUXGA<br>(1920x1200) | 1920 x 1200 | 3,500 ANSI lm<br>12,000:1 | 16:10        | 1.5 - 1.7   | 1.1x optical zoom                               | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In, VGA Out, Mini USB  |
| PG703W  | DLP Lamp | WXGA (1280x800)      | 1280 x 800  | 4,000 ANSI lm<br>22,000:1 | 16:10        | 1.55~1.70   | 1.1x optical zoom                               | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, HDMI MHL, VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB, 3D VESA  |
| PG703X  | DLP Lamp | XGA (1024x768)       | 1024 x 768  | 4,000 ANSI lm<br>22,000:1 | 16:10        | 1.96~2.15   | 1.1x optical zoom                               | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI, HDMI MHL, VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB   |
| PG705HD | DLP Lamp | HD (1920x1080)       | 1920 x 1080 | 4,000 ANSI lm<br>12,000:1 | 16:9         | 1.5 - 1.8   | 1.2x Manual optical zoom / manual optical focus | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB   |
| PG705WU | DLP Lamp | WUXGA<br>(1920x1200) | 1920 x 1200 | 4,000 ANSI lm<br>12,000:1 | 16:10        | 1.49-1.76   | 1.2x Manual optical zoom / manual optical focus | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Composite RCA Video In, S-Video In, Mini USB   |
| PG800HD | DLP Lamp | HD (1920x1080)       | 1920 x 1080 | 5,000 ANSI lm<br>5,000:1  | 16:9         | 1.15-1.5    | 1.3x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In(x2), Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R), 3D VESA, IR out |
| PG800W  | DLP Lamp | WXGA (1280x800)      | 1280 x 800  | 5,000 ANSI lm<br>5,000:1  | 16:10        | 1.2 - 1.6   | 1.3x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In(x2), Control (RS232), HDMI(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R), 3D VESA, IR out |

# PX - Home Theater (1080p) Series: True Cinema Experience

| Product | Type     | Resolution Type | Resolution  | Brightness / Contrast     | Aspect Ratio | Throw Ratio | Lens              | Connectivity   |
|---------|----------|-----------------|-------------|---------------------------|--------------|-------------|-------------------|--|
| PX700HD | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 3,500 ANSI lm<br>12,000:1 | 16:9         | 1.5 - 1.65  | 1.1x optical zoom | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), VGA In, VGA Out, Mini USB                    |
| PX706HD | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 3,000 ANSI lm<br>22,000:1 | 16:9         | 0.69-0.83   | 1.2x optical zoom | USB 3.1 Type C, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In, Composite RCA Video In, Mini USB |

| Product  | Type     | Resolution Type | Resolution  | Brightness / Contrast      | Aspect Ratio | Throw Ratio | Lens  | Connectivity  |
|----------|----------|-----------------|-------------|----------------------------|--------------|-------------|---|---|
| PX725HD  | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 2,000 ANSI lm<br>22,000:1  | 16:9         | 1.5~1.65    | 1.1x Manual optical zoom / manual optical focus | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI 1.4, HDMI 1.4 (with HDCP 1.4), VGA In, Composite RCA Video In, Mini USB, RCA Audio In (L/R)         |
| PX727-4K | DLP Lamp | 4K (3840x2160)  | 3840 x 2160 | 2,200 ANSI lm<br>12,000:1  | 16:9         | 1.5 - 1.8   | 1.2x optical zoom                               | USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, VGA Out, Mini USB          |
| PX747-4K | DLP Lamp | 4K (3840x2160)  | 3840 x 2160 | 3,500 ANSI lm<br>12,000:1  | 16:9         | 1.47 - 1.76 | 1.2x optical zoom                               | USB 2.0 Type A, 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4), HDMI 2.0 (with HDCP 2.2), VGA In, Mini USB                   |
| PX800HD  | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 2,000 ANSI lm<br>100,000:1 | 16:9         | 0.23        | Manual optical focus                            | USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), 3.5mm Audio In(x2), Control (RS232), HDMI 1.4(x2), HDMI 1.4/MHL 2.0, Composite RCA Video In, RGB Input(x2) |

## PS - Ultra Short Throw (Interactive) Series: Big Images Anywhere

| Product | Type     | Resolution Type | Resolution  | Brightness / Contrast  | Aspect Ratio | Throw Ratio | Lens                 | Connectivity   |
|---------|----------|-----------------|-------------|------------------------|--------------|-------------|----------------------|--|
| PS501W  | DLP Lamp | WXGA (1280x800) | 1280 x 800  | 3,500 ANSI lm 22,000:1 | 16:10        | 0.49        | Fixed Zoom           | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB  |
| PS501X  | DLP Lamp | XGA (1024x768)  | 1024 x 768  | 3,500 ANSI lm 22,000:1 | 4:3          | 0.61        | Fixed Zoom           | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB  |
| PS600W  | DLP Lamp | WXGA (1280x800) | 1280 x 800  | 3,500 ANSI lm 22,000:1 | 16:10        | 0.5         | Fixed Zoom           | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB   |
| PS600X  | DLP Lamp | XGA (1024x768)  | 1024 x 768  | 3,500 ANSI lm 22,000:1 | 4:3          | 0.6         | Fixed Zoom           | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4(x2), VGA In(x2), VGA Out, Composite RCA Video In, Mini USB   |
| PS700W  | DLP Lamp | WXGA (1280x800) | 1280 x 800  | 3,300 ANSI lm          | 16:10        | 0.23        | Fixed Zoom           | USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), HDMI 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R)                                 |
| PS700X  | DLP Lamp | XGA (1024x768)  | 1024 x 768  | 3,300 ANSI lm 10,000:1 | 4:3          | 0.29        | Fixed Zoom           | USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x2), HDMI 1.4 (with HDCP 1.4), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB, RCA Audio In (L/R)                                 |
| PS750HD | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 3,300 ANSI lm 10,000:1 | 16:9         | 0.22        | Manual optical focus | USB 2.0 Type A(x2), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, RS232 Out, HDMI, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB(x2), RCA Audio In (L/R)   |
| PS750W  | DLP Lamp | WXGA (1280x800) | 1280 x 800  | 3,300 ANSI lm 10,000:1 | 16:10        | 0.23        | Manual optical focus | USB 2.0 Type A, USB Type A (5V 2A) , Mini USB Type B(x2), Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI 1.4/MHL 2.0, VGA Out, Composite RCA Video In, S-Video In, RCA Audio In (L/R), RGB Input(x2) |

# PLED/M Portable Series: Compact Designs

| Product | Type    | Resolution Type | Resolution | Brightness / Contrast | Aspect Ratio | Throw Ratio | Lens       | Connectivity  |
|---------|---------|-----------------|------------|-----------------------|--------------|-------------|------------|---|
| M1      | DLP LED | WVGA (854x480)  | 854 x 480  | 250 lm 120,000:1      | 16:9         | 1.2         | Fixed Zoom | USB 2.0 Type A, USB 3.1 Type C, Micro SD, 3.5mm Audio Out, HDMI 1.4 |

# LS - Laser Series: Long-Lasting Laser Projection

| Product | Type      | Resolution Type   | Resolution  | Brightness / Contrast   | Aspect Ratio | Throw Ratio | Lens                  | Connectivity  |
|---------|-----------|-------------------|-------------|-------------------------|--------------|-------------|-----------------------|---|
| LS620X  | DLP Laser | XGA (1024x768)    | 1024 x 768  | 3,200 ANSI lm 100,000:1 | 4:3          | 0.61        | Digital optical focus | USB Type A (5V 2A) , Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio In, HDMI 1.4/MHL 2.0, VGA Out, RGB Input(x2)  |
| LS625W  | DLP Laser | WXGA (1280x800)   | 1280 x 800  | 3,200 ANSI lm 100,000:1 | 16:10        | 0.52        | Fixed Zoom            | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4 (with HDCP 1.4)(x2), VGA In(x2), VGA Out, Composite RCA Video In, S-Video In, Mini USB   |
| LS800HD | DLP Laser | HD (1920x1080)    | 1920 x 1080 | 5,000 ANSI lm 100,000:1 | 16:9         | 1.2-1.9     | 1.65x optical zoom    | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS-232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT   |
| LS800WU | DLP Laser | WUXGA (1920x1200) | 1920 x 1200 | 5,500 ANSI lm 100,000:1 | 16:10        | 1.2 - 1.9   | 1.65x optical zoom    | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI(x3), VGA In, VGA Out, Composite RCA Video In, Mini USB, RCA Audio In (L/R), RCA Audio Out, 3D VESA, HDBT  |
| LS810   | DLP Laser | WXGA (1280x800)   | 1280 x 800  | 5,200 ANSI lm 100,000:1 | 16:10        | 0.23        | Digital optical focus | USB 2.0 Type A, USB Type A (5V 2A) , Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, Mini USB, Micro USB   |
| LS820   | DLP Laser | HD (1920x1080)    | 1920 x 1080 | 3,500 ANSI lm 100,000:1 | 16:9         | 0.23        | Digital optical focus | USB 2.0 Type A, USB Type A (5V 2A) , USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm 12V Trigger, 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, S-Video In, Mini USB, Micro USB, RCA Audio In (L/R), 3D VESA, RGB Input(x2) |
| LS830   | DLP Laser | HD (1920x1080)    | 1920 x 1080 | 4,500 ANSI lm 100,000:1 | 16:9         | 0.23        | Digital optical focus | USB 2.0 Type A, USB Type A (5V 2A) , USB Micro B (5V 2A) , Mini USB Type B, Audio Output (Mini Jack), Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, Control (RS232), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Component RCA, Mini USB, Micro USB, 3D VESA, RGB Input(x2)  |

# Pro Series: Bright & Versatile for Pro Installations

| Product     | Type     | Resolution Type   | Resolution  | Brightness / Contrast     | Aspect Ratio    | Throw Ratio          | Lens  | Connectivity  |
|-------------|----------|-------------------|-------------|---------------------------|-----------------|----------------------|---|---|
| PRO10100    | DLP Lamp | XGA (1024x768)    | 1024 x 768  | 6,000 ANSI lm<br>4,400:1  | 4:3<br>(native) | 1.26-1.28            | Lens sold separately                            | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI, VGA In, VGA Out, Composite RCA Video In, 15-pin mini D-sub  |
| PRO10100-SD | -        | XGA (1024x768)    | 1024 x 768  | 6,000 ANSI lm             | 4:3<br>(native) | LEN-009: 1.26 - 1.58 | -   | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI, VGA In, VGA Out, Composite RCA Video In, 15-pin mini D-sub  |
| PRO7827HD   | DLP Lamp | HD (1920x1080)    | 1920 x 1080 | 2,200 ANSI lm<br>22,000:1 | 16:9            | 1.1~1.5              | 1.3x Manual optical zoom / manual optical focus | USB 2.0 Type A, 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4, HDMI MHL(x2), Composite RCA Video In, Mini USB, Micro USB, 15-pin mini D-Sub (x1)  |
| PRO8510L    | DLP Lamp | XGA (1024x768)    | 1024 x 768  | 5,200 ANSI lm             | 4:3<br>(native) | 1.41 ~ 2.25          | 1.6x Manual optical zoom / manual optical focus | USB 2.0 Type A, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4(x3), HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, Micro USB  |
| PRO8530HDL  | DLP Lamp | HD (1920x1080)    | 1920 x 1080 | 5,200 ANSI lm             | 16:9            | 1.07~1.71:1          | 1.6x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4(x3), VGA In, VGA Out, Micro USB  |
| PRO8800WUL  | DLP Lamp | WUXGA (1920x1200) | 1920 x 1200 | 5,200 ANSI lm             | 16:10           | 1.07~1.71:1          | 1.6x Manual optical zoom / manual optical focus | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4(x3), HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Micro USB, 3D VESA, Wired Remote Out, 5-BNC   |
| PRO9510L    | DLP Lamp | XGA (1024x768)    | 1024 x 768  | 6,200 ANSI lm<br>8,000:1  | 4:3             | 1.3 - 2.21:1         | 1.7x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC |
| PRO9520WL   | DLP Lamp | WXGA (1280x800)   | 1280 x 800  | 5,200 ANSI lm<br>8,000:1  | 16:10           | 1.32 - 2.24:1        | 1.7x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC |
| PRO9800WUL  | DLP Lamp | WUXGA (1920x1200) | 1920 x 1200 | 5,500 ANSI lm<br>15,000:1 | 16:10           | 1.25 - 2.13:1        | 1.7x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB 2.0 Type B, Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x3), Control (RS232), HDMI 1.4, HDMI MHL, DVI-D, VGA In(x2), VGA Out, Composite RCA Video In, RCA Audio Out, 3D VESA, Wired Remote In, Wired Remote Out, 5-BNC |

## PJD7 - Multimedia Series: Immersive Multimedia

| Product    | Type     | Resolution Type | Resolution  | Brightness / Contrast     | Aspect Ratio | Throw Ratio | Lens  | Connectivity   |
|------------|----------|-----------------|-------------|---------------------------|--------------|-------------|---|--|
| PJD7720HD  | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 3,200 ANSI lm<br>22,000:1 | 16:9         | 1.49~1.64:1 | 1.1x Manual optical zoom / manual optical focus | 3.5mm Audio Out, 3.5mm Audio In, HDMI 1.4, HDMI MHL, Mini USB  |
| PJD7828HDL | DLP Lamp | HD (1920x1080)  | 1920 x 1080 | 3,200 ANSI lm             | 16:9         | 1.15~1.5    | 1.3x Manual optical zoom / manual optical focus | USB 2.0 Type A, USB Micro B (5V 2A) , 3.5mm Audio Out, 3.5mm Audio In, 3.5mm Mic In, HDMI 1.4, HDMI MHL, VGA Out, Composite RCA Video In, S-Video In, 15-pin mini D-Sub (x1) |

## PJD6 - Networkable Series: Facility-wide Control

| Product    | Type     | Resolution Type | Resolution | Brightness / Contrast     | Aspect Ratio          | Throw Ratio | Lens  | Connectivity  |
|------------|----------|-----------------|------------|---------------------------|-----------------------|-------------|---|---|
| PJD6352    | DLP Lamp | XGA (1024x768)  | 1024 x 768 | 22,000:1                  | 4:3 (native)          | 1.51-1.97   | 1.3x Manual optical zoom / manual optical focus | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI, HDMI 1.4, HDMI MHL, Composite RCA Video In, Mini USB  |
| PJD6352LS  | DLP Lamp | XGA (1024x768)  | 1024 x 768 | 3,500 ANSI lm<br>22,000:1 | 4:3 (native),<br>16:9 | 0.61        | Fixed zoom / manual optical focus               | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2)     |
| PJD6552LW  | DLP Lamp | WXGA (1280x800) | 1280 x 800 | 3,500 ANSI lm<br>22,000:1 | 16:10                 | 1.21~1.57   | 1.3x Manual optical zoom / manual optical focus | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In(x2), HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2) |
| PJD6552LWS | DLP Lamp | WXGA (1280x800) | 1280 x 800 | 3,500 ANSI lm<br>22,000:1 | 16:10                 | 0.49        | Fixed zoom / manual optical focus               | Ethernet LAN (RJ45), 3.5mm Audio Out, 3.5mm Audio In, HDMI 1.4, HDMI MHL, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2)     |

## PJD5 - Everyday Series: Multipurpose Projection

| Product    | Type     | Resolution Type | Resolution | Brightness / Contrast     | Aspect Ratio | Throw Ratio | Lens                              | Connectivity   |
|------------|----------|-----------------|------------|---------------------------|--------------|-------------|-----------------------------------|--|
| PJD5553LWS | DLP Lamp | WXGA (1280x800) | 1280 x 800 | 3,200 ANSI lm<br>20,000:1 | 16:10        | 0.49        | Fixed zoom / manual optical focus | 3.5mm Audio Out, 3.5mm Audio In, HDMI 1.4, VGA In(x2), VGA Out, Composite RCA Video In, Mini USB, 15-pin mini D-Sub (x2) |